

NORTH 1/4 CORNER SECTION 22, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 315 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-17-11 ON DECEMBER 27, 1856.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.90 CHAINS WEST TO THE 20" X 18" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22
 - 2) 39.90 CHAINS EAST TO THE 21" X 12" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 31, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 212 DATED AUGUST 12, 1901 BY THE ORDER OF W. E. DAVIS TO SURVEY SECTION 22-17-11, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 22-17-11 ON LINE AND MIDWAY BETWEEN THE GOVERNMENT STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11 AND THE LOCATION OF THE NORTHEAST CORNER OF SECTION 22-17-11, AS LOCATED BY THE AFFIDAVIT OF J. H. OGLESBY, ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,633' WEST TO THE GOVERNMENT STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11
 - 2) 1,316.5' EAST TO THE 3" X 6" X 10" STONE HE SET FOR THE PERMANENT NORTH 1/8TH CORNER OF THE NE1/4 OF SECTION 22-18-11
 - 3) 2,633' EAST TO THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 22-18-11, AS LOCATED BY THE AFFIDAVIT OF J. H. OGLESBY

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER 1/4 CORNER OF SECTION 15-17-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 26, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 48, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 229 DATED APRIL 22, 1902 FOR A ROAD BETWEEN SECTIONS 15 & 22-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 22-17-11 ON THIS ROAD SURVEY FOR A ROAD OF VARYING WIDTHS.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11, LAYING THE ROAD 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND, LAYING THE ROAD 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE; THEN S. 62°37' E. [ROAD 40 FEET WIDE FROM HERE TO THE END] FOR 3 CHAINS, THEN N. 87°15' E. FOR 7.00 CHAINS, THEN N. 65°53' E. FOR 3.00 CHAINS TO THE SECTION LINE, THEN EAST ON THE SECTION LINE FOR 7.52 TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-17-11 AND THERE ENDING

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 571 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 149 THROUGH PETITION BY W. E. DAVIS AND OTHERS FOR A ROAD IN TOWNSHIP 17-11 [PACKET 712 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 22, 1902 WAS GRANTED AS A 40 AND 50 FOOT WIDE, EQUAL DISTANCE ON EACH SIDE OF THE SURVEYED LINE, ON MAY 8, 1902 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JUNE 16, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 22-17-11 ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11, LAYING THE ROAD 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 1/4 OF A MILE TO THE STONE HE FOUND, LAYING THE ROAD 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE; THEN S. 62°37' E. [ROAD 40 FEET WIDE FROM HERE TO THE END] FOR 3 CHAINS, THEN N. 87°15' E. FOR 7.00 CHAINS, THEN N. 65°53' E. FOR 3.00 CHAINS TO THE SECTION LINE, THEN EAST ON THE SECTION LINE FOR 7.52 TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-17-11 AND THERE ENDING
- 6) THE KRETSINGER TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **4" X 10" X 17" LIMESTONE WITH A 1/2" X 24" REBAR UNDER THE STONE** AT THE "SE CORNER SW1/4 SECTION 15-17-11".
- 1) 21.0' NORTH TO A SPIKE & DISC IN THE TOP OF A CORNER FENCE POST
 - 2) 28.3' SSW TO A SPIKE & DISC IN THE ROOT OF AN 80" ELM
 - 3) 67.0' WNW TO A SPIKE & WASHER IN A 40" MULBERRY
 - 4) IN LINE WITH A FENCE TO THE NORTH
- 7) LLOYD J. DOBLER, L.S. 541, IN SURVEY F22001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY FOR A TRACT IN THE NORTHWEST AND NORTHEAST QUARTERS OF SECTION 22-17-11 FOR JAMES W. AND THELMA SMITH DATED MAY 8, 1878, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTH 1/4 CORNER OF SECTION 22-17-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 312.70' WEST TO THE 3/4" IRON PIN HE SET FOR THE NORTHWEST TRACT CORNER
 - 2) 158.15' EAST TO THE 3/4" IRON PIN HE SET FOR THE NORTHEAST TRACT CORNER
- 8) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 7, 2003 FOR THE J. A. DAVIS SUBDIVISION IN THE DRAWER FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE 4" X 10" X 17" LIMESTONE WITH A 1/2" REBAR ON THE SOUTH SIDE OF THE STONE, WITH THE TOP OF THE REBAR BELOW THE TOP OF THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 22-17-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. HE SAID THAT THIS STONE IS FROM A PRIOR SURVEY BY ALVA J. SMITH DATED 1901 AND RECORDED IN SURVEY BOOK "E" ON PAGE 212 IN THE COUNTY ENGINEER'S OFFICE.
- 1) 27.35' SOUTH TO A CONCRETE NAIL & SHINER IN THE ROOT OF AN 80" ELM
 - 2) 22.40' NE TO A CONCRETE NAIL & SHINER IN A BRACE POST
 - 3) 22.20' NORTH TO A 60 D SPIKE & DISC IN THE TOP OF A CORNER FENCE POST
 - 4) 40.25' NW TO A CONCRETE NAIL & SHINER IN THE TOP OF AN ELM STUMP

HIS TIES ARE CONTINUED ON PAGE 3

- 5) 4.00' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 280
- 6) IN LINE WITH A FENCE TO THE NORTH EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.20' EAST TO THE 5/8" CAPPED REBAR HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 2) 2,630.40' EAST TO THE 5/8" CAPPED REBAR HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 3) 2,653.95' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 22-17-11

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 5, 2010 FOR PROJECT NUMBER 10268-02, SURVEY F15004 IN THE SURVEY FILE FOR TOWNSHIP 17-11 TO SURVEY THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 15-17-11 FOR EMPORIA SATE BANK AND MOUNKES, SAID THAT **HE FOUND THE LIMESTONE [WITH A 1/2" REBAR ON THE SOUTH SIDE OF THE STONE, WITH TO THE TOP OF THE REBAR BELOW THE TOP OF THE STONE]** AT THE SOUTH 1/4 CORNER OF SECTION 15-17-11 FROM EXISTING REFERENCES BY A. DAVIS, L.S. 1368, IN 2003 ON FILE AT THE COUNTY ENGINEER'S OFFICE.

- 1) 22.4' NE TO A CONCRETE NAIL & SHINER IN A BRACE POST
- 2) 20.1' NORTH TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 3) 74.25' ENE TO THE NEAR FACE OF A MAIL BOX POST
- 4) 9' EAST TO THE WEST EDGE OF A HOUSE TO THE SOUTH EXTENDED
- 5) 2' NORTH TO THE CENTER TRAVELED WAY OF COUNTY ROAD 380 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,324.46' NORTH THE 5/8" REBAR WITH A LYON COUNTY HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 15-17-11
- 2) 2,648.52' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 15-17-11
- 3) 2,630.69' EAST TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 15-17-11

NORTH QUARTER CORNER 22-17-11