

**NORTH 1/16<sup>TH</sup> CORNER OF NORTHEAST 1/4 SECTION 22, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 31, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 212 DATED AUGUST 12, 1901 BY THE ORDER OF W. E. DAVIS TO SURVEY SECTION 22-17-11, SAID **HE SET A 3" X 6" X 20" STONE** FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11 AT MIDWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 22-17-11 AND THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 22-17-11, AS LOCATED BY THE AFFIDAVIT OF J. H. OGLESBY, ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,316.5' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 22-17-11
  - 2) 3,949.5' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11
  - 3) 1,316.5' EAST TO THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 22-17-11, AS LOCATED BY THE AFFIDAVIT OF J. H. OGLESBY
  
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 48, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 229 DATED APRIL 22, 1902 FOR A ROAD BETWEEN SECTIONS 15 & 22-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 22-17-11 ON THIS ROAD SURVEY FOR A ROAD OF VARYING WIDTHS.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1/4 OF A MILE, LAYING THE ROAD 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 22-17-11, THEN CONTINUES WEST ON THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11 TO BEGIN THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE
  - 2) THIS ROAD EXTENDS S. 62°37' E. [ROAD 40 FEET WIDE FROM HERE TO THE END] FOR 3 CHAINS, THEN N. 87°15' E. FOR 7.00 CHAINS, THEN N. 65°53' E. FOR 3.00 CHAINS TO THE SECTION LINE, THEN EAST ON THE SECTION LINE FOR 7.52 TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-17-11 AND THERE ENDING
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 571 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 149 THROUGH PETITION BY W. E. DAVIS AND OTHERS FOR A ROAD IN TOWNSHIP 17-11 [PACKET 712 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 22, 1902 WAS GRANTED AS A 40 AND 50 FOOT WIDE, EQUAL DISTANCE ON EACH SIDE OF THE SURVEYED LINE, ON MAY 8, 1902 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JUNE 16, 1902 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 1/4 OF A MILE, LAYING THE ROAD 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 22-17-11, THEN CONTINUES WEST ON THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11 TO BEGIN THIS

ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE

- 2) THIS ROAD EXTENDS S. 62°37' E. [ROAD 40 FEET WIDE FROM HERE TO THE END] FOR 3 CHAINS, THEN N. 87°15' E. FOR 7.00 CHAINS, THEN N. 65°53' E. FOR 3.00 CHAINS TO THE SECTION LINE, THEN EAST ON THE SECTION LINE FOR 7.52 TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 22-17-11 AND THERE ENDING
  
- 4) GREGORY A. MILES, L.S. 667, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 17, 1982, SURVEY F22002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THREE TRACTS IN THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 22-17-11 FOR LOUISE BAKER, RECORDED IN VOLUME 393 ON PAGE 939 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 21, 1982, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 667" CAP** FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11 ON LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER AND THE NORTH 1/4 CORNER OF SECTION 22-17-11. HE SAID THAT THE DISTANCE CLOSELY CHECKED WITH ALVA J. SMITH'S OFFICIAL SURVEY OF 1901, AND FIT THE FENCE TO THE SOUTH.
  - 1) 23.65' SSW TO A NAIL IN THE TOP OF A CORNER FENCE POST
  - 2) 47.62' WSW TO A NAIL IN THE TOP OF A CORNER FENCE POST
  - 3) 24.60' NNW TO A NAIL NEAR THE TOP OF A STEEL FENCE POST
  - 4) 27.93' NNE TO A NAIL NEAR THE TOP OF A STEEL FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 1,316.81' EAST TO THE NAIL HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 22-17-11
  - 2) 992.06' SOUTH TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHWEST CORNER OF TRACT 1
  - 3) 1,823.44' SOUTH TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHWEST CORNER OF TRACT 2
  - 4) 2,653.50' SOUTH TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11 AND THE SOUTHWEST CORNER OF TRACT 3
  
- 5) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 7, 2003, FOR THE J. A. DAVIS SUBDIVISION IN THE DRAWER FOR TOWNSHIP 17-11, SAID THAT HE EXCAVATED FOR THE STONE THAT WAS SET BY ALVA J. SMITH AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11 ON TRUE LINE AND AT HALF THE DISTANCE BETWEEN THE NORTH 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 22-17-11 AS PER THE PERMANENT SURVEY BY SAID ALVA J. SMITH DATED 1901 AND RECORDED IN SURVEY BOOK "E" ON PAGE 212 IN THE COUNTY ENGINEER'S OFFICE.
  - 1) 32.35' NW TO A CONCRETE NAIL & SHINER IN THE TOP OF A HEDGE FENCE POST
  - 2) 20.40' NORTH TO A CONCRETE NAIL & SHINER IN THE TOP OF A HEDGE FENCE POST
  - 3) 39.85' NE TO A CONCRETE NAIL & SHINER IN THE TOP OF A HEDGE FENCE POST
  - 4) 27.95' NE TO A 40 D SPIKE NEAR THE TOP OF A STEEL FENCE POST
  - 5) 24.00' SOUTH TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
  - 6) IN LINE WITH A FENCE TO THE SOUTH EXTENDED
  - 7) 4.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 280 EAST-WEST
  - 8) **2.11' SE TO A 1/2" REBAR WITH A "LS 667" CAP FOUND**

HIS INFORMATION IS CONTINUED ON PAGE 3

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,315.20' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 22-15-11
- 2) 1,325.20' EAST TO THE REBAR OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 3) 2,654.99' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 22-17-11