

NORTH 1/16TH CORNER OF SOUTHEAST 1/4 SECTION 22, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 31, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 212 DATED AUGUST 12, 1901 BY THE ORDER OF W. E. DAVIS TO SURVEY SECTION 22-17-11, SAID THAT **HE SET A 3" X 10" X 18" STONE** FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11 ON LINE AND MIDWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 22-17-11 AND THE TEMPORARY CORNER HE SET FOR THE EAST 1/4 CORNER OF SECTION 22-17-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318.5' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 22-17-11
 - 2) 1,318.5' EAST TO THE TEMPORARY CORNER HE SET FOR THE EAST 1/4 CORNER OF SECTION 22-17-11
- 2) GREGORY A. MILES, L.S. 667, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 17, 1982, SURVEY F22002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THREE TRACTS IN THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 22-17-11 FOR LOUISE BAKER, RECORDED IN VOLUME 393 ON PAGE 939 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 21, 1982, SAID THAT HE CONSIDERED THAT THIS 1/16TH CORNER WAS **LOST**. **HE SET A 1/2" REBAR WITH HIS "LS 667" CAP** FOR THE NORTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 22-17-11 BASED ON ALVA J. SMITH'S OFFICIAL SURVEY OF 1901.

- 1) 9.43' EAST TO A NAIL IN THE TOP OF A FENCE POST
- 2) 8.28' NORTH TO A NAIL IN THE TOP OF A FENCE POST
- 3) 35.40' WEST TO A NAIL IN THE TOP OF A FENCE POST
- 4) 0.30' SOUTH TO THE BASE OF A CORNER FENCE POST

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 830.06' NORTH TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHWEST CORNER OF TRACT 2
- 2) 1,661.44' NORTH TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHWEST CORNER OF TRACT 1
- 3) 2,653.50' NORTH TO THE 1/2" STEEL PIN HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 4) 1,319.28' EAST TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 22-17-11

- 3) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 7, 2003, FOR THE J. A. DAVIS SUBDIVISION IN THE DRAWER FOR TOWNSHIP 17-11, SAID THAT HE EXCAVATED FOR THE STONE SET BY A PRIOR SURVEY BY ALVA J. SMITH DATED 1901 AND RECORDED IN SURVEY BOOK "E" ON PAGE 212 IN THE COUNTY ENGINEER'S OFFICE AT THE NORTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 22-17-11. HE DID **NOT** FIND THE STONE, BUT **HE FOUND THE 1/2" REBAR WITH A WIRE FLAG** AT THE NORTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 22-17-11 THAT WAS ATTRIBUTABLE TO GREGORY A. MILES, L.S. 667, FROM THE EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY MILES.

- 1) 35.50' WEST TO A 40 D NAIL & SHINER IN THE TOP OF A FENCE POST
- 2) IN LINE WITH A LINE OF FENCE TO THE NORTH
- 3) 6.93' TO A CONCRETE NAIL & SHINER IN A BRACE POST
- 4) 0.90' SOUTH TO A CONCRETE NAIL & SHINER IN A CORNER FENCE POST
- 5) 0.30' SOUTH TO THE NORTH FACE OF A CORNER FENCE POST
- 6) 0.60' SOUTH TO A LINE OF FENCE RUNNING EAST & WEST

HIS TIES ARE CONTINUED ON PAGE 2

7) 8.85' EAST TO A CONCRETE NAIL & SHINER IN A BRACE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.19' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 22-17-11
- 2) 1,319.28' EAST TO THE 5/8" CAPPED REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 3) 2,654.99' NORTH TO THE 5/8" CAPPED REBAR HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 22-17-11