

**NORTHWEST CORNER SECTION 23, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 311 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 12" X 2"** FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-17-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-17-11
- 2) 80.00 CHAINS EAST TO THE 22" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-17-11

- 2) J. D. WALKER, SURVEYOR, IN THE "REPORT OF SURVEY OF TOWNSHIP ROAD NO. 2" RECORDED AT THE TOP OF PAGE 54 IN ROAD RECORD BOOK "A" SURVEYED JUNE 9, 1859 FOR A ROAD IN FREMONT TOWNSHIP, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 23-17-11 ON THIS ROAD SURVEY. IT WAS NOTED THAT THIS ROAD WAS "PERMANENTLY LOCATED AND ESTABLISHED ACCORDING TO SAID SURVEY" ON MARCH 26, 1860 BY SUPERVISORS J. D. WALKER AND W. B. DAVIS.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH OF THE SECTION LINE TO THE NORTHWEST CORNER OF SECTION 14-17-11 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 23-18-11 TO THE END OF THIS ROAD SURVEY

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 31, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 212 DATED AUGUST 12, 1901 BY THE ORDER OF W. E. DAVIS TO SURVEY SECTION 22-17-11, SAID THAT HE DETERMINED THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 22-17-11 BASED ON THE AFFIDAVIT OF J. H. OGLESBY, WHICH WAS MADE A PART OF THIS **PERMANENT SURVEY**. **HE SET A STONE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 22-17-11.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.5' WEST TO THE 3" X 6" X 20" STONE HE SET FOR THE PERMANENT NORTH 1/8<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 22-17-11
- 2) 2,633' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 22-17-11
- 3) 5,266' WEST TO THE GOVERNMENT STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11
- 4) 2,655' SOUTH TO THE TEMPORARY CORNER HE SET FOR THE EAST 1/4 CORNER OF SECTION 22-17-11
- 5) 5,310' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-17-11

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 44, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 225 DATED APRIL 23, 1902 ORDERED BY LOUIS NELSON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER OF SECTION 10-17-11 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 15-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGES 24 AND 47, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 46" IN MISCELLANEOUS DRAWER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.15 CHAINS NORTH TO HEDGES TO THE EAST AND WEST – NO STONE

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 80.46 CHAINS NORTH TO THE STONE THAT HE SET IN THE MOUNKES SURVEY HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 10-17-11 ON THIS PERMANENT SURVEY
  - 3) 141.01 CHAINS NORTH TO THE STONE IN THE ROAD HE FOUND THAT WAS SET BY "UNKNOWN PARTIES"
  - 4) 160.92 CHAINS NORTH TO THE 15" X 8" X 3" STONE MARKED "X" ON THE SIDE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 10-17-11
  - 5) 238.65 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 3-17-11 ON THE TOWNSHIP LINE
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 46, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 227 DATED MARCH 18 & 21 AND CLOSED MAY 8, 1902 ORDERED BY ROBERT MOUNKES FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTHEAST CORNER, THE 1/4 CORNER ON THE EAST LINE, AND THE CENTER 1/4 CORNER OF SECTION 15-17-11 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 15-17-11 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 26, AND ADDITIONAL INFORMATION IS IN PACKET "M 66" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 40.23 CHAINS NORTH TO THE 18" X 6" X 6" STONE MARKED "X" ON THE NORTH FACE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 15-17-11
  - 2) 80.46 CHAINS NORTH TO THE 24" X 12" X 4" STONE WITH A DRILL HOLE ON THE BOTTOM HE SET FOR THE PERMANENT NORTHEAST CORNER OF SEC. 15-17-11
  - 3) 160.92 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-17-11
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 48, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 229 DATED APRIL 22, 1902 FOR A ROAD BETWEEN SECTIONS 15 & 22-17-11, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 22-17-11 TO END THIS ROAD SURVEY FOR A ROAD OF VARYING WIDTHS.
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 7.52 CHAINS, THEN S. 65°53' W. FOR 3.00 CHAINS, THEN S. 87°15' W. FOR 7.00 CHAINS, THEN N. 62°37' W. FOR 3 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11, LAYING ALL OF THE ROAD FROM THE BEGINNING TO HERE AT 40 FEET WIDE, 20 FEET EACH SIDE OF THE SURVEYED LINE, THEN WEST ON THE SECTION LINE FOR 1/4 OF A MILE, LAYING THE ROAD 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 22-17-11, THEN CONTINUES WEST ON THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11 TO BEGIN THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 571 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 149 THROUGH PETITION BY W. E. DAVIS AND OTHERS FOR A ROAD IN TOWNSHIP 17-11 [PACKET 712 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 22, 1902 WAS GRANTED AS A 40 AND 50 FOOT WIDE, EQUAL DISTANCE ON EACH SIDE OF THE SURVEYED LINE, ON MAY 8, 1902 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON JUNE 16, 1902 BY

ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 22-17-11 TO END THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

2) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 7.52 CHAINS, THEN S. 65°53' W. FOR 3.00 CHAINS, THEN S. 87°15' W. FOR 7.00 CHAINS, THEN N. 62°37' W. FOR 3 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/8<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11, LAYING ALL OF THE ROAD FROM THE BEGINNING TO HERE AT 40 FEET WIDE, 20 FEET EACH SIDE OF THE SURVEYED LINE, THEN WEST ON THE SECTION LINE FOR 1/4 OF A MILE, LAYING THE ROAD 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 22-17-11, THEN CONTINUES WEST ON THE SECTION LINE FOR 1/2 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 22-17-11 TO BEGIN THIS ROAD SURVEY, LAYING THE ROAD 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE

8) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F14001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 DATED JULY 18, 1973 FOR A SURVEY TO ESTABLISH THE CORNERS TO A 10 ACRE TRACT OF LAND IN THE SOUTHWEST 1/4 OF SECTION 14-17-11, SHOWS ON HIS SURVEY DRAWING AN **“IRON PIN SET”** AT THE SOUTHWEST CORNER OF SECTION 14-17-11 ON THIS SURVEY. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' NORTH TO THE IRON PIN HE SET FOR THE SOUTHWEST CORNER OF THE 10 ACRE TRACT
- 2) 2,653.50' NORTH TO THE IRON PIN HE SET IN LINE WITH A HEDGE ROW TO THE EAST AT THE NORTHWEST CORNER OF THE 10 ACRE TRACT

9) GREGORY A. MILES, L.S. 667, IN SURVEY F22002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 DATED SEPTEMBER 22, 2982 FOR THREE TRACTS IN THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 22-17-11 FOR LOUISE BAKER, RECORDED IN VOLUME 393 ON PAGE 939 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 21, 1982, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A NAIL** AT THE NORTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 22-17-11. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.81' WEST TO THE 1/2" STEEL PIN HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 2) 992.07' SOUTH TO THE 1/2" STEEL PIN HE SET FOR THE P.O.B. OF TRACT 2
- 3) 1,823.46' SOUTH TO THE 1/2" STEEL PIN HE SET FOR THE P.O.B. OF TRACT 3
- 4) 2,655.20' SOUTH TO THE 1/2" STEEL PIN HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 22-17-11

10) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT WITH NO DATE BUT PRIOR TO THE RECONSTRUCTION OF THE ALLEN ROAD, SAID THAT **HE FOUND A LIMESTONE AT 2-1/2' BELOW THE ROAD SURFACE** AT THE SOUTHWEST CORNER OF SECTION 14-17-11. **HE SET A 1/2" REBAR WITH HIS “LS 752” CAP OVER THE STONE.** THERE WERE NO TIES ON THE REPORT.

11) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY F14002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, DATED AUGUST 4, 1987, FOR PROJECT NUMBER 87169 FOR A SURVEY TO LOCATE THE NORTHWEST CORNER OF SECTION 14-17-11, SAID THAT **HE FOUND A SPIKE OVER THE STONE HE PREVIOUSLY CONFIRMED** AT THE SOUTHWEST CORNER OF SECTION 14-17-11 FROM TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. HE NOTED THAT THIS AREA OF THIS TOWNSHIP SHOWS EVIDENCE OF GLO FRAUD.

- 1) 35.5' EAST TO A SPIKE IN THE TOP OF A GATE POST
  - 2) 40.3' SSW TO A SPIKE IN THE TOP OF A FENCE POST
  - 3) 44.0' NW TO A SPIKE IT THE TOP OF A CORNER FENCE POST
  - 4) IN THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
  - 5) 5.5' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,653.93' NORTH TO THE 1/2" REBAR HE FOUND IN THE ASPHALT SURFACE AT THE WEST 1/4 CORNER OF SECTION 14-17-11
  - 2) 5,306.70' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF SECTION 14-17-11
- 12) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 27, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS IN COUNTY ASPHALT ROADS, **FOUND A 1/2" X 6" ROUND HEAD BOLT AT 4" BELOW THE SURFACE OF THE ASPHALT ROAD** AT THE NORTHWEST CORNER OF SECTION 23-17-11 FROM REFERENCE TIES OF RECORD. SINCE THE BOLT FIT THE EXISTING REFERENCES, I DID NOT ATTEMPT TO UNCOVER THE STONE AS IT IS OVER 3 FEET BELOW THE EXISTING SURFACE. I VERIFIED THAT THIS WAS THE CORRECT MONUMENT WITH STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR. **I REPLACED THE BOLT WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP OVER THE STONE AND I SET A COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF ASPHALT COUNTY ROAD "L" FOR THE NORTHWEST CORNER OF SECTION 23-17-11.**
- 1) 40.1' SSW TO A FOUND SPIKE IN THE TOP OF A CORNER FENCE POST
  - 2) 36.6' ENE TO A FOUND PK NAIL & WASHER IN A CORNER FENCE POST
  - 3) 38.1' EAST TO A FOUND PK NAIL & WASHER IN A CORNER FENCE POST
  - 4) 39.6' NW TO A FOUND PK NAIL & WASHER IN A CORNER FENCE POST
  - 5) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 280 TO THE WEST
  - 6) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF ASPHALT COUNTY ROAD "L" NORTH-SOUTH
- 13) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 1, 2001, FOR PROJECT NUMBER 01440-02, SURVEY F23001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THE SURVEY OF A 42.16 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 23-17-11, SAID THAT **HE FOUND THE STONE WITH A 1/2" X 6" BOLT OVER THE TOP** AT THE NORTHWEST CORNER OF SECTION 23-17-11 FROM TIES OF RECORD. **[NOTE: THE FIELD WORK WAS COMPLETED BEFORE THE COUNTY INSTALLED THE MONUMENT BOX - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 38.6' ENE TO A PK NAIL & WASHER IN A POWER POLE
  - 2) 38.1' EAST TO A PK NAIL & WASHER IN A FENCE POST
  - 3) 39.6' NW TO A PK NAIL & WASHER IN A CORNER FENCE POST
  - 4) 40.1' SSW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 5) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 280 TO THE WEST
  - 6) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L" NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 3,666.42' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 42.16 ACRE TRACT
  - 2) 5,310.42' EAST TO THE 1/2" CAPPED REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 23-17-11

CONTINUED ON PAGE 5

- 14) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 7, 2003, FOR THE J. A. DAVIS SUBDIVISION PRELIMINARY PLAT, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE IN THE COUNTY MONUMENT WELL** AT THE NORTHEAST CORNER OF SECTION 22-17-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.
- 1) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L"
  - 2) 38.50' ENE TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 3) 38.10' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 4) 39.60' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 5) 40.10' SSW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
  - 6) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 280 TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,315.20' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
  - 2) 2,630.40' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 22-17-11
  - 3) 2,658.12' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 22-17-11
- 15) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 19, 2003, FOR PROJECT NUMBER 03254-15, SURVEY F15003 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THE SURVEY OF A 7.00 ACRE TRACT IN THE NORTHEAST 1/4 AND THE SOUTHEAST 1/4 OF SECTION 15-17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE IN THE MONUMENT WELL** AT THE SOUTHEAST CORNER OF SECTION 15-17-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED APRIL 2003.
- 1) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "L"
  - 2) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 280 TO THE WEST
  - 3) 38.50' ENE TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 4) 38.10' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 5) 39.60' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 6) 40.10' SSW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,568.58' NORTH TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHEAST CORNER OF THE 7.00 ACRE TRACT
  - 2) 2,652.10' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 15-17-11
  - 3) 2,968.58' NORTH TO THE COTTON GIN SPINDLE HE SET FOR THE NORTHEAST CORNER OF THE 7.00 ACRE TRACT
  - 4) 5,303.27' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHEAST CORNER OF SEC. 15-17-11
- 16) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 5, 2010 FOR PROJECT NUMBER 10268-02, SURVEY F15004 IN THE SURVEY FILE FOR TOWNSHIP 17-11 TO SURVEY THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 15-17-11 FOR EMPORIA SATE BANK AND MOUNKES, SAID THAT HE CROSSED OUT THE EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE AND **HE SET A COTTON GIN SPINDLE IN ASPHALT OVER THE COVERED MONUMENT WELL** AT THE SOUTHEAST CORNER OF SECTION 15-17-11.

HIS TIES ARE ON PAGE 6

- 1) 38.5' ENE TO A CONCRETE NAIL & WASHER IN A POWER POLE
- 2) 38.10' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 39.60' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 4) 40.10' SSW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- 5) IN THE CENTERLINE TRAVELED WAY OF ASPHALT COUNTY ROAD "L" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,630.69' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 15-17-11
- 2) 880.77' NORTH TO THE SOUTHEAST CORNER OF TRACT "A", AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET ON THE RIGHT-OF-WAY LINE
- 3) 1,325.77' NORTH TO THE COTTON GIN SPINDLE HE SET FOR THE SOUTHEAST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 15-17-11
- 4) 2,651.54' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 15-17-11

- 17) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2011 FOR PROJECT NUMBER 11098-02, A SURVEY OF 3 TRACTS IN THE NORTHEAST 1/4 OF SECTION 14-17-11 FOR BETTY DUNN, SURVEY F14003 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE COTTON GIN SPINDLE** AT THE SOUTHWEST CORNER OF SECTION 14-17-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE FOUND THE STONE AT THIS CORNER IN 1987 AND THAT HE SET THE COTTON GIN SPINDLE OVER THE 5/8" REBAR IN A MONUMENT WELL IN 2010.

- 1) 38.0' ENE TO A 40 D NAIL & WASHER IN A POWER POLE
- 2) 37.95' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 39.45' NW TO A MAG NAIL & WASHER IN A CORNER FENCE POST
- 4) 40.35' SSW TO A SPIKE IN THE TOP OF A CORNER FENCE POST
- 5) 1' SOUTH TO A FENCE TO THE EAST EXTENDED
- 6) 2' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 280 TO THE EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,654.97' EAST TO THE DETERMINED POSITION FOR THE SOUTH 1/4 CORNER OF SECTION 14-17-11
- 2) 5,309.94' EAST TO THE 1/2" CAPPED REBAR CAP HE FOUND AT THE SOUTHEAST CORNER OF SECTION 14-17-11
- 3) 2,651.35' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE WEST 1/4 CORNER OF SECTION 14-17-11
- 4) 5,302.49' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE NORTHWEST CORNER OF SEC. 14-17-11

- 18) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 4, 2013 FOR PROJECT NUMBER 13239-02, THE SURVEY OF A TRACT IN THE NORTHEAST AND SOUTHEAST 1/4 OF SECTION 23-17-11 FOR RON JACKSON, SURVEY F23002 IN THE SURVEY FILE FOR TOWNSHIP 17-11, SAID THAT **HE FOUND THE COTTON GIN SPINDLE IN ASPHALT OVER THE COVERED MONUMENT WELL** AT THE NORTHWEST CORNER OF SECTION 23-17-11 FROM HIS EXISTING REFERENCE TIES FOR PROJECT 10268-02 DATED OCTOBER 5, 2010 ON FILE AT THE LYON COUNTY ENGINEERS OFFICE.

- 1) 38.5' EAST-NORTHEAST TO A CONCRETE NAIL & WASHER IN A POWER POLE
- 2) 38.10' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 39.60' NORTHWEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST

HIS TIES ARE CONTINUED ON PAGE 7

- 4) 40.10' WEST-SOUTHWEST TO A SPIKE IN TO THE TOP OF A CORNER FENCE POST
- 5) IN THE CENTERLINE TRAVELED WAY OF ASPHALT COUNTY ROAD "L" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,676.35' EAST TO THE 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 23-17-11
- 2) 3,66.46' EAST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF THE "EXCEPTED TRACT"
- 3) 5,310.51' EAST TO THE 1/2" IRON PIN WITH A CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 23-17-11, AND THE NORTHEAST CORNER OF THE "EXCEPTED TRACT"

NORTHWEST CORNER 23-17-11