

NORTH 1/4 CORNER SECTION 24, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 308 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 24-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.10 CHAINS WEST TO THE 22" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 3 & 24
 - 2) 40.10 CHAINS EAST TO THE 20" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 18, 19 7 24 ON THE EAST TOWNSHIP BOUNDARY

- 2) LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 121 DATED APRIL 15, 1955 TO SET AN IRON PIN IN THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 13-17-11, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A TEMPORARY POINT** FOR THE SOUTH 1/4 CORNER OF SECTION 13-17-11 ON HIS SURVEY. THERE IS NO INDICATION OF THE METHODOLOGY THAT HE USED TO DETERMINE THE LOCATION FOR THIS CORNER.

NORTH QUARTER CORNER 24-17-11