

NORTH 1/4 CORNER SECTION 25, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 308 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 15" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 24 & 25-17-11.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.96 CHAINS WEST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26
 - 2) 39.95 CHAINS EAST TO THE 19" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 24, 25 & 30 ON THE EAST TOWNSHIP BOUNDARY

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 11, 2005, FOR PROJECT NUMBER 05028-02, SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF A 14.91 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 25-17-11 FOR JARET MOYER, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE GLO LIMESTONE AT THE NORTH 1/4 CORNER OF SECTION 25-17-11, BUT HE DID **NOT** FIND THE STONE. HE STATED THAT "DUE TO THE HIGH INSTANCES OF GLO FRAUD IN THIS TOWNSHIP" HE DEEMED THAT THIS CORNER WAS **OBLITERATED** IN BOTH POSITIONS. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 25-17-11.
 - 1) 20.45' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 25.2' SOUTH TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 3) 26.55' SSE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 4) IN LINE WITH A HEDGE TO THE SOUTH EXTENDED
 - 5) 1.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF ROAD 270 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 4,566.07' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 14.91 ACRE TRACT
 - 2) 5,256.07' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 25-17-11—FALLS IN A CREEK—WITH THE 1/2" WITNESS REBAR WITH HIS "LS 752" CAP HE SET AT 33.00' NORTH OF THE **TRUE POSITION**

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 22, 2006, FOR PROJECT NUMBER 06071-02, SURVEY F25002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF THE WEST 50 ACRES OF THE NORTHEAST 1/4 OF SECTION 25-17-11 FOR CLIFF ROETHER, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 25-17-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE DATED MARCH 2005.
 - 1) 20.45' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 25.2' SOUTH TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 3) 26.55' SSE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 4) IN LINE WITH A HEDGE TO THE SOUTH EXTENDED
 - 5) IN THE CENTERLINE TRAVELED-WAY OF GRAVEL ROAD 270 EAST-WEST
 - 6) 7.0' EAST TO A LINE OF FENCE TO THE SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,662.80' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 25-17-11
 - 2) 5,256.22' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 25-17-11—FALLS IN A CREEK—WITH A 1/2" WITNESS REBAR WITH HIS "LS 752" CAP HE SET AT 33.00' NORTH OF THE **TRUE POSITION**

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 817.50' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE WEST 50 ACRES OF THE NE1/4 OF SEC. 25-17-11
 - 4) 2,617.57' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 25-17-11 ON THE RANGE LINE
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 16, 2009 FOR PROJECT NUMBER 08212-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 17-11 TO ESTABLISH CONTROL POINTS FOR LYON COUNTY BRIDGE PROJECT 08-QV IN THE NORTHEAST 1/4 OF SECTION 36-17-11, SAID THAT **HE FOUND THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/4 CORNER OF SECTION 25-17-11 FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 20.45' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 2) 25.30' SOUTH TO A CONCRETE NAIL & WASHER IN A GATE POST
 - 3) 26.70' SE TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 4) 36.20' SW TO THE CENTER OF A FIBER OPTIC MARKER SIGN POST
 - 5) IN LINE WITH A HEDGE TO THE SOUTH EXTENDED
 - 6) 1.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 270 EAST-WEST
 - 7) SURVEY COORDINATES: NORTH = 10,254.154 EAST = 2,936.562
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,223.07' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 33.00' NORTH OF THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 36-17-10 WITH SURVEY COORDINATES NORTH = 5,031.207 AND EAST = 2,900.774
 - 2) 5,256.07' SOUTH TO THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 36-17-10

NORTH QUARTER CORNER 25-17-11