

NORTHWEST CORNER SECTION 26, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 311 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 5"** FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-17-11.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS EAST TO THE 14" X 10" X 8" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-17-11
- 2) 80.00 CHAINS EAST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-17-11

- 2) J. D. WALKER, SURVEYOR, IN THE "REPORT OF SURVEY OF TOWNSHIP ROAD NO. 2" RECORDED AT THE TOP OF PAGE 54 IN ROAD RECORD BOOK "A" SURVEYED JUNE 9, 1859 FOR A ROAD IN FREMONT TOWNSHIP, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 26-17-11 ON THIS ROAD SURVEY. IT WAS NOTED THAT THIS ROAD WAS "PERMANENTLY LOCATED AND ESTABLISHED ACCORDING TO SAID SURVEY" ON MARCH 26, 1860 BY SUPERVISORS J. D. WALKER AND W. B. DAVIS.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH OF THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 14-17-11 TO COMMENCE THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 23-18-11 TO THE END OF THIS ROAD SURVEY

- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 383 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 478 TO 480 PETITION BY EDWARD AYERS AND OTHERS TO LOCATE TWO ROADS AND VACATE A ROAD IN TOWNSHIPS 17-11 AND 17-12 [PACKET 639 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON FEBRUARY 23, 1891, WERE ESTABLISHED AS 49-1/2 FOOT WIDE ROADS ON JANUARY 6, 1892 AS NOTED BY J. W. LAY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AS ATTESTED BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE MARKED "R/2M"** AT THE NORTHEAST CORNER OF SECTION 27-17-11 ON THE SECOND ROAD ON THIS ROAD SURVEY. THE ROAD **VACATED** BEGAN AT A POINT WHERE THE ROAD RUNNING NORTHEAST LEAVES THE SECTION LINE ON THE SOUTH SIDE OF THE SOUTHEAST 1/4 OF SECTION 25-17-11 TO WHERE SAID ROAD INTERSECTS THE SECTION LINE ON THE EAST SIDE OF SECTION 30-17-12.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE ROAD STONE HE SET FOR THE NORTHEAST CORNER OF SECTION 28-17-11 AT THE TERMINUS OF THE SECOND ROAD ON THIS ROAD SURVEY
- 2) THIS SECOND ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE ROAD STONE HE SET AT THE SOUTHEAST CORNER OF SECTION 24-17-11 ON THE RANGE LINE TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 31, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 212 DATED AUGUST 12, 1901 BY THE ORDER OF W. E. DAVIS TO SURVEY SECTION 22-17-11, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 22-19-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,642.5' WEST TO THE TEMPORARY POINT HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 22-17-11
- 2) 5,185' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-17-11

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,655' NORTH TO THE TEMPORARY POINT HE SET FOR THE EAST 1/4 CORNER OF SECTION 22-17-11
- 4) 5,310' NORTH TO THE LOCATION FOR THE NORTHEAST CORNER OF SECTION 22-17-11 AS LOCATED BY THE AFFIDAVIT OF J. H. OGLESBY
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-11 SHOWS A **RED HEAD IN BLACKTOP** AT THE "NE CORNER SECTION 27-17-11" ON AUGUST 25, 1966.
 - 1) 38.95' NE TO A SPIKE IN A CORNER POST
 - 2) 35.55' SE TO A SPIKE IN A REA POLE
- 6) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F27002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 DATED DECEMBER 14, 1972, SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE NORTHEAST CORNER OF SECTION 27-17-11. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.
- 7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 29, 1982, SAID THAT **HE FOUND A 60 D SPIKE** AT THE NORTHWEST CORNER OF SECTION 26-17-11 THAT WAS USED BY GREGORY A. MILES, L.S. 667, ON A SURVEY IN SEPTEMBER 17, 1982. **HE REPLACED THE FOUND 60 D SPIKE WITH A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE NORTHWEST CORNER OF SECTION 26-17-11.
 - 1) 27.5' EST TO A LINE OF FENCE TO THE SOUTH
 - 2) 34.0' WEST TO A LINE OF FENCE TO THE NORTH
 - 3) 27.0' EAST TO A LINE OF FENCE TO THE NORTH
 - 4) 37.3' EAST TO A LINE OF FENCE TO THE SOUTH
 - 5) 24.0' SOUTH TO A LINE OF FENCE EAST-WEST
 - 6) 26.0' NORTH TO A LINE OF FENCE EAST-WEST
 - 7) IN THE TRAVELED WAY OF THE ROADS NORTH-SOUTH-EAST-WEST
HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
 - 1) 2,651.55' EAST TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 26-17-11
 - 2) 5,310.20' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-17-11
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SURVEY DATED SEPTEMBER 9, 1999, FOR PROJECT NUMBER 99014-02, SURVEY F26001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR THE SURVEY OF NORTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 26-17-11, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE NORTHWEST CORNER OF SECTION 26-17-11 FROM HIS 1982 TIES. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 671.95' SOUTH TO THE COTTON GIN SPINDLE HE SET FOR THE NORTHWEST CORNER OF A 10 ACRE TRACT
 - 2) 1,331.95' SOUTH TO THE COTTON GIN SPINDLE HE SET FOR THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 26-17-11
 - 3) 2,663.90' SOUTH TO THE COTTON GIN SPINDLE HE SET FOR THE WEST 1/4 CORNER OF SECTION 26-17-11
 - 4) 5,309.86' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 26-17-11
 - 5) 1,325.83' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 26-17-11
 - 6) 2,651.66' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 26-17-11
 - 7) 5,310.32' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 26-17-11

- 9) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 27, 2001, FOR PROJECT NUMBER 01-59, SETTING COUNTY MONUMENT BOXES OVER SECTION CORNERS IN COUNTY ASPHALT ROADS, **FOUND A 1/2" X 24" CAPPED REBAR AT 3" BELOW THE ASPHALT ROAD SURFACE AT THE NORTHWEST CORNER OF SECTION 26-17-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DATED NOVEMBER 29, 1982. I REPLACED THIS CAPPED 1/2" REBAR WITH A 5/8" X 24" REBAR WITH A LYON COUNTY CAP AND I SET A COUNTY MONUMENT BOX FLUSH WITH THE SURFACE OF ASPHALT COUNTY ROAD "L" AT THE NORTHWEST CORNER OF SECTION 26-17-11.**
- 1) 37.0' NE TO A MAG NAIL & WASHER IN THE WEST FACE OF A POWER POLE
 - 2) 46.4' SE TO A FOUND SPIKE & WASHER IN A CORNER FENCE POST
 - 3) 36.4' SE TO A MAG NAIL & WASHER IN THE WEST FACE OF A POWER POLE
 - 4) 42.6' NW TO A FOUND SPIKE & WASHER IN A CORNER FENCE POST
 - 5) IN THE TRAVELED WAY OF ROAD 270 TO THE EAST
 - 6) 3' NORTH TO THE TRAVELED WAY OF GRAVEL COUNTY ROAD 270 TO THE WEST
 - 7) IN THE TRAVELED WAY OF ASPHALT COUNTY ROAD "L" NORTH-SOUTH

NORTHWEST CORNER 26-17-11