

**NORTH 1/4 CORNER SECTION 30, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 324 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 16" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-17-11 ON MARCH 1, 1861. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 35.70 CHAINS WEST TO THE 14" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-17-11 ON THE WEST TOWNSHIP BOUNDARY
  - 2) 40.00 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-17-11
  
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 4, 2004, FOR PROJECT NUMBER 04145-02, SURVEY F19002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A 10.0 ACRE TRACT IN THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 19-17-11 FOR MARC & BROOKE RUMMEL, SAID THAT HE DUG WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 19-17-11. **HE FOUND THE 12" X 16" X 2-1/2" GLO LIMESTONE** AT THE SOUTH 1/4 CORNER OF SECTION 19-17-11.
  - 1) 5/8" X 24" REBAR WITH A LYON COUNTY CAP SET [ON SOUTH SIDE, CENTER OF THE STONE FOUND]
  - 2) 1/2" X 24" REBAR WITH HIS CAP SET [ON THE NORTH SIDE, CENTER OF THE STONE FOUND]
  - 3) 29.15' NNW TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 4) 31.90' NNE TO A CONCRETE NAIL & WASHER IN A BRACE POST
  - 5) 32.75' SE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 6) 1.0' WEST TO A LINE OF FENCE TO THE NORTH [EXTENDED]
  - 7) 12.5' EAST TO A LINE OF FENCE TO THE SOUTH [EXTENDED]
  - 8) 5.5' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 270 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION
  - 1) 1,700.47' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 10.0 ACRE TRACT
  - 2) 2,648.47' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 19-17-11
  
- 3) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 30, 2015, FOR PROJECT NUMBER 15160-02, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 17-11, THE SURVEY OF A 20.00 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 30-17-11 FOR DAVID CROTT, SAID THAT **HE FOUND THE EXISTING RECORD 12" X 16" X 2-1/2" GLO STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP ON THE SOUTH SIDE OF THE STONE AND A 1/2" REBAR WITH HIS "S. BROSEMER" CAP ON THE NORTH SIDE OF THE STONE** FROM HIS EXISTING REFERENCE TIES DATED IN 2004 FOR HIS PROJECT NUMBER 04145 ON FILE AT THE COUNTY ENGINEERS OFFICE.
  - 1) 29.15' NNW TO A CONCRETE NAIL & WASHER IN A POWER POLE
  - 2) 32.00' NNE TO A CONCRETE NAIL & WASHER IN A BRACE POST
  - 3) 1.00' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED
  - 4) 12.50' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
  - 5) 6.00' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF COUNTY ROAD 270 EAST-WEST

NORTH QUARTER CORNER 30-17-11