

WEST 1/4 CORNER SECTION 33, TOWNSHIP 17 SOUTH, RANGE 11 EAST

- 1) ON PAGE 317 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 15" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-17-11.
- 2) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST “HEELED-IN” FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 15 SAYS THAT **THEY SET AN IRON PIN** FOR THE EAST 1/4 CORNER OF SECTION 32-17-11 AT 2,649.25 FEET NORTH OF THE SOUTHEAST CORNER OF SECTION 32-17-11.
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR THIS TOWNSHIP SHOWS A **REA PIN** AT THE “SW CORNER NW1/4 SECTION 33-17-11”. **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST “HEELED-IN” FOR UTILITY USE ONLY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 29° EAST TO A WITNESS [REA]
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 22, 2004, FOR PROJECT NUMBER 04460-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 19-11 FOR A 6.67 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 32-17-11, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 32-17-11 WAS BOTH **LOST** AND **OBLITERATED**. HE RESET THE EAST 1/4 CORNER OF SECTION 32-17-11 ON TRUE LINE BETWEEN THE NORTHEAST AND SOUTHEAST SECTION CORNERS OF SECTION 32-17-11 [**LOST**], AND IN LINE WITH A FENCE TO THE WEST [**OBLITERATED**]. **HE SET A 5/8" X 24" REBAR WITH HIS “LS 752” CAP** FOR THE EAST 1/4 CORNER OF SECTION 32-17-11.
 - 1) 35.2' EAST TO A 40 D NAIL AND WASHER IN A POWER POLE
 - 2) 23.3' WEST TO A CONCRETE NAIL & WASHER IN THE SIDE OF A CORNER FENCE POST
 - 3) 74.25' SE TO A 40 D NAIL AND WASHER IN A POWER POLE
 - 4) 35.2' EAST TO A LINE OF FENCE TO THE NORTH
 - 5) 23.5' WEST TO A LINE OF FENCE TO THE SOUTH AND NORTH
 - 6) IN LINE WITH A FENCE TO THE WEST
 - 7) 3.0' EAST TO THE TRAVELED-WAY NORTH-SOUTH GRAVEL COUNTY ROAD “J”**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
 - 1) 453.00' NORTH TO THE SOUTHEAST CORNER OF THE 6.67 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS “LS 752” CAP HE SET AT 20.00' WEST
 - 2) 861.00' NORTH TO THE NORTHEAST CORNER OF THE 6.67 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS “LS 752” CAP HE SET AT 20.00' WEST
 - 3) 2,649.58' NORTH TO THE 3/4" SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 32-17-11
 - 4) 2,647.84' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-17-11 ON THE TOWNSHIP LINE
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F32003 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR PROJECT NUMBER 10162-02 DATED JUNE 22, 2010, THE SURVEY OF A 6.67 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 32-17-11 FOR CATHY GROVER, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 32-17-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES. SEE HIS TIES DATED JULY 19, 2005.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 453.00' NORTH TO THE P.O.B. OF THE 6.67 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20.00' WEST
- 2) 861.00' NORTH TO THE NORTHEAST CORNER OF THE 6.67 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20.00' WEST
- 3) 2,649.58' NORTH TO THE 3/4" SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 32-17-11
- 4) 2,647.84' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 32-17-11 ON THE TOWNSHIP LINE

WEST QUARTER CORNER 33-17-11