

**NORTH 1/16<sup>TH</sup> CORNER OF NORTHEAST 1/4 SECTION 36, TOWNSHIP 17 SOUTH, RANGE 11 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 31 RECORDED IN SURVEY BOOK "A" ON PAGE 126 DATED APRIL 2, 1868 TO SURVEY SECTION 36-17-11 FOR W. GILLILAND, ANDERSON, SHIELDS, AND ROSYENE, SAID THAT **HE SET A STONE** FOR THE NORTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 36-17-11 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-11 AND THE STONE THAT HE SET FOR THE NORTH 1/4 CORNER FO SECTION 36-17-11 ON THIS SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 80 RODS, 2 LINKS EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-11
  - 2) 80 RODS, 2 LINKS WEST TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 36-17-11
  - 3) 160 RODS, 4 LINKS WEST TO THE STONE HE SET FOR THE NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 36-17-11
  - 4) 240 RODS, 6 LINKS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-17-11
  
- 2) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 23, 1983, SAID THAT HE DID NOT EXCAVATE FOR THE STONE THAT WAS SET BY D. T. McAULEY IN 1868 IN SURVEY BOOK "A" ON PAGE 128. HE SAID THAT DUE TO THE LARGE ROAD CUT, HE CONSIDERED THAT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 36-17-11 WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 36-17-11 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, CONFIRMED BY MEASUREMENT: I.E., IN LINE WITH THE HEDGE ROW TO THE SOUTH AND IN THE CENTER OF THE ROAD EAST-WEST.
  - 1) 24.0' NORTH TO A LINE OF FENCE TO THE EAST-WEST
  - 2) 24.0' SOUTH TO A LINE OF FENCE TO THE EAST EXTENDED
  - 3) IN THE TRAVELED WAY OF THE ROAD EAST-WEST
  - 4) 1,316.62' EAST TO THE NORTHEAST CORNER OF SECTION 36HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING
  - 1) 1,316.62' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 36-17-11
  
- 3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 9, 1985, FOR PROJECT NUMBER 85113, SURVEY F36002 IN THE SURVEY FILE FOR TOWNSHIP 17-11 TO REESTABLISH THE WEST LINE OF SECTION 36-17-11, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP** AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 36-17-11 FROM HIS EXISTING TIES OF RECORD AT THE COUNTY ENGINEERS OFFICE DATED AUGUST 1983. THIS SURVEY WAS FILED IN VOLUME 418 ON PAGE 13 IN THE REGISTER OF DEEDS OFFICE ON AUGUST 22, 1985.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,316.5' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-11
  - 2) 3,946.82' WEST TO THE 1/2" REBAR WITH HIS "BROSEMER LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF SECTION 36-17-11
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 11, 2005, FOR PROJECT NUMBER 05028-02, SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 17-11 FOR A SURVEY OF A 14.91 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 25-17-11 FOR JARET MOYER,

SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP AT THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 25-17-11 FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.**

- 1) 1,313.62' EAST TO THE SOUTHEAST CORNER OF SECTION 25
- 2) IN LINE WITH A HEDGE TO THE SOUTH EXTENDED
- 3) 24.0' NORTH TO A LINE OF FENCE TO THE EAST-WEST
- 4) IN THE CENTERLINE TRAVELED WAY OF GRAVEL ROAD 260 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.51' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 25-17-11
- 2) 375.51' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 14.91 ACRE TRACT
- 3) 1,316.51' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 25-17-11—FALLS IN A CREEK—WITH THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 33.00' NORTH OF THE TRUE POSITION AS A **WITNESS CORNER**

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 16, 2009 FOR PROJECT NUMBER 08212-02, SURVEY F36003 IN THE SURVEY FILE FOR TOWNSHIP 17-11 TO ESTABLISH CONTROL POINTS FOR LYON COUNTY BRIDGE PROJECT 08-QV IN THE NORTHEAST 1/4 OF SECTION 36-17-11, SAID THAT **HE FOUND THE 5/8" REBAR AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 36-17-11 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 2005.**

- 1) 1,316.51' EAST TO THE NORTHEAST CORNER OF SECTION 36-17-11
- 2) 24.0' SOUTH TO A LINE OF POWER POLES TO THE WEST EXTENDED
- 3) 81.70' SE TO A 40 D NAIL & WASHER IN A POWER POLE
- 4) IN LINE WITH A HEDGE TO THE SOUTH EXTENDED
- 5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 260 EAST-WEST

6) SURVEY COORDINATES: NORTH = 4,987.849 EAST = 4,217.020

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,316.51' EAST TO THE 5/8" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-11
- 2) 1,316.51' WEST TO THE THEORETICAL POSITION FOR THE NORTH 1/4 CORNER OF SECTION 36-17-11—FALLS IN A CREEK—WITH THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 33.00' NORTH OF THE TRUE POSITION FOR A **WITNESS CORNER**
- 3) 3,946.76' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 36-17-11

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 36-17-11