

NORTH 1/4 CORNER SECTION 10, TOWNSHIP 17 SOUTH, RANGE 12 EAST

- 1) ON PAGE 480 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-17-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.60 CHAINS WEST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 19-17-12
 - 2) 39.60 CHAINS EAST TO THE 23" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-17-12

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 125, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 206 DATED MARCH 14 AND JUNE 28, 1905 FOR A ROAD BETWEEN SECTIONS 3 & 10-17-12 FOR J. W. SHADE, PRINCIPAL PETITIONER, SAID THAT HE FOUND THE 1/4 STONE **"LOOSE ON THE GROUND"** AT THE NORTH 1/4 CORNER OF SECTION 10-17-12 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD. HE DID NOT SAY THAT HE RESET THE STONE ON THIS ROAD SURVEY

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "D" ON PAGES 273 THROUGH 276 FOR ROAD NUMBER 601 BY A PETITION BY J. W. SHADE [PACKET 749 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JUNE 1905, SAID THAT HE FOUND THE 1/4 STONE **"LOOSE ON THE GROUND"** AT THE NORTH 1/4 CORNER OF SECTION 10-17-12 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD. HE DID NOT SAY IF HE RESET THE STONE ON THIS ROAD SURVEY.

- 4) LLOYD J. DOBLER, L.S. 541, IN A SECTION CORNER REPORT DATED FEBRUARY 21, 1990, FOR A SURVEY FOR LELAND SPADE OF A PART OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 10-17-12, SURVEY F10002 IN THE SURVEY FILES FOR TOWNSHIP 17-12, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 10-17-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" X 18" REBAR** FOR THE NORTH 1/4 CORNER OF SECTION 10-17-12 IN THE CENTER OF THE ROAD AND IN LINE WITH THE FENCE TO THE SOUTH.
 - 1) 36.35' NE TO A NAIL IN THE TOP OF THE WEST BRACE POST
 - 2) 23.10' SOUTH TO A NAIL IN THE NORTH SIDE POST 6" FROM THE TOP OF THE POST
 - 3) IN THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
 - 4) IN LINE WITH FENCES TO THE NORTH AND SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,622.90' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 10-17-12

NORTH QUARTER CORNER 10-17-12