

NORTH 1/4 CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 12 EAST

- 1) ON PAGE 487 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-17-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 32.15 CHAINS WEST TO THE 17' X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 12" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-17-12

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 14, 2008 FOR PROJECT NUMBER 08137-02, SURVEY F18002 IN THE SURVEY FILE FOR TOWNSHIP 17-12 FOR A SURVEY OF THE NORTHEAST 1/4 OF SECTION 18-17-12 FOR MILFORD, SAID THAT HE SEARCHED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 18-17-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED** IN EAST-WEST POSITION AND **LOST** IN NORTH SOUTH POSITION. HE RESET THE CORNER ON TRUE LINE FROM THE NORTHWEST AND NORTHEAST SECTION CORNERS, AND IN LINE WITH A FENCE TO THE SOUTH AND A HEDGE TO THE NORTH. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 18-17-12.
 - 1) 34.2' SSW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 2) 30.2' SOUTH TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 3) 37.0' NW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
 - 4) 36.3' NE TO A 40 D NAIL & WASHER IN THE SOUTH FACE OF A CORNER FENCE POST
 - 5) 1.5' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 290 EAST-WEST
 - 6) IN LINE WITH A FENCE TO THE SOUTH AND A HEDGE TO THE NORTH
 - 7) 16' EAST TO A LINE OF FENCE TO THE NORTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,134.06' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 18-17-12
 - 2) 1,502.61' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE WEST TRACT
 - 3) 2,646.23' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 18-17-12
 - 4) 2,645.44' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 18-17-12
 - 5) 5,285.36' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 18-17-12

NORTH QUARTER CORNER 18-17-12