

NORTH 1/4 CORNER SECTION 24, TOWNSHIP 17 SOUTH, RANGE 12 EAST

- 1) ON PAGE 470 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 17" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 24-17-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.93 CHAINS WEST TO THE 20" X 16" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-17-12
 - 2) 39.94 CHAINS EAST TO THE 22" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13 & 24 ON THE EAST TOWNSHIP LINE

- 2) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY RECORDED IN VOLUME 429, PAGE 115 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 13, 1986, SURVEY F24001 IN THE SURVEY FILE FOR TOWNSHIP 17-12 IN THE COUNTY SURVEYOR'S OFFICE FOR A SURVEY OF THREE TRACTS IN THE SOUTHEAST 1/4 OF SECTION 24-17-12 DATED OCTOBER 28, 1986, SAID THAT **HE FOUND THE GLO STONE WITH THE LONG AXIS NORTH-SOUTH AT 5" DEEP** AT THE NORTH 1/4 CORNER OF SECTION 24-17-12 IN LINE WITH THE FENCES TO THE NORTH AND SOUTH.
 - 1) IN LINE WITH FENCES TO THE NORTH AND SOUTH
 - 2) 34.65' SE TO A PK NAIL IN A GATE POST
 - 3) 37.3' NE TO A PK NAIL IN A POWER POLE
 - 4) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,637.14' WEST TO THE GLO STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 24-17-12
 - 2) 2,649.14' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HEH SET FOR THE CENTER OF SECTION 24-17-12
 - 3) 5,290.79' SOUTH TO THE GLO STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 24-17-12
 - 4) 2,637.83' EAST TO THE GLO STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 24-17-12

NORTH QUARTER CORNER 24-17-12