

NORTH 1/4 CORNER SECTION 27, TOWNSHIP 17 SOUTH, RANGE 12 EAST

- 1) ON PAGE 477 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 22 & 27-17-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST TO THE 23" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-17-12
 - 2) 39.95 CHAINS EAST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-17-12
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 103, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 103 DATED MAY 29 & 30, 1885 ORDERED BY WALTER BUSHNELL TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 27-17-12 INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 27-17-12 ON THIS **PERMANENT SURVEY**.
- 3) **REA PIN:** REA BOOK 30 ON PAGE 29 SAYS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 27-17-12 MIDWAY BETWEEN THE STONE THAT THEY FOUND AT THE NORTHWEST CORNER OF SECTION 27-17-12 AND THE PIN AND WOODEN STAKE THAT THEY FOUND AT THE NORTHEAST CORNER OF SECTION 27-17-12, AND 2,647 FEET FROM EACH CORNER.
 - 1) 24' SOUTH TO A WITNESS PIN 8.5' EAST OF A TELEPHONE POLE
- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 31, 1985, FOR JOB NUMBER 85134, SURVEY F22002 IN THE SURVEY FILE FOR TOWNSHIP 17-12 FOR A SURVEY OF THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 22-17-12 AND RECORDED IN VOLUME 419 ON PAGE 887 IN THE REGISTER OF DEEDS OFFICE ON OCTOBER 28, 1885, SAID THAT **HE FOUND A #6 SQUARE REBAR AT ABOUT 2 FEET DEEP** AT THE SOUTH 1/4 CORNER OF SECTION 22-17-012. **HE STRAIGHTENED THIS OLD MONUMENT AND HE RAISED IT TO A DEPTH OF 6"**. HE SAID THAT THIS REBAR IS OF UNCERTAIN ORIGIN BUT HE ACCEPTED IT AS THE SOUTH 1/4 CORNER OF SECTION 22-17-12.
 - 1) 57.4' NE TO A PK NAIL IN A POWER POLE
 - 2) 25.0' NORTH TO A 1/2" X 24" REBAR WITH HIS "LS 752" CAP
 - 3) 2.0' NORTH TO THE TRAVELED WAY OF THE ROAD EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.75' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-17-12
 - 2) 1,327.34' NORTH TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16TH CORNER OF THE SE1/4 OF SECTION 22-17-12
 - 3) 2,654.68' NORTH TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 22-17-12
 - 4) 5,295.83' NORTH TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 22-17-12
 - 5) 1,325.25' EAST TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH 1/16TH CORNER OF THE SE1/4 OF SECTION 22-17-12
 - 6) 2,650.5' EAST TO THE #4 IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 22-17-12
- 5) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, SAID THAT **HE FOUND THE 3/4" SQUARE REBAR** AT THE NORTH 1/4 CORNER OF SECTION 27-17-12 FROM HIS 1985 TIES ON FILE IN THE COUNTY SURVEYORS OFFICE.
HIS TIES ARE ON PAGE 2

- 1) 57.4' NE TO A PK NAIL IN A POWER POLE
- 2) 25.0' NORTH TO A 1/2" X 24" CAPPED REBAR
- 3) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST

NORTH QUARTER CORNER 27-17-12