

NORTH 1/4 CORNER SECTION 35, TOWNSHIP 17 SOUTH, RANGE 12 EAST

- 1) ON PAGE 473 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-17-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.87 CHAINS WEST TO THE 18" X 14" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-17-12
 - 2) 39.88 CHAINS EAST TO THE 24" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-17-12
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A **PERMANENT SURVEY** RECORDED IN VOLUME 36 ON PAGE 4 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY F26003 IN THE SURVEY FILE FOR TOWNSHIP 17-12, FOR A SURVEY DATED MARCH 12, 1883 TO ESTABLISH THE 1/4 CORNER ON THE WEST SIDE AND THE CENTER CORNER OF SECTION 26-17-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 26-17-12 ON THIS **PERMANENT SURVEY**.
- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-12 SHOWS A **STONE** AT THE "SW CORNER SE1/4 SECTION 26-17-12".
 - 1) 26.9' NW TO A 6" HEDGE POST
 - 2) 22.6' NE TO A CORNER FENCE POST
 - 3) 26.5' SE TO A CORNER FENCE POST
 - 4) 28.9' SW TO A 7" HEDGE POST
- 4) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 18 AT THE BOTTOM OF THE PAGE SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 26-17-12".
 - 1) 22.6' NNE TO THE NEAR FACE OF AN 8" HEDGE CORNER FENCE POST
 - 2) 26.5' SSE TO THE NEAR FACE OF A 6" HEDGE CORNER FENCE POST
 - 3) 28.9' SW TO THE NEAR FACE OF A 7" HEDGE FENCE POST
 - 4) 26.9' NW TO THE NEAR FACE OF A 6" HEDGE FENCE POST

NORTH QUARTER CORNER 35-17-12