

NORTHWEST CORNER SECTION 35, TOWNSHIP 17 SOUTH, RANGE 12 EAST

- 1) ON PAGE 473 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 5"** FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-17-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.87 CHAINS EAST TO THE 19" X 12" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-17-12
 - 2) 79.75 CHAINS EAST TO THE 24" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-17-12

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 39 DATED DECEMBER 5, 1882, FOR A ROAD IN TOWNSHIP 17, RANGE 12 FOR FRED BERRETT, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-17-12 TO AT THE TERMINUS OF THIS ROAD SURVEY. THERE IS NO WIDTH RECORDED ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-12 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY

- 3) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 203 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 398 TO 400 PETITIONED BY FRED BERRETT AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-12 [PACKET 482 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 5, 1882, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JANUARY 3, 1883 AS NOTED BY HUGH F. HOLMES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 22, 1883 AS NOTED BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 35-17-12 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-12 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 103, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 103 DATED MAY 29 & 30, 1885 ORDERED BY WALTER BUSHNELL TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 27-17-12 INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 27-17-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1.318+['] WEST TO THE 2" X 8" X 16" LIMESTONE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 27-17-12
 - 2) 2,636.5' WEST TO THE ORIGINAL STONE HE FOUND AND **HE RESET** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 27-17-12
 - 3) 5,273' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-17-12

- 5) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 157, A ROAD SURVEY IN SURVEY BOOK "F" ON PAGE 114 DATED AUGUST 17, 1888 FOR A ROAD IN TOWNSHIP 17, RANGE 12, SAID THAT **HE SET A 15" X 10" X 2-1/2" LIMESTONE MARKED "R/1M"** FOR THE NORTHEAST CORNER OF SECTION 34-17-12 FOR THE TERMINUS OF THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD GOING WEST ONE MILE, LYING 20 FEET EACH SIDE OF THE SECTION LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR ONE MILE TO THE 15" X 5" X 3-1/2" STONE MARKED "R" HE SET FOR THE NORTHWEST CORNER OF SECTION 34-17-12 TO BEGIN THIS ROAD SURVEY

- 6) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-12 SHOWS A **STONE** AT THE "SW CORNER SECTION 26-17-12".
 - 1) 31' NE TO A CORNER FENCE POST
 - 2) 30' NW TO A CORNER FENCE POST
 - 3) 48.3' SE TO A MULBERRY TREE

- 7) KRETSINGER TIE BOOK NUMBER 13 SHOWS A **STONE** AT THE NORTHWEST CORNER OF SECTION 35.
 - 1) 30' NW TO A 7" HEDGE CORNER POST
 - 2) 31' NE TO A 10" HEDGE CORNER POST
 - 3) 48.3' SW TO THE NEAR FACE OF 3 @ 6" MULBERRY TREE

- 8) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 17 AT THE TOP OF THE PAGE SHOWS A **STONE** AT THE "SE CORNER SECTION 27-17-12".
 - 1) 31' NE TO THE NEAR FACE OF A 10" HEDGE CORNER FENCE POST
 - 2) 48.3' SW TO THE NEAR FACE OF A 6" MULBERRY TREE – THE NORTH OF 3 TREES
 - 3) 30' NW TO THE NEAR FACE OF A 7" HEDGE CORNER FENCE POST

- 9) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 16, 1997, FOR A SURVEY FOR CHARLES RAYL, SURVEY F34001 IN THE SURVEY FILE FOR TOWNSHIP 17-12 TO ESTABLISH THE NORTHEAST QUARTER AND NORTHWEST QUARTER OF SECTION 34-17-12, SAID THAT HE EXCAVATED WITH A COUNTY GRADER FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 34-17-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. HE RESET THIS CORNER IN THE CENTER OF THE NORTH-SOUTH ROAD AND IN THE CENTER OF THE RIGHT-OF-WAY OF THE ROAD TO THE EAST. HE SAID THAT THIS POSITION CHECKED WITH THE WITNESS TIES ON FILE WITH THE COUNTY SURVEYOR THAT WERE CONTRIBUTED TO THE KRETSINGER COLLECTION. **HE SET A 1/2" REBAR WITH HIS "LS 82" CAP** FOR THE NORTHEAST CORNER OF SECTION 34-17-12.
 - 1) 21.3' NORTH TO A LINE OF FENCE TO THE EAST
 - 2) 21.3' SOUTH TO A LINE OF FENCE TO THE EAST
 - 3) 34.6' SW TO THE NEAR FACE OF A STEEL GATE POST
 - 4) 2,646.29' WEST TO THE NORTH 1/4 CORNER OF SECTION 34-17-12

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,656.88' SOUTH TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 34-17-12
- 2) 2,646.29' WEST TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 34-17-12
- 3) 5,292.58' WEST TO THE 5/8" BENT REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-17-12 AND **HE REPLACED** WITH A 1/2" REBAR WITH HIS "LS 82" CAP

NORTHWEST CORNER 35-17-12