

NORTHEAST CORNER SECTION 03, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 95 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 16" X 3-1/2"** FOR THE CORNER TO SECTIONS 2 & 3-17-13 ON THE TOWNSHIP LINE AND THE COUNTY LINE ON DECEMBER 31, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.40 CHAINS SOUTH ON THE COUNTY LINE TO THE 24" X 10" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-17-13 ON OCTOBER 11, 1860
 - 2) 79.40 CHAINS SOUTH ON THE COUNTY LINE TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-17-13 ON OCTOBER 11, 1960
 - 3) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 20" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 3-17-13
 - 4) 80.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE 24" X 14" X 2-1/2" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-17-13
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGE 278 FOR ROAD NUMBER 69 AND DATED JULY 1880, SAID THAT **HE FOUND** THE SOUTHEAST CORNER OF SECTION 34-16-13 ON THE TOWNSHIP LINE AND THE LYON AND OSAGE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY ON THE COUNTY LINE.

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 129 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 102 TO 104 PETITIONED BY M. LUNGREN AND OTHERS FOR A ROAD IN TOWNSHIP 16-13 ON THE LYON AND OSAGE COUNTY LINE [PACKET 381 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 24, 1881, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 5, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE AND THE TOWNSHIP LINE AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 6 MILES TO THE NORTHEAST CORNER OF SECTION 3-16-13 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 233 DATED SEPTEMBER 24, 1881, FOR A ROAD SURVEY IN TOWNSHIP 16-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 34-16-13 ON THE TOWNSHIP LINE AND THE LYON AND OSAGE COUNTY LINE AT THE TERMINUS OF THIS ROAD SURVEY ON THE OSAGE COUNTY LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE COUNTY LINE FOR 6 MILES TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 3-16-13 ON THE 3RD STANDARD PARALLEL TO COMMENCE THIS ROAD SURVEY
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 173 AND DATED MAY 1904, ORDERED BY J. W. MAVITY, OSAGE COUNTY SURVEYOR AT THE REQUEST OF J. J. DAHL, AGENT FOR TILLIE SLUSSER, AND CHARLES LINDBLOOM OF OSAGE COUNTY FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY

ESTABLISHING THE EAST LINE OF SECTION 3-17-13 AND THE EAST LINE OF SECTION 34-16-13 ON THE LYON AND OSAGE COUNTY LINE AND RUN SUCH LINES AS NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 22" X 9" X 2" STONE MARKED WITH A PLUS ("+") ON THE SOUTH SIDE** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 3-17-13 ON THE TOWNSHIP LINE AND THE LYON AND OSAGE COUNTY LINE ON THIS JOINT **PERMANENT SURVEY** WITH THE OSAGE COUNTY SURVEYOR. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGE 46 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 135" IN MISCELLANEOUS DRAWER NUMBER 7 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.45 CHAINS WEST ON THE TOWNSHIP LINE TO THE GOVERNMENT STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 3-17-13
- 2) 39.50 CHAINS SOUTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 3-17-13
- 3) 79.32 CHAINS SOUTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 3-17-13
- 4) 39.42 CHAINS NORTH ON THE COUNTY LINE TO THE ORIGINAL GOVERNMENT STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 34-16-13 [**NOTE: HE RESET** THE ORIGINAL GOVERNMENT STONE AT 1/2 THE DISTANCE AND 8 LINKS SOUTH OF THE STAKE THAT HE SET AT 40 CHAINS, MAKING THE CORRECT DISTANCE **39.92 CHAINS** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 5) 79.84 CHAINS NORTH ON THE COUNTY LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-16-13
- 6) 39.45 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 2-17-13 IN OSAGE COUNTY

NORTHEAST CORNER 03-17-13