

**NORTHWEST CORNER SECTION 06, TOWNSHIP 17 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 95 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 12" X 5"** FOR THE CORNER TO TOWNSHIPS 16 & 17 SOUTH, RANGES 12 & 13 EAST AT THE NORTHWEST CORNER OF SECTION 6-17-13 ON DECEMBER 29, 1855.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.35 CHAINS EAST ON THE TOWNSHIP LINE TO THE 18" X 10" X 3" SANDSTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 6-17-13
  - 2) 43.25 CHAINS EAST ON THE TOWNSHIP LINE TO THE WEST BOUNDARY OF THE SAC & FOX INDIAN LANDS
  - 3) 79.35 CHAINS EAST ON THE TOWNSHIP LINE TO THE 20" X 18" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-17-13
  - 4) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 3" LIMESTONE THE SET FOR THE WEST 1/4 CORNER OF SECTION 6-17-13
  - 5) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-17-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 33, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 33 DATED MAY 16 & 17, 1870 TO ESTABLISH SECTION AND 1/4 SECTION CORNERS ON THE RANGE LINE BETWEEN RANGES 12 & 13 IN TOWNSHIP 17, SAID THAT SAID THAT HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE CORNER COMMON TO SECTIONS 24-15-19-30 TO **THE STONE HE FOUND AT THE TOWNSHIP CORNER**, A DISTANCE OF 4 MILES AND 62 FEET. AND HE FELL 50 FEET WEST OF THE TOWNSHIP CORNER ON THIS **PERMANENT SURVEY**.
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 212 DATED MAY 23 & 24, 1878 ORDERED BY THOMAS C. NICCUM FOR A SURVEY IN THE NORTHEAST 1/4 OF SECTION 6-17-13, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-13 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 6-17-13 TO RESET THE NORTHEAST CORNER OF SECTION 6-17-13 ON THE TOWNSHIP LINE.
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 138, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 219 DATED DECEMBER 12, 1905 FOR A ROAD IN TOWNSHIP 17, RANGES 12 & 13 FOR MARTIN HANSON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE AT 25 FEET SOUTH AND 25 FEET EAST OF THE CORNER OF AN OSAGE HEDGE** AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-13 TO BEGIN THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 40.22 CHAINS TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-17-13; THEN CONTINUES SOUTH ON THE RANGE LINE FOR 40.11 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-17-13 AT 3' NORTH OF A HEDGE; THEN EAST LAYING THE ENTIRE ROAD ON THE NORTH SIDE OF THE HEDGE FOR 12.55 CHAINS TO THE CENTER OF A PUBLIC ROAD AND THERE ENDING THIS ROAD SURVEY
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 610 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 309 THROUGH 312 PETITIONED BY MARTIN HANSON AND OTHERS FOR A

ROAD IN TOWNSHIP 17-13 [PACKET 760 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 12, 1905, AND WAS GRANTED AS A 40 FOOT ROAD ON JANUARY 4, 1906 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE AT 25 FEET SOUTH AND 25 FEET EAST OF THE CORNER OF AN OSAGE HEDGE** AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-13 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION

2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE FOR 40.22 CHAINS TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-17-13; THEN CONTINUES SOUTH ON THE RANGE LINE FOR 40.11 CHAINS TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 6-17-13 AT 3' NORTH OF A HEDGE; THEN EAST LAYING THE ENTIRE ROAD ON THE NORTH SIDE OF THE HEDGE FOR 12.55 CHAINS TO THE CENTER OF A PUBLIC ROAD AND THERE ENDING THIS ROAD SURVEY

6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 150, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 231 DATED MAY 8, 1906 FOR THE MILLER BROTHERS FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE NORTH 1/4 CORNER, THE EAST 1/4 CORNER, THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 19; THE SOUTHEAST CORNER AND THE SOUTH 1/4 CORNER AND THE EAST 1/4 CORNER OF SECTION 20; THE SOUTH 1/4 CORNER, SOUTHEAST CORNER, EAST 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 31, AND THE LINE BETWEEN THE EAST AND WEST 1/2 OF THE WEST 1/2 OF SECTION 32, ALL IN TOWNSHIP 16, RANGE 13; AND ALSO THE NORTH 1/4 CORNER, NORTHEAST CORNER, SOUTH 1/4 CORNER AND SOUTHEAST CORNER OF SECTION 25, TOWNSHIP 16, RANGE 12 AND OTHER SUCH CORNERS AND LINES CONNECTING THEREWITH AS MAY BE NECESSARY, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE SOUTHWEST CORNER OF SECTION 31-16-13 ACCORDING TO THE AFFIRMATION OF R. E. BURNHAM ON THIS **PERMANENT SURVEY**. THERE IS ADDITIONAL INFORMATION IN PACKET "M 84" IN MISCELLANEOUS DRAWER NUMBER 4 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

1) 39.57 CHAINS EAST ON THE TOWNSHIP LINE TO THE LOCATION FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 31-16-13  
2) 43.12 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE SET ON THE INDIAN RESERVE LINE ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 31-16-13  
3) 79.80 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-16-13  
4) 99.86 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 32-16-13  
5) 119.92 CHAINS EAST ON THE TOWNSHIP LINE TO THE LOCATION FOR THE SOUTH 1/4 CORNER OF SECTION 32-16-13  
6) 160.04 CHAINS EAST ON THE TOWNSHIP LINE TO THE LOCATION FOR THE SOUTHEAST CORNER OF SECTION 32-16-13

7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY HOWARD E. BROWN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 91 BY THE NOTICE OF WILL WHITMORE TO DETERMINE THE BOUNDARIES OF THE SOUTHWEST 1/4 AND LOT 2 OF THE NORTHWEST 1/4 OF SECTION 6-17-13, SAID THAT **HE FOUND THE STONE** AT THE TOWNSHIP CORNER AT THE NORTHWEST CORNER OF SECTION 6-17-13 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THIS SECTION CORNER IS ALSO THE NORTHWEST CORNER OF GOVERNMENT LOT 1. THE SURVEY WAS CONDUCTED

APRIL 9, 10, 11, 16 & 17, 1913. SEE PACKET "M 177" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,326.6' SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE SW1/4 OF THE NW1/4 OF SECTION 6-17-13 AND THE NORTHWEST CORNER OF GOVERNMENT LOT 2
  - 2) 2,653.2' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-17-13 AND THE SOUTHWEST CORNER OF GOVERNMENT LOT 2
  - 3) 2,574' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 6-17-13
  - 4) 2,808.3' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND ON THE INDIAN LINE AT THE NORTHEAST CORNER OF GOVERNMENT LOT 1
  - 5) 5,232.48' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-17-13
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 19, 2005, FOR PROJECT NUMBER 05147-02, SURVEY F01001 IN THE SURVEY FILE FOR TOWNSHIP 17-12 OF THE EAST AND WEST "HALVES" OF THE FRACTIONAL NORTHEAST 1/4 OF SECTION 1-17-12 FOR MALLEIN, SAID THAT HE EXCAVATED FOR THE STONE AT THE NORTHEAST CORNER OF SECTION 1-17-12 ON THE RANGE LINE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHEAST CORNER OF SECTION 1-17-12 PER ALVA J. SMITH'S TIES TO THE END OF THE HEDGE TO THE NORTHWEST AS RECORDED IN PERMANENT SURVEY BOOK "F" AT PAGE 219. HE NOTED ON HIS SURVEY DRAWING THAT THIS IS ALSO THE NORTHEAST CORNER OF GOVERNMENT LOT 1 IN THE FRACTIONAL NORTHEAST 1/4 OF SECTION 1-17-12.
- 1) 19.6' NNW TO A 40 D NAIL & WASHER IN THE TOP OF A CORNER FENCE POST
  - 2) 34.3' NW TO A 40 D NAIL & WASHER IN A 40" HEDGE TREE
  - 3) 27.3' SE TO A 40 D NAIL & WASHER IN THE SIDE OF A CORNER FENCE POST
  - 4) 20.0' SOUTH TO A LINE OF FENCE TO THE WEST - EXTENDED
  - 5) IN THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 310 EAST-WEST
  - 6) 5.0' WEST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "V" TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,653.30' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 1-17-12
- 2) 1,323.79' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 1-17-12 [AKA NORTHWEST CORNER OF GOVERNMENT LOT 1]
- 3) 2,647.58' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 1-17-12 [AKA NORTHWEST CORNER OF GOVERNMENT LOT 2]
- 4) 5,287.89' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 1-17-12 [AKA NORTHWEST CORNER OF GOVERNMENT LOT 4]

NORTHWEST CORNER 06-17-13