

NORTHWEST CORNER SECTION 07, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 94 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE CORNER TO SECTIONS 6 & 7-17-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 29, 1885.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-17-13
- 2) 80.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIP 16 & 17 SOUTH, RANGES 12 & 13 EAST AT THE NORTHWEST CORNER OF SECTION 6-17-13
- 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 7-17-13
- 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-17-13
- 5) 40.00 CHAINS EAST TO THE 22" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-17-13
- 6) 42.86 CHAINS EAST TO THE 19" X 10" X 3" LIMESTONE THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX RESERVATIONS LANDS
- 7) 78.86 CHAINS EAST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-17-13

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 33, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 33 DATED MAY 16 & 17, 1870 TO ESTABLISH SECTION AND 1/4 SECTION CORNERS ON THE RANGE LINE BETWEEN RANGES 12 & 13 IN TOWNSHIP 17, SAID THAT HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE CORNER COMMON TO SECTIONS 24-15-19-30 TO THE STONE THAT HE FOUND AT THE TOWNSHIP CORNER, A DISTANCE OF 4 MILES AND 62 FEET, AND HE FELL 50 FEET WEST OF THE TOWNSHIP CORNER. **HE SET A STONE** FOR THE PERMANENT CORNER COMMON TO SECTIONS 1-12-6-7 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 34, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 34 DATED MAY 19, 1870 TO ESTABLISH THE SOUTH 1/4 CORNER OF SECTION 1-17-12 AND THE CENTER OF SECTION 1-17-12, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 1-17-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 2,651-1/2' WEST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 1-17-12
 - 2) 5,303' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 1-17-12
- 4) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** NUMBER 63 RECORDED IN SURVEY BOOK "B" ON PAGE 61 DATED JULY, 1870, TO DIVIDE THE (WATERLOO TOWNSITE) NORTHWEST 1/4 OF SECTION 7 AND THE SOUTHWEST 1/4 OF SECTION 6 INTO FIVE PARTS OF EQUAL VALUE, ALL IN TOWNSHIP 17 AND RANGE 13, SAID THAT **HE FOUND THE STONE** AT THE CORNER TO SECTIONS 6, 7, 12 & 1 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 50 RODS EAST TO THE STONE THAT HE SET FOR A TRACT CORNER
- 2) 41.60 CHAINS EAST TO THE STONE HE FOUND ON THE SAC & FOX LINE

CONTINUED ON PAGE 2

- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 138, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 219 DATED DECEMBER 12, 1905 FOR A ROAD IN TOWNSHIP 17, RANGES 12 & 13 FOR MARTIN HANSON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE AT 3 FEET NORTH OF A HEDGE** AT THE SOUTHWEST CORNER OF SECTION 6-17-13 ON THE RANGE LINE AT A TURN ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 40.11 CHAINS TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-17-13; THEN CONTINUES NORTH ON THE RANGE LINE FOR 40.22 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-17-13 ON THE TOWNSHIP LINE, AT 25 FEET NORTH AND 25 FEET EAST OF THE CORNER OF AN OSAGE HEDGE, TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST LAYING THE ENTIRE ROAD ON THE NORTH SIDE OF THE HEDGE FOR 12.55 CHAINS TO THE CENTER OF A PUBLIC ROAD AT THE TERMINUS OF THIS ROAD SURVEY
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 610 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 309 THROUGH 312 PETITIONED BY MARTIN HANSON AND OTHERS FOR A ROAD IN TOWNSHIP 17-13 [PACKET 760 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 12, 1905, AND WAS GRANTED AS A 40 FOOT ROAD ON JANUARY 4, 1906 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, SAID THAT **HE FOUND THE STONE AT 3 FEET NORTH OF A HEDGE** AT THE SOUTHWEST CORNER OF SECTION 6-17-13 ON THE RANGE LINE ON THIS ROAD SURVEY. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION
- 3) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 40.11 CHAINS TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 6-17-13; THEN CONTINUES NORTH ON THE RANGE LINE FOR 40.22 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 6-17-13 ON THE TOWNSHIP LINE, AT 25 FEET NORTH AND 25 FEET EAST OF THE CORNER OF AN OSAGE HEDGE, TO BEGIN THIS ROAD SURVEY
 - 4) THIS ROAD EXTENDS EAST LAYING THE ENTIRE ROAD ON THE NORTH SIDE OF THE HEDGE FOR 12.55 CHAINS TO THE CENTER OF A PUBLIC ROAD AT THE TERMINUS OF THIS ROAD SURVEY
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1992, FOR JOB NUMBER 90394, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A SURVEY OF THE NORTHEAST AND SOUTHEAST FRACTIONAL QUARTERS OF SECTION 7-17-13, SAID THAT **HE FOUND A ROCK** AT THE NORTHWEST CORNER OF SECTION 7-17-12 ON THE RANGE LINE AT THE PLACE INDICATED BY THE PHYSICAL EVIDENCE. NO OTHER STONE WAS FOUND IN THE AREA, AS THE EAST-WEST HEDGE ROW MENTIONED BY ALVA J. SMITH NO LONGER EXISTS 3' SOUTH OF THE STONE, BUT STILL EXISTS ABOUT 100 FEET TO THE WEST. THIS POSITION PROVED TO BE REASONABLE AND THE FOUND ROCK WAS **ACCEPTED** AS THE LOCATION OF THE NORTHWEST CORNER OF SECTION 7-17-13. **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP OVER THE ROCK** FOR THE NORTHWEST CORNER OF SECTION 7-17-13 ON THE RANGE LINE.
- 1) 55.2' NNE TO A CONCRETE NAIL & DISC IN A CORNER FENCE POST
 - 2) 39.5' EAST TO A 12" DIAMETER COTTONWOOD TREE
 - 3) 52.0' NNW TO A CONCRETE NAIL & DISC IN A POWER POLE
 - 4) 3.0' SOUTH TO A FENCE LINE EAST-WEST
 - 5) IN THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE NORTH EXTENDED
- HIS INFORMATION IS CONTINUED ON PAGE 3

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,795.59' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF GOVERNMENT LOT 8 ON THE INDIAN RESERVE LINE
- 2) 5,216.77' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 7-17-13
- 3) 5,281.33' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-17-13 THAT WAS SET BY MILLIKEN IN 1870

NORTHWEST CORNER 07-17-13