

NORTHWEST CORNER OF SECTION 08, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 632 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-17-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS NORTH TO THE 15" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-17-13
 - 2) 79.10 CHAINS NORTH TO THE 20" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-17-13 ON THE TOWNSHIP LINE
 - 3) 39.97 CHAINS EAST TO THE 17" X 13" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-17-13
 - 4) 79.94 CHAINS EAST TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-17-13
 - 5) 36.00 CHAINS WEST TO THE 19" X 10" X 3" LIMESTONE THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX RESERVATION LANDS
 - 6) 38.86 CHAINS WEST TO THE 22" X 14" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-17-13
 - 7) 78.86 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 6 & 7-17-13 ON THE WEST TOWNSHIP BOUNDARY

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 212 DATED MAY 23 & 24, 1878 ORDERED BY THOMAS C. NICCUM FOR A SURVEY IN THE NORTHEAST 1/4 OF SECTION 6-17-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 6-17-13 ON THIS **PERMANENT SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 6-17-13 TO RESET THE NORTHEAST CORNER OF SECTION 6-17-13 ON THE TOWNSHIP LINE.

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 213 DATED MAY 24 & 25, 1878 ORDERED BY JOHN COLEBURG FOR A SURVEY OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 5-17-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 5-17-13 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 5-17-13
 - 2) 160 RODS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 5-17-13
 - 3) 160 RODS, 6 LINKS NORTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 5-17-13

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 69 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 278 TO 280 PETITIONED BY VAL BEST AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-13 THAT HE SURVEYED ON MAY 24, 1880, WAS ESTABLISHED AT A 60 FOOT WIDE ROAD ON JULY 7, 1880, AND WAS RECORDED ON JULY 7, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 6-17-13 ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 6-17-13 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO A POINT 3,372 FEET EAST OF THE SOUTHEAST CORNER OF SECTION 5-17-13; THEN EXTENDS NORTH

FOR 888 FEET; THEN EXTENDS NORTHEASTERLY TO A POINT ON THE LYON AND OSAGE COUNTY LINE AT 287 FEET SOUTH OF THE EAST 1/4 CORNER OF SECTION 3-17-13 AT THE TERMINUS OF THIS ROAD SURVEY

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 144 DATED OCTOBER 10, 1882 AT THE REQUEST OF JOHN DICKSON TO SURVEY THE NORTHWEST 1/4 OF SECTION 8-17-13, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 8-17-13 ON THIS **INFORMAL SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 19.97-1/2 CHAINS SOUTH TO THE STONE HE SET FOR THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 8-17-13
- 2) 39.95 CHAINS SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 8-17-13

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 267 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 18 TO 20 PETITIONED BY JOHN DICKSON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-13 [PACKET 513 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1884, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 15, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 19, 1884 BY ROLAND LAKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 8-17-13 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-17-13 ON THE TOWNSHIP LINE TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 1 MILE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 8-17-13 AT THE TERMINUS OF THIS ROAD SURVEY

- 7) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 202
ON NOVEMBER 18, 1988, A PETITION SIGNED BY L. S. JENKINS, JR. AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-13 WAS PRESENTED TO THE COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON DECEMBER 15, 1988 AND THE FINAL ORDER DATED DECEMBER 15, 1988 ORDERED THAT THE FOLLOWING ROAD BE **VACATED AS PETITIONED:**

- 1) ONE (1) MILE SECTION LINE ROAD RUNNING NORTH AND SOUTH BETWEEN SECTIONS 7 AND 8, TOWNSHIP 17, RANGE 13 IN READING TOWNSHIP

- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1992, FOR JOB NUMBER 90394, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A SURVEY OF THE FRACTIONAL NORTHEAST AND SOUTHEAST QUARTERS OF SECTION 7-17-13, SAID THAT HE DEEMED THAT THE NORTHEAST CORNER OF SECTION 7-17-13 WAS **OBLITERATED** AS IT HAD BEEN EXCAVATED ABOUT 15 YEARS AGO AND THE STONE WAS **NOT** FOUND THEN. **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTHEAST CORNER OF SECTION 7-17-13 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER.

- 1) 37.5' SW TO A PK NAIL & SHINER IN A CORNER FENCE POST
- 2) 29.5' SE TO A PK NAIL & SHINER IN A POWER POLE
- 3) 35.2' NE TO A PK NAIL & SHINER IN A POWER POLE
- 4) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE NORTH
- 5) 2.0' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE EAST

HIS INFORMATION IS CONTINUED ON PAGE 3

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,321.00' SOUTH TO THE STONE HE FOUND AT THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 7-17-13 THAT WAS SET BY RICE IN 1882
 - 2) 2,642.00' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 7-17-13
 - 3) 5,284.00' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 7-17-13
 - 4) 2,421.18' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF LOT 8 ON THE NORTH LINE OF THE NE1/4 OF SECTION 7-17-13 AND THE WEST LINE OF THE INDIAN RESERVE LINE
 - 5) 5,216.77' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-17-13
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 25, 1998, FOR JOB NUMBER 97427, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A 6.0 ACRE TRACT OF LAND IN THE SOUTHEAST 1/4 OF SECTION 6-17-13, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS "LS 752" CAP** AT THE SOUTHEAST CORNER OF SECTION 6-17-13 FROM HIS SURVEY IN 1992.
- 1) 35.30' NE TO A PK NAIL & SHINER IN A POWER POLE
 - 2) 37.50' SW TO A PK NAIL & SHINER IN A CORNER FENCE POST
 - 3) 85.60' SE TO A 40 D NAIL IN A CORNER FENCE POST
 - 4) 1' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE NORTH
 - 5) 2.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 450.00' NORTH TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 6.0 ACRE TRACT
- 2) 2,650.16' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 6-17-13 ON THE TOWNSHIP LINE
- 3) 548.00' WEST TO THE #4 REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE 6.0 ACRE TRACT
- 4) 2,421.17' WEST TO THE #4 REBAR HE FOUND FROM A PREVIOUS SURVEY AT THE INDIAN RESERVE CORNER

NORTHWEST CORNER 08-17-13