

**NORTHWEST CORNER OF SECTION 15, TOWNSHIP 17 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 621 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 10" X 3"** FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-17-13.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.08 CHAINS EAST TO THE 19" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 15-17-13
  - 2) 80.16 CHAINS EAST TO THE 32" X 6" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10 & 15-17-13 ON THE TOWNSHIP LINE
  
- 2) L. P. HUNTOON, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 55, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 64 DATED MAY 7, 1870 TO DIVIDE THE NORTHEAST 1/4 OF SECTION 16-17-13 INTO EQUAL PARTS BY A LINE RUNNING NORTH-SOUTH, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 16-17-13 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 19.80 CHAINS WEST TO THE 4" X 4" MULBERRY POST THAT HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 16-17-13
  - 2) 39.60 CHAINS WEST TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 16-17-13
  
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 11, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 11 DATED FEBRUARY 15-18, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 15, 16, 21, & 22 AND TO ESTABLISH THE CENTER OF SECTION 15, ALL IN TOWNSHIP 17, RANGE 13, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 15-17-13 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 2,648' SOUTH TO THE STONE HE FOUND "BROKEN TO PIECES" AT THE WEST 1/4 CORNER OF SECTION 15-17-13, WHICH HE REPLACED WITH A "GOOD NEW STONE"
  - 2) 1,319-1/2' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 15-17-13
  - 3) 2,639' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 15-17-13
  
- 4) IN THE MATTER OF TWO ROADS IN TOWNSHIP 17-13 THAT WAS PETITIONED BY T. J. PRICE AND OTHERS RECORDED IN ROAD RECORD BOOK "A" ON PAGE 201 [PACKET 57 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE], THE VIEWERS RECOMMENDED THAT BOTH OF THE ROADS BE OPENED AT 50 FEET WIDE. THERE IS NO SURVEY IN THE PACKET AND ROAD RECORD BOOK "B" IN THE COUNTY CLERKS OFFICE IS MISSING. THE VIEWERS MET ON APRIL 15, 1872, AND THE ROADS WERE ORDERED FILED BY THE BOARD OF COUNTY COMMISSIONERS ON MARCH 18, 1872 AS ATTESTED TO BY DANIEL S. GILMORE, COUNTY CLERK. THE SECOND ROAD AS PETITIONED PASSES NEAR THE NORTHWEST CORNER OF SECTION 15-17-13.  
THE PETITION GIVES THE FOLLOWING INFORMATION:
  - 1) THIS SECOND ROAD EXTENDS WEST ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 9-17-13 TO BEGIN THIS SECOND ROAD
  - 2) THIS SECOND ROAD EXTENDS EAST ON THE SECTION LINES WITH DEVIATIONS DUE TO ELM CREEK AND BLUFFS TO END AT THE LYON AND OSAGE COUNTY LINE AT THE SOUTHEAST CORNER OF SECTION 10-17-13

CONTINUED ON PAGE 2

- 5) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 3 FOR A ROAD SURVEY IN TOWNSHIP 17-13 DATED MAY 17, 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 15-17-13 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINE FOR 66 FEET TO THE 13" X 5" X 3" ANGLE STONE HE SET; THEN DEVIATES NORTH OF THE SECTION LINE AND INTERSECTS THE SECTION LINE AT THE 12" X 8" X 3" ANGLE STONE AT A POINT 1,667 FEET WEST OF THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 15-17-13; THEN EXTENDS EAST ON THE SECTION LINE FOR 1,667 FEET TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 15-17-13 AT THE TERMINUS OF THIS ROAD SURVEY
- 6) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 166 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 250 AND 251 PETITION BY E. H. SPENCER AND OTHERS FOR THE VACATION AND RELOCATION OF A COUNTY ROAD IN TOWNSHIP 17-13 [PACKET 424 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 17 1882, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 15-17-13 TO BEGIN THIS ROAD SURVEY. THE ROAD **VACATED** WAS THE ANGLE ROAD SOUTH OF THE NORTH LINE OF SECTION 15-17-13.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) BEGINNING AT THE NORTHWEST CORNER OF SECTION 15-17-13; THENCE EAST ON THE SECTION LINE AT A VARIANCE OF 10°15' EAST FOR 66 FEET TO A SET ANGLE STONE; THEN N. 62°05' E. FOR 219' TO A SET ANGLE STONE; THENCE N. 30° E. FOR 197 FEET TO A SET ANGLE STONE; THENCE S. 76°30' E. FOR 716-1/2 FEET TO A SET ANGLE STONE; THENCE EAST ON THE SECTION LINE FOR 1,664 FEET TO THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 15-17-13 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) SAID ROAD IS LOCATED 60 FEET IN WIDTH, EXCEPT THAT PART ASCENDING THE HILL COURSE S. 76°30' E. FOR 716-1/2 FEET WHERE IT SHALL BE 50 FEET IN WIDTH SOUTH OF THE CENTERLINE AND 30' ON THE NORTH SIDE OF THE CENTERLINE

NORTHWEST CORNER 15-17-13