

NORTH 1/4 CORNER OF SECTION 16, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 626 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 9 & 16.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:
 - 1) 40.00 CHAINS WEST TO THE 22" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17
 - 2) 40.00 CHAINS EAST TO THE 22" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16

- 2) L. P. HUNTOON, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 55, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 64 DATED MAY 7, 1870 TO DIVIDE THE NORTHEAST 1/4 OF SECTION 16-17-13 INTO EQUAL PARTS BY A LINE RUNNING NORTH-SOUTH, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION-17-13 16 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.80 CHAINS EAST TO THE 4" X 4" MULBERRY POST THAT HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 16-17-13
 - 2) 39.60 CHAINS EAST TO THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-17-13

NORTH QUARTER CORNER 16-17-13