

**WEST 1/4 CORNER OF SECTION 16, TOWNSHIP 17 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 625 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 17-17-13.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 117 RECORDED IN SURVEY BOOK "A" ON PAGE 206 DATED MAY 18, 1869 TO RUN THE EAST AND WEST CENTERLINE OF SECTION 16-17-13 AND BLAZE THE LINE THROUGH THE TIMBER, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 16-17-13 ON THIS SURVEY.
- 3) L. P. HUNTOON, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 55, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 64 DATED MAY 7, 1870 TO DIVIDE THE NORTHEAST 1/4 OF SECTION 16-17-13 INTO EQUAL PARTS BY A LINE RUNNING NORTH-SOUTH, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 16-17-13 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 40.04 CHAINS EAST TO THE LIMESTONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 16-17-13
  - 2) 59.87-1/2 CHAINS EAST TO THE 4" DIAMETER MULBERRY STAKE THAT HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 16-17-13
  - 3) 79.71 CHAINS EAST TO THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 16-17-13
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY TO LOCATE A BRIDGE IN READING TOWNSHIP AT THE PLACE WHERE THE SECTION LINE BETWEEN SECTIONS 16 & 17-17-13 CROSSES 142 MILE CREEK RECORDED IN SURVEY BOOK "D" ON PAGE 51 DATED APRIL 4, 1882, SAID THAT **HE FOUND THE 1/4 STONE** AT THE WEST 1/4 CORNER OF SECTION 16-17-13 ON THIS SURVEY.
- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 144 DATED OCTOBER 10, 1882 AT THE REQUEST OF JOHN DICKSON TO SURVEY THE NORTHWEST 1/4 OF SECTION 8-17-13, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 17-17-13 ON THIS **INFORMAL SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.08 CHAINS NORTH TO THE "PROPER CORRECTION" FOR THE SOUTHEAST CORNER OF SECTION 8-17-13
  - 2) 80.16 CHAINS NORTH TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 8-17-13
  - 3) 120.24 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 8-17-13
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 12, 2009 FOR PROJECT NUMBER 09235-02, SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A 7.4 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 16-17-13 FOR BRIGGS, SAID THAT HE CONSIDERED THAT THE WEST 1/4 CORNER OF SECTION 16-17-13 WAS **LOST**. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 16-17-13 BASED ON THE FAS PLANS THAT HE FOUND IN THE COUNTY ENGINEER'S OFFICE.
  - 1) 67' SOUTH TO THE CENTERLINE OF AN ENTRANCE
  - 2) 71.45' SW TO A SPIKE & BOTTLE CAP IN THE TOP OF A GATE POST

HIS TIES ARE CONTINUED ON PAGE 2

- 3) 92.35' SSW TO A SPIKE & BOTTLE CAP IN THE TOP OF A GATE POST
- 4) IN THE CENTERLINE TRAVELED WAY OF ROAD ["X"] NORTH-SOUTH  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,647.73' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 16-17-13
- 2) 593.25' SOUTH TO THE P.O.B. OF THE 7.4 ACRE TRACT
- 3) 1,787.83' SOUTH TO THE SOUTHWEST CORNER OF THE 7.4 ACRE TRACT
- 4) 1,806.62' SOUTH TO THE 1/2" REBAR HE FOUND FROM THE FAS PLANS
- 5) 2,648.35' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 16-17-13

WEST QUARTER CORNER 16-17-13