

NORTHWEST CORNER OF SECTION 17, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 631 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-17-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.97 CHAINS EAST TO THE 16" X 15" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 8 & 17-17-13
 - 2) 79.94 CHAINS EAST TO THE 22" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 8, 9, 16 & 17-17-13
 - 3) 37.00 CHAINS WEST TO A 20" X 12" X 3" LIMESTONE SET ON THE WEST BOUNDARY OF THE SAC & FOX RESERVATION LANDS
 - 4) 39.70 CHAINS WEST TO THE 18" X 9" X 3-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-17-13
 - 5) 79.70 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18 ON THE WEST TOWNSHIP BOUNDARY

- 2) L. P. HUNTOON, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 63-1/2, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 62 DATED MAY 7, 1870 TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 17-17-13, STATES THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 17-17-13 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 25.06-1/4 CHAINS EAST TO THE 12" X 16" LIMESTONE THAT HE SET FOR A PROPERTY CORNER
 - 2) 40.10 CHAINS EAST TO THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-17-13

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 210 DATED MAY 14, 1878 ORDERED BY H. F. HOLMES TO ESTABLISH THE NORTHWEST AND SOUTHWEST CORNERS OF HIS LAND IN THE NORTHEAST 1/4 OF SECTION 18-17-13, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 18-17-13 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 149 RODS, 4.4 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST PROPERTY CORNER AT THE INTERSECTION OF THE NORTH LINE OF SECTION 18-17-13 WITH THE WEST BOUNDARY LINE OF THE SAC & FOX INDIAN TRUST LANDS

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 267 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 18 TO 20 PETITIONED BY JOHN DICKSON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-13 [PACKET 513 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 4, 1884, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 15, 1884 AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 19, 1884 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 8-17-13 AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-17-13 ON THE TOWNSHIP LINE TO BEGIN THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 5) COMMISSIONERS ROAD JOURNAL BOOK "B" ON PAGE 109:
IT WAS NOTED THAT THE FOLLOWING ROAD WAS **CLOSED** UNDER THE PROVISIONS OF 68-102 OF THE GENERAL STATUTES 1953 SUPPLEMENT BY A RESOLUTION OF THE BOARD OF COUNTY COMMISSIONERS DATED JANUARY 25, 1958:
- 1) BEGINNING AT THE NORTHEAST CORNER OF THE NORTH SIDE OF SECTION 13-17-12 THENCE [EAST] TO THE NORTHEAST CORNER OF THE NORTH SIDE OF SECTION 17-17-13.
- 6) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 157
ON MARCH 16, 1971 A PETITION SIGNED BY WALTER BRIGGS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-13 WAS PRESENTED TO ROSEMARY SPALDING, COUNTY CLERK. THE COUNTY COMMISSIONERS VIEWED THE ROAD ON MARCH 8, 1971 AND RECOMMENDED THAT THE FOLLOWING ROAD BE **VACATED:**
- 1) BEGINNING AT THE SOUTH END OF SECTION 7 AND 8-17-13 AND ENDING AT THE SOUTH ONE-HALF MILE, BETWEEN SECTIONS 7 AND 8-17-13, WITH **EXCEPTION** OF THE NORTH 50 FEET WHICH MUST REMAIN OPEN TO ALLOW ACCESS TO LAND ON THE WEST SIDE.
 - 2) **NOTE:** THIS IS THE SOUTH ONE-HALF MILE OF ROAD BETWEEN SECTIONS 7 AND 8-17-13
- 7) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 202
ON NOVEMBER 18, 1988, A PETITION SIGNED BY L. S. JENKINS, JR. AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 17-13 WAS PRESENTED TO THE COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS ON DECEMBER 15, 1988 AND THE FINAL ORDER DATED DECEMBER 15, 1988 ORDERED THAT THE FOLLOWING ROAD BE **VACATED AS PETITIONED:**
- 1) ONE (1) MILE SECTION LINE ROAD RUNNING NORTH AND SOUTH BETWEEN SECTIONS 7 AND 8, TOWNSHIP 17, RANGE 13 IN READING TOWNSHIP
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1992, FOR JOB NUMBER 90394, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A SURVEY OF THE FRACTIONAL NORTHEAST AND SOUTHEAST QUARTERS OF SECTION 7-17-13, SAID THAT HE PRODDED AND SEARCHED IN TIMBER, BETWEEN THE HIGH AND LOW BANKS OF THE CREEK, FOR THE STONE AT THE SOUTHEAST CORNER OF SECTION 7-17-13, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **LOST. HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTHEAST CORNER OF SECTION 7-17-13 BASED UPON THE PRORATED DISTANCE TO THE SOUTHEAST CORNER OF SECTION 8-17-13, THE DISTANCE TO THE INDIAN RESERVE LINE TO THE WEST, AND THE ALIGNMENT AND DISTANCE TO THE NORTH.
- 1) 11.7' SW TO A CONCRETE NAIL & DISC IN A 24" DIAMETER HACKBERRY TREE
 - 2) 41.1' ESE TO A CONCRETE NAIL & DISC IN A 72" DIAMETER COTTONWOOD
 - 3) 13.1' SOUTH TO A CONCRETE NAIL & DISC IN AN 18" DIAMETER HEDGE TREE
 - 4) 20.0' SOUTH TO A HEDGE LINE TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,466.27' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF LOT 5 ON THE WEST LINE OF THE INDIAN RESERVE LINE IN THE SOUTHEAST 1/4 OF SECTION 7-17-13
 - 2) 5,213.76' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-17-13 THAT WAS SET BY MILLIKEN IN 1870
 - 3) 5,303.58' EAST TO THE 1" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-17-13
 - 4) 2,642.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 7-17-13

HIS INFORMATION IS CONTINUED ON PAGE 3

- 5) 3,963.00' NORTH TO THE STONE HE FOUND AT THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 7-17-13 THAT WAS SET BY RICE IN 1882
- 6) 5,284.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 7-17-13

NORTHWEST CORNER 17-17-13