

**NORTHWEST CORNER SECTION 18, TOWNSHIP 17 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 94 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 4"** FOR THE CORNER TO SECTIONS 7 & 18-17-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 19, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 18-17-13
  - 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-17-13
  - 3) 40.00 CHAINS EAST TO THE 18" X 9" X 3-1/2" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-17-13
  - 4) 42.70 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET ON THE WEST BOUNDARY OF THE SAC & FOX RESERVATION LINE
  - 5) 79.70 CHAINS EAST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-17-13
- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 26 FOR THE "FOREST HILL TO WATERLOO ROAD" [PACKET 164 I THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT WAS SURVEYED MARCH 15 & 16, 1859 AND ESTABLISHED ON APRIL 4, 1959 IN COMMISSIONERS JOURNAL ON PAGE 59, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 13-17-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD TURNS TO THE NORTHEASTERLY TO THE SOUTH LINE OF WATERLOO TOWNSITE
  - 2) THIS ROAD EXTENDS SOUTH ON THE RANGE LINE TO THE EAST 1/4 CORNER OF SECTION 36-18-12 AT A TURN TO THE SOUTHWESTERLY TO THE NORTH 1/4 CORNER OF SECTION 1-19-12 AT A TURN TO THE SOUTH ON THE 1/2 SECTION LINE TO THE NORTH 1/4 CORNER OF SECTION 12-19-12 AT THE NORTHEAST CORNER OF THE TOWN OF FOREST HILL TO COMMENCE THIS ROAD SURVEY
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 33, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 33 DATED MAY 16 & 17, 1870 TO ESTABLISH SECTION AND 1/4 SECTION CORNERS ON THE RANGE LINE BETWEEN RANGES 12 & 13 IN TOWNSHIP 17, SAID THAT HE RAN THE RANGE LINE FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-13 TO THE STONE THAT HE FOUND AT THE TOWNSHIP CORNER, A DISTANCE OF 4 MILES AND 62 FEET, AND HE FELL 50 FEET WEST OF THE TOWNSHIP CORNER. **HE SET A STONE** FOR THE PERMANENT NORTHWEST CORNER OF SECTION 18-17-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 210 DATED MAY 14, 1878 ORDERED BY H. F. HOLMES TO ESTABLISH THE NORTHWEST AND SOUTHWEST CORNERS OF HIS LAND IN THE NORTHEAST 1/4 OF SECTION 18-17-13, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST OF SECTION 18-17-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 159 RODS, 22-1/2 LINKS SOUTH ON THE RANGE LINE TO THE 1' X 1' X 5" STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 18-17-13
- HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 319 RODS, 20 LINKS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-17-13
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 10 & 11 FOR ROAD NUMBER 3 BY A PETITION BY H. F. HOLMES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-13 [PACKET 105 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 3, 1878, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON JULY 7, 1878, AND WAS RECORDED ON NOVEMBER 26, 1878 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-13 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 70 RODS AND 23 LINKS TO A TURN TO THE SOUTHEASTERLY DUE TO 142 MILE CREEK
  - 2) SEE THE SURVEY FOR REMAINDER OF THE LOCATION OF THE TURNS IN THE ROAD THAT INTERSECTS THE NORTH LINE OF SECTIONS 18-17-13 IN SEVERAL LOCATIONS BEFORE THE ROAD INTERSECTS THE SECTION LINE AT 288 RODS AND 35 LINKS WEST OF THE NORTHEAST CORNER OF SECTION 17-17-13 AND THEN CONTINUES EAST ON THE SECTION LINE FOR 288 RODS AND 35 LINKS TO THE NORTHEAST CORNER OF SECTION 17-17-13 TO COMMENCE THIS ROAD SURVEY
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" AT THE LEFT SIDE OF PAGE 161 DATED SEPTEMBER 2, 1878, 1878, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 18-17-13 ON THE RANGE LINE TO END THIS ROAD SURVEY THAT EXTENDED TWO MILES EAST TO THE NORTHEAST CORNER OF SECTION 17-17-13.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) 70 RODS, 23 LINKS EAST TO AN ANGLE STONE HE SET ON THIS ROAD SURVEY
- 7) COMMISSIONERS ROAD JOURNAL BOOK "B" ON PAGE 109:  
 IT WAS NOTED THAT THE FOLLOWING ROAD WAS **CLOSED** UNDER THE PROVISIONS OF 68-102 OF THE GENERAL STATUTES 1953 SUPPLEMENT BY A RESOLUTION OF THE BOARD OF COUNTY COMMISSIONERS DATED JANUARY 25, 1958:
- 1) BEGINNING AT THE NORTHEAST CORNER OF THE NORTH SIDE OF SECTION 13-17-12 THENCE [EAST] TO THE NORTHEAST CORNER OF THE NORTH SIDE OF SECTION 17-17-13.
- 8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 31, 1992, FOR JOB NUMBER 90394, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A SURVEY OF THE NORTHEAST AND SOUTHEAST FRACTIONAL QUARTERS OF SECTION 7-17-13, SAID THAT HE EXCAVATED FOR THE STONE THAT WAS SET BY ROBERT MILLIKEN [BOOK "B", PAGE 33, 1870] AT THE SOUTHWEST CORNER OF SECTION 7-18-13 ON THE RANGE LINE. **HE FOUND MILLIKEN'S STONE STANDING.** HE DID NOT SAY IF HE SET A REBAR BY THE STONE.
- 1) 40.2' SW TO THE EAST FACE OF A STEEL GATE POST SET IN CONCRETE
  - 2) 33.0' WEST TO THE EAST FACE OF A STEEL POST SET IN CONCRETE
  - 3) 1.5' SOUTH TO A FENCE LINE TO THE WEST
  - 4) 1.5' SOUTH TO A FENCE LINE TO THE EAST
  - 5) 30.0' EAST TO A LINE OF FENCE NORTH-SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 3

- 1) 2,747.49' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF LOT 5 IN THE SOUTHEAST 1/4 OF SECTION 7-17-13 ON THE WEST LINE OF THE INDIAN RESERVE LINE
- 2) 5,213.76' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 7-17-13
- 3) 10,517.34' EAST TO THE 1" IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF SECTION 8-17-13
- 4) 5,281.33' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-17-13

NORTHWEST CORNER 18-17-13