

NORTH 1/4 CORNER SECTION 22, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 621 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 14" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-17-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:
 - 1) 40.13 CHAINS WEST TO THE 20" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-17-13
 - 2) 40.12 CHAINS EAST TO THE 26" X 13" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-17-13 ON THE COUNTY LINE

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 116 RECORDED IN SURVEY BOOK "A" ON PAGE 205 DATED MAY 17, 1869 TO FIND THE SOUTHWEST CORNER OF SECTION 15, AND ALSO THE SOUTH LINE OF SAID SECTION, BEING IN TOWNSHIP 17, RANGE 13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-17-13 ON THIS SURVEY.

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 11, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 11 DATED FEBRUARY 15-18, 1870 TO ESTABLISH THE CORNER COMMON TO SECTIONS 15-16-21-22 AND TO ESTABLISH THE CENTER CORNER OF SECTION 15, ALL IN TOWNSHIP 17, RANGE 13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-17-13 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,659' EAST TO THE STONE FOUND AT THE SOUTHEAST CORNER OF SECTION 15-17-13

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 12, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 12 DATED FEBRUARY 18TH, 1870, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTIONS 22-17-13 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,051' WEST TO THE STONE HE SET ON THE SECTION LINE

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 29, 2005, FOR PROJECT NUMBER 05406-02, SURVEY F22001 IN THE SURVEY FILE FOR TOWNSHIP 17-13 FOR A SURVEY OF THE SOUTH LINE OF THE NORTH HALF OF THE NORTHWEST 1/4 OF SECTION 22-17-13 FOR DAVIES, SAID THAT HE SEARCHED FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 22-17-13. HE FOUND A PIECE OF STONE NEAR A CORNER FENCE POST SO HE CONSIDERED THAT THE CORNER WAS **OBLITERATED**. HE DEEMED THAT THE POST TO BE IN A REASONABLE POSITION, **SO HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF THE CORNER FENCE POST** FOR THE NORTH 1/4 CORNER OF SECTION 22-17-13.
 - 1) 24.85' SW TO A CONCRETE NAIL & SHINER IN A 10" TWIN KENTUCKY COFFEY TREE
 - 2) 11.4' NORTH TO A CONCRETE NAIL & SHINER IN A FENCE BRACE POST
 - 3) 6.0' SE TO A CONCRETE NAIL & SHINE INA 10" TWIN OAK TREE
 - 4) IN LINE WITH A FENCE TO THE EAST
 - 5) IN LINE WITH A FENCE TO THE NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,655.05' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 22-17-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 1,322.41' SOUTH TO THE THEORETICAL POSITION FOR THE EAST 1/16TH CORNER OF THE NW1/4 OF SECTION 22-17-13
- 3) 2,644.82' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 22-17-13
- 4) 5,289.64' SOUTH TO THE 3/4" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 22-17-13

NORTH QUARTER CORNER 22-17-13