

NORTHWEST CORNER OF SECTION 28, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 624 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 22" X 16" X 2-1/2"** FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-17-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS EAST TO THE 24" X 12" X 3" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 28-17-13
 - 2) 79.90 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-17-13

- 2) IN THE MATTER OF TWO ROADS IN TOWNSHIP 17-13 THAT WAS PETITIONED BY T. J. PRICE AND OTHERS RECORDED IN ROAD RECORD BOOK "A" ON PAGE 201 [PACKET 57 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE], THE VIEWERS RECOMMENDED THAT BOTH OF THE ROADS BE OPENED AT 50 FEET WIDE. THERE IS NO SURVEY IN THE PACKET AND ROAD RECORD BOOK "B" IN THE COUNTY CLERKS OFFICE IS MISSING. THE VIEWERS MET ON APRIL 15, 1872, AND THE ROADS WERE ORDERED FILED BY THE BOARD OF COUNTY COMMISSIONERS ON MARCH 18, 1872 AS ATTESTED TO BY DANIEL S. GILMORE, COUNTY CLERK. THE FIRST ROAD HAS A TURN AT THE SOUTHWEST CORNER OF SECTION 21-17-13.
THE PETITION GIVES THE FOLLOWING INFORMATION:
 - 1) THIS FIRST ROAD EXTENDS NORTH TO WHERE THE EMPORIA AND LAWRENCE STATE ROAD CROSSES ELM CREEK BETWEEN SECTIONS 32 & 33-16-13 TO COMMENCE THIS FIRST ROAD
 - 2) THIS FIRST ROAD EXTENDS EAST ON THE SECTION LINES FOR ONE MILE TO THE NORTHEAST CORNER OF SECTION 28-17-13 AT A TURN TO THE SOUTH

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 215 [PACKET 266 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY H. F. HOLMES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 17-13 THAT HE SURVEYED ON SEPTEMBER 16, 1874, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 5, 1874 AS ATTESTED BY J. S. CRAIG, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 29-17-13 TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE FOR 176.3 RODS TO A TURN TO THE SOUTHWESTERLY DUE TO DUCK CREEK; THEN INTERSECTS THE SECTION LINE AT 44.84 RODS NORTH OF THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-17-13 AND CONTINUES SOUTH ON THE SECTION LINE TO THE CORNER TO SECTIONS 32, 33, 4 & 5 ON THE TOWNSHIP LINE TO TOWNSHIPS 17 & 18, RANGE 13 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 41 OF THE 8TH TERM RECORDED IN SURVEY BOOK "C" ON PAGE 98, A ROAD SURVEY PETITIONED FOR BY HUGH R. HOLMES, ET. AL. DATED SEPTEMBER 16, 1874, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 29-17-13 TO BEGIN THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640' SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 29-17-13
 - 2) 2,909' SOUTH ON THE SECTION LINE TO AN ANGLE STONE HE SET ABOUT 50 FEET NORTH OF THE CENTER OF DUCK CREEK

- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 147 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 174 TO 176 PETITIONED BY RILEY SANDERS AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP

17-13 [PACKET 386 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON AUGUST 26, 1881, WAS ESTABLISHED AS A 60 FOOT WIDE ROAD ON OCTOBER 5, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON OCTOBER 17, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 20-17-13 AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 19-17-13 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 232 DATED SEPTEMBER 3, 1881, FOR A ROAD SURVEY IN TOWNSHIP 17-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 20-17-13 AT THE TERMINUS OF THIS ROAD SURVEY
- HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE FOR 2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 19-17-13 ON THE RANGE LINE TO COMMENCE THIS ROAD SURVEY
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-13 SHOWS A **STONE** AT THE "SW CORNER SECTION 21-17-13".
- 1) 6.8' WEST OF THE WEST EDGE OF A CULVERT
 - 2) 15.8' NE TO THE CORNER OF THE HEADWALL
 - 3) 17.1' SE TO THE CORNER OF THE HEADWALL

NORTHWEST CORNER 28-17-13