

WEST 1/4 CORNER OF SECTION 29, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 629 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 16" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 30-17-13.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 22 RECORDED IN SURVEY BOOK "A" ON PAGE 118 DATED MARCH 3, 1868 FOR A SURVEY OF W. JACOBY'S LAND, TO ESTABLISH THE CENTER CORNER, AND TO DIVIDE THE NORTHWEST 1/4 OF SECTION 30-17-13 NORTH AND SOUTH, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 30-17-13 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 319 RODS, 17 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 30-17-13 ON THE RANGE LINE
- 3) HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK 1 ON PAGE 57 AND DATED MARCH 1910, SHOWS A **STONE** AT THE WEST 1/4 CORNER OF SECTION 29-17-13 ON THIS **PERMANENT SURVEY**.
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 2, 1990, FOR JOB NUMBER 90195, SAID THAT HE CONSIDERED THAT THE WEST 1/4 CORNER OF SECTION 29-17-13 WAS **LOST**. **HE SET A PK NAIL IN THE BRIDGE DECK** FOR THE WEST 1/4 CORNER OF SECTION 29-17-13 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 29-17-13.
 - 1) 25.0' WEST AT RIGHT ANGLES TO A 1/2" REBAR WITH A CHANNEL POST
 - 2) 70' NORTH TO A 5/8 REBAR WITH A LYON COUNTY CAP
 - 3) 30' SOUTH TO A 5/8" REBAR WITH A LYON COUNTY CAP
 - 4) 2,645.44' NORTH TO THE NORTHWEST CORNER OF SECTION 29
 - 5) 2,645.44' SOUTH TO THE SOUTHWEST CORNER OF SECTION 29
 - 6) 6.0' EAST TO THE CENTERLINE OF THE BRIDGE AT THE SOUTH ENDHIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
 - 1) 2,645.44' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-17-13
 - 2) 2,645.44' SOUTH TO THE 5/8" CAPPED REBAR OVER THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-17-13
- 5) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 14, 2011 FOR BRIDGE REPLACEMENT PROJECT NUMBER 11-YW, BRIDGE 963.0-500.6, DID **NOT** FIND THE PK NAIL IN THE BRIDGE DECK AT THE WEST 1/4 CORNER OF SECTION 29-17-13. I CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. I RESET THE CORNER ON TRUE LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE SOUTHWEST CORNER OF SECTION 29-17-13 ACCORDING TO THE METHOD USED BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JULY 2, 1990 ON FILE IN THE COUNTY ENGINEER'S OFFICE. **I SET A MAG NAIL** IN THE ASPHALT DECK OF BRIDGE NUMBER 963.0-500.4 FOR THE WEST 1/4 CORNER OF SECTION 29-17-13. THE WEST 1/4 CORNER OF SECTION 29-17-13 IS LOCATED AT PROJECT SECTION LINE STATION 26+45.41
 - 1) 70.0' NORTH TO A FOUND 5/8" REBAR WITH A LYON COUNTY CAP
 - 2) 29.9' SOUTH TO A SET 5/8" REBAR WITH A LYON COUNTY CAP
 - 3) 25.1' SE TO THE BASE OF THE SOUTHEAST CORNER OF THE ANGLE IRON GUARDRAIL POST AT THE SOUTHEAST CORNER OF THE BRIDGE

MY TIES ARE CONTINUED ON PAGE 2

- 4) 7.75' WEST TO THE BASE OF THE SOUTHWEST CORNER OF THE ANGLE IRON GUARDRAIL POST AT THE SOUTHWEST CORNER OF THE BRIDGE
- 5) 48.0' NNE TO THE BASE OF THE NORTHEAST CORNER OF THE ANGLE IRON GUARDRAIL POST AT THE NORTHEAST CORNER OF THE BRIDGE
- 6) 53.25' NNW TO THE BASE OF THE NORTHWEST CORNER OF THE ANGLE IRON GUARDRAIL POST AT THE NORTHWEST CORNER OF THE BRIDGE
- 7) 2,645.41' NORTH TO A 5/8" CAPPED REBAR FOUND AT THE NORTHWEST CORNER OF SECTION 29-17-13
- 8) 2,645.41' SOUTH TO A 5/8" CAPPED REBAR OVER THE GLO STONE FOUND AT THE SOUTHWEST CORNER OF SECTION 29-17-13

PLANS FOR BRIDGE REPLACEMENT PROJECT 963.0-500.6 SHOWS THE FOLLOWING:

- 1) 345.41' SOUTH TO THE 5/8" X 12" REBAR WITH A LYON COUNTY CAP SET 3" DEEP AT PROJECT SECTION LINE STATION 23+00.00
- 2) 945.41' SOUTH TO THE 5/8" X 12" REBAR WITH A LYON COUNTY CAP SET 3" DEEP AT PROJECT SECTION LINE STATION 17+00.00
- 3) 2,645.41' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP FOUND AT 6" DEEP IN THE REMAINS OF THE GLO STONE THE SOUTHWEST CORNER OF SECTION 29-17-13 AT PROJECT STATION 0+00.00

WEST QUARTER CORNER 29-17-13