

WEST 1/4 CORNER SECTION 30, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 93 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A MULBERRY POST** FOR THE WEST 1/4 CORNER OF SECTION 30-17-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 29, 1855, FROM WHICH:
 - 1) A HACKBERRY TREE 10" IN DIAMETER BEARS S. 78° W. AT 9 LINKS DISTANCE
 - 2) AN ELM TREE 36" IN DIAMETER BEARS EAST 75 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

 - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-17-13
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-17-13
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 22 RECORDED IN SURVEY BOOK "A" ON PAGE 118 DATED MARCH 3, 1868 FOR A SURVEY OF W. JACOBY'S LAND, TO ESTABLISH THE CENTER CORNER, AND TO DIVIDE THE NORTHWEST 1/4 OF SECTION 30-17-13 NORTH AND SOUTH, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 30-17-13 ON THE RANGE LINE ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 319 RODS, 17 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 30-17-13
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 33, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 33 DATED MAY 16 & 17, 1870 TO ESTABLISH SECTION AND 1/4 SECTION CORNERS ON THE RANGE LINE BETWEEN RANGES 12 & 13 IN TOWNSHIP 17, SAID THAT **HE REESTABLISHED** THE CORNER BETWEEN SECTIONS 25-17-12 & 30-17-13 ON THE RANGE LINE BY THE WITNESS TREES FROM THE GOVERNMENT FIELD NOTES. HE SAID THAT BOTH TREES WERE STANDING WITH THE MARKS QUITE DISTINCT UPON THEM. **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 30-17-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

 - 1) 2,649' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-17-13
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-13 SHOWS A **STONE** AT THE "SW CORNER NW1/4 SECTION 30-17-13" ON THE RANGE LINE.
 - 1) 33.66' NW TO A 10" ELM TREE
 - 2) 6.25' SE TO A 6" OAK TREE
 - 3) 20' SE TO A 6" WALNUT TREE
 - 4) 40.66' SOUTH TO A 12" WALNUT TREE
- 5) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 62 IN THE MIDDLE OF THE PAGE SHOWS A **STONE** AT THE "W1/4 CORNER SECTION 30-17-13" ON THE RANGE LINE.
 - 1) 33.66' NW TO A 10" ELM TREE
 - 2) 6.25' SE TO A 6" OAK TREE
 - 3) 20.0' SSE TO A 6" WALNUT TREE ON THE NORTH BANK OF DUCK CREEK
 - 4) 40.66' SOUTH TO A 12" WALNUT NEAR THE NORTH BANK OF DUCK CREEK
- 6) STEVEN S. BROSEMER, L.S. 752, IN A SURVEY RECORDED IN VOLUME 429, PAGE 115 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 13, 1986, SURVEY F24001 IN THE SURVEY FILE FOR TOWNSHIP 17-12 IN THE COUNTY SURVEYOR'S OFFICE FOR A SURVEY OF THREE TRACTS IN THE SOUTHEAST 1/4 OF SECTION 24-17-12 DATED OCTOBER 28, 1986, SAID THAT HE SEARCHED FOR THE STONE AT THE EAST 1/4

CORNER OF SECTION 25-17-12 ON THE RANGE LINE THAT WAS SET BY ROBERT MILLIKEN ON THE BANK OF DUCK CREEK, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. HE DID **NOT** REMONUMENT THE EAST 1/4 CORNER OF SECTION 25-17-12 ON THIS SURVEY.

- 7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 28, 1986, FOR PROJECT NUMBER 86098, SURVEY F25001 IN THE SURVEY FILE FOR TOWNSHIP 17-12 AND RECORDED IN VOLUME 429 ON PAGE 119 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 3, 1986 TO ESTABLISH THE EAST LINE OF THE WEST HALF OF THE WEST HALF OF THE SOUTHEAST 1/4 OF SECTION 25-17-12, SAID THAT HE STILL CONSIDERED THAT THE NORTHEAST CORNER OF SECTION 25-17-12 ON THE RANGE LINE WAS **LOST**. HE CALCULATED A **THEORETICAL POSITION** FOR THE EAST 1/4 CORNER OF SECTION 25-17-12 TO BE ON LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER AND THE SOUTHEAST CORNER OF SECTION 25-17-12 ON THE RANGE LINE, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.61' NORTH ON THE RANGE LINE TO THE 5/8" SQUARE REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 25-17-12
- 2) 2,647.61' SOUTH ON THE RANGE LINE TO THE GLO STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 25-17-12
- 3) 1,981.76' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE W1/2 OF THE SE1/4 OF SEC. 25-17-12
- 4) 2,642.34' WEST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 25-17-12
- 5) 5,288.05' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 25-17-12

WEST QUARTER CORNER 30-17-13