

WEST 1/4 CORNER OF SECTION 31, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 93 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 11" X 3-1/2"** FOR THE WEST 1/4 CORNER OF SECTION 31-17-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 29, 1855.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-17-13
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 15" X 4" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 17 & 18 SOUTH, RANGES 12 & 13 EAST AT THE SOUTHWEST CORNER OF SECTION 31-17-13

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 158 DATED MAY 13, 1878, APPARENTLY **FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 31-17-13 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS EAST ON THE 1/2 SECTION LINES TWO MILES TO THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 31-17-13

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN AN **AGREEMENT SURVEY** TO ESTABLISH THE CORNERS OF SECTION 36-17-12 DATED APRIL 6 & 7, 1880 AND RECORDED IN THE REGISTER OF DEEDS OFFICE ON MAY 29, 1880, SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 17-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 36-17-12 ON THE RANGE LINE ON THIS **AGREEMENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 19.98 CHAINS NORTH ON THE RANGE LINE TO THE ROCK HE SET FOR THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 36-17-12
 - 2) 39.96 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-12
 - 3) 19.98 CHAINS SOUTH ON THE RANGE LINE TO THE ROCK HE SET FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 36-17-12
 - 4) 39.96 CHAINS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-17-12

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 58, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 58 DATED AUGUST 25, 1884 AT THE REQUEST OF ED YOUNGHAM TO **VACATE** A ROAD IN TOWNSHIP 17, RANGE 13, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 31-17-13 ON THE RANGE LINE TO BEGIN THIS ROAD **VACATION** SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS **VACATED** ROAD EXTENDS EAST ON THE 1/4 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-17-10 AT THE TERMINUS OF THIS ROAD **VACATION SURVEY**

- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 58, A ROAD SURVEY FOR ROAD NUMBER 286 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 94 TO 96 PETITIONED BY ED LAUGHLIN AND OTHERS FOR THE **VACATION** OF A COUNTY ROAD IN SECTION 31-17-10 [PACKET 557 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] THAT HE SURVEYED ON AUGUST 25, 1884, WAS ORDERED **VACATED** ON JANUARY 9, 1885 WITH THE PRINCIPAL PETITIONER TO PAY ALL COSTS AS NOTED BY P. Y. HALLBERG, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MARCH 24, 1885 BY ROLAND

LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 31-17-11 ON THE RANGE LINE TO BEGIN THIS ROAD VACATION SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS VACATED ROAD EXTENDS EAST ON THE 1/4 SECTION LINE FOR 1 MILE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-17-10 AT THE TERMINUS OF THIS ROAD VACATION SURVEY

- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 68, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 147 DATED MARCH 3, 1903 FOR MARY D. COULSON FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 36-17-12 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 16" X 8" X 4" STONE** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 36-17-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK 3 ON PAGE 118 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 74" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.06 CHAINS SOUTH ON THE RANGE LINE TO THE 14" X 8" X 2-1/2" STONE HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE SE1/4 OF SEC. 36-17-12
- 2) 20.07 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 36-17-12
- 3) 40.12 CHAINS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-17-12

WEST QUARTER CORNER 31-17-13