

NORTHWEST CORNER SECTION 33, TOWNSHIP 17 SOUTH, RANGE 13 EAST

- 1) ON PAGE 623 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 13" X 4"** FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-17-13.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.32 CHAINS EAST TO THE 16" X 13" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-17-13
 - 2) 80.64 CHAINS EAST TO THE 16" X 11" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-17-13

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 41 OF THE 8TH TERM RECORDED IN SURVEY BOOK "C" ON PAGE 98, A ROAD SURVEY PETITIONED FOR BY HUGH R. HOLMES, ET. AL. DATED SEPTEMBER 16, 1874, SAID THAT **HE SET AN ANGLE STONE** AT 38' NORTH OF THE NORTHWEST CORNER OF SECTION 33-17-13 ON THIS ROAD SURVEY.

NORTHWEST CORNER 33-17-13