

NORTH 1/4 CORNER SECTION 03, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) ON PAGE 51 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 3-18-10 ON THE TOWNSHIP LINE ON JANUARY 6, 1861.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 20" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-18-10 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS EAST TO THE 20" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2 & 3-18-10 ON THE TOWNSHIP LINE

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 81 RECORDED IN SURVEY BOOK "A" ON PAGE 175 & 178 DATED JANUARY 26 & 27, 1869 FOR A SURVEY OF LAND OWNED BY G. ANDERSON AND J. McCAIN SITUATED IN SECTION 34-17-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 34-17-10 ON THE TOWNSHIP LINE ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS NORTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 34-17-10
 - 2) 160 RODS NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 34-17-10
 - 3) 320 RODS, 41 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-17-10

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 37 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 92 DATED AUGUST 17, 1874 TO SUBDIVIDE THE NORTHWEST 1/4 OF SECTION 3-18-10 INTO TWO EQUAL PARTS BY A LINE EAST & WEST, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 3-18-10 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,783' SOUTH TO THE 16" X 10" X 3" STONE HE SET AT THE INTERSECTION OF THE SOUTH BOUNDARY OF THE KAW TRUST LANDS
 - 2) 2,281' SOUTH TO THE 18" X 9" X 5" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 3-18-10

- 4) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR** REA BOOK 30 ON PAGE 18 SAYS THAT **THEY DROVE AN IRON PIN** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 34-17-10 ON THE TOWNSHIP LINE.
 - 1) 20' SOUTH TO A WITNESS PIN BY A STONE POST

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 17-10 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 34-17-10" ON THE TOWNSHIP LINE. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR**
 - 1) 20' SOUTH TO A WITNESS [REA] BY A FENCE POST

- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 24, 2011 FOR PROJECT NUMBER 11107-02, A SURVEY FOR KERMIT GROTHOR TO LOCATE THE LINE BETWEEN GOVERNMENT LOT 4 AND 5 IN FRACTIONAL SECTION 3, SURVEY F03001 IN THE SURVEY FILE FOR

TOWNSHIP 18-10, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 3-18-10 ON THE TOWNSHIP LINE. HE FOUND A 16" X 12" X 4" LIMESTONE. HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP ON THE SOUTH SIDE CENTER OF THE STONE AND A 5/8" X 30" REBAR WITH A LYON COUNTY CAP ON THE NORTH SIDE CENTER OF THE STONE. HE NOTED ON HIS SURVEY DRAWING THAT THIS SURVEY IS A DIRECT RETRACEMENT OF A PERMANENT SURVEY BY MILLIKEN IN 1874 RECORDED IN SURVEY BOOK "C" ON PAGE 92.

- 1) IN THE TRAVELED WAY OF GRAVEL ROAD 250 EAST-WEST
- 1) 25.00' SOUTH TO A 1/2" X 24" REBAR WITH "LS 752" CAP SET
- 2) 966.00' SOUTH TO A 1/2" REBAR WITH "LS 752" CAP SET
- 3) 2,663.19' EAST TO A 1/2" REBAR WITH "LS 752" CAP
- 4) 2,680.25' WEST TO A 1/2" REBAR
- 5) 1,731.21' SOUTH TO A 1/2" REBAR WITH "LS 752" CAP SET ON THE INDIAN RESERVE LINE AT THE SOUTHWEST CORNER OF GOVERNMENT LOT 4

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 966.00' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AS A POINT ON LINE BETWEEN THE NORTH 1/4 CORNER OF SECTION 3-18-10 AND THE SOUTHWEST CORNER OF GOVERNMENT LOT 4
- 2) 1,256.53' SOUTH TO THE 1/2" REBAR WITH "GEOTECH" CAP HE SET AS A POINT ON LINE BETWEEN THE NORTH 1/4 CORNER OF SECTION 3-18-10 AND THE SOUTHWEST CORNER OF GOVERNMENT LOT 2
- 3) 1,731.21' SOUTH TO THE 1/2" REBAR WITH "GEOTECH" CAP HE SET FOR THE SOUTHWEST CORNER OF GOVERNMENT LOT 4
- 4) 4,933.14' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 3-18-10

NORTH QUARTER CORNER 03-18-10