

CENTER CORNER SECTION 04, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 18 RECORDED IN SURVEY BOOK "A" ON PAGE 115 DATED FEBRUARY 21, 1868 TO SURVEY GRACE S. BRAUM'S LAND, BEING LOTS 3 & 4 IN THE NORTHEAST 1/4 OF SECTION 4-18-10, SAID THAT **HE SET A POST** FOR THE CENTER CORNER OF SECTION 4-18-10, BEING THE SOUTHWEST CORNER OF LOT 1, AT 160 RODS NORTH OF THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-18-10 ON A LINE PARALLEL WITH THE EAST LINE OF SECTION 4-18-10 ON THIS SURVEY. HE NOTED ON THE BOTTOM OF THE PAGE THAT THIS SURVEY FOR LOTS 3 & 4 IN THE NORTHEAST 1/4 OF SECTION 4-18-10 WAS **SET ASIDE** BY A DECISION OF THE **DISTRICT COURT**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 160 RODS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-18-10
 - 2) 52 RODS, 22 LINKS NORTH TO THE POST HE SET FOR THE SOUTHWEST CORNER OF THAT PORTION OF LAND EMBRACED IN LOTS 3 & 4
 - 3) 147 RODS, 33 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-18-10
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 69 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 125 DATED APRIL 1, 1875 TO PART OFF 14 ACRES FROM THE WEST END OF LOT 1 IN SECTION 4-18-10, SAID THAT HE FOUND THE CENTER CORNER OF SECTION 4-18-10 "FALLEN INTO THE RIVER. I PROCEEDED TO REESTABLISH SAID CORNER BY A **WITNESS CORNER 33 FEET EAST** OF POINT OF TRUE CORNER BY TAKING MEASUREMENTS FROM A TREE MARKED AS A WITNESS BY G. M. WALKER IN A SURVEY MADE BY ORDER OF THE COURT SEPTEMBER 28TH TO OCTOBER 1ST 1868 AND ON FILE IN THE OFFICE OF THE CLERK OF THE DISTRICT COURT".

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 544' NORTH TO THE STONE THAT WAS SET ON THE SOUTH BOUNDARY OF THE KAW TRUST LANDS BY SAID G. M. WALKER, SAID CORNER BEING THE NORTHWEST CORNER OF LOT 1
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 76 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 133 DATED JULY 21, 1875 TO ESTABLISH THE 1/4 CORNER AND THE CORNER ON THE SOUTH BOUNDARY OF THE KAW INDIAN TRUST LANDS ON LINE BETWEEN SECTIONS 4 & 5-18-10, SAID THAT **HE FOUND THE CENTER CORNER OF SECTION 4-18-10** "AS SET BY G. M. WALKER SEPTEMBER 30, 1868" ON THIS **PERMANENT SURVEY**.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640' WEST TO THE STONE HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 4-18-10
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 3, 1988, SURVEY F04001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 TO ESTABLISH THE NORTHEAST CORNER OF THE WEST HALF OF THE SOUTHWEST 1/4 OF SECTION 4-18-10 AND THE SOUTH LINE OF LOT 2 OF SAID SECTION 4, RECORDED IN VOLUME 441 ON PAGE 5 IN THE REGISTER OF DEEDS OFFICE ON MAY 23, 1988, SAID THAT **HE FOUND THE 3" X 15" X 16" LIMESTONE WITNESS CORNER FOR THE CENTER CORNER OF SECTION 4-18-10 WITH A POST ROCK ON THE EAST SIDE AT 14" DEEP. HE DROVE REBARS ON THE EAST AND WEST SIDES, AND A 1978 NICKEL WAS LEFT ON THE SOUTH SIDE OF THE STONE AS A MEMORIAL.**

- 1) **33.0' WEST TO THE TRUE POSITION FOR THE CENTER OF SECTION 4-18-10**
- 2) 25.3' WEST TO A PK NAIL & WASHER IN A 12" ASH TREE
- 3) 22.3' WNW TO A PK NAIL & WASHER IN A 14" ASH TREE
- 4) 19.3' SSW TO A PK NAIL & WASHER IN A 22" WALNUT TREE
- 5) A CORNER POST ROCK WAS FOUND BURIED 1.0' EAST OF THE STONE
- 6) A 1978 NICKEL WAS LEFT ON THE SOUTH SIDE OF THE STONE AS A MEMORIAL
- 7) SURVEY COORDINATES: NORTH = 3,680.14 EAST = 5,122.01

HIS SURVEY REPORT/DRAWING SHOWS THE FOLLOWING FROM THE POSITION FOR THE TRUE CENTER CORNER:

- 1) 541.45' NORTH TO THE STONE THAT WAS SET BY WALKER IN A DISTRICT COURT ORDERED SURVEY IN 1868 THAT HE FOUND AT THE NORTHEAST CORNER OF LOT 2
 - 2) 2,681.13' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 4-18-10
 - 3) 1,317.17' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 4-18-10
 - 4) 2,634.34' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 4-18-10
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 25, 2003, FOR PROJECT NUMBER 03284-02, SURVEY F04002 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THE SOUTH 40 ACRES OF GOVERNMENT LOTS 3 & 4 IN THE NORTHEAST 1/4 OF FRACTIONAL SECTION 4-18-10, SAID THAT **HE FOUND THE WITNESS STONE** FOR THE CENTER CORNER OF SECTION 4-18-10 FROM HIS PRIOR SURVEY IN 1988.

- 1) **33.0' WEST TO THE TRUE POSITION FOR THE CENTER CORNER**
- 2) 25.3' WEST TO A PK NAIL & WASHER IN A 12" ASH TREE
- 3) 22.3' WNW TO A PK NAIL & WASHER IN A 14" ASH TREE
- 4) 19.3' SSW TO A PK NAIL & WASHER IN A 22" WALNUT TREE
- 5) A CORNER POST ROCK WAS FOUND BURIED 1.0' EAST OF THE STONE

HIS SURVEY DRAWING SHOWS THE FOLLOWING FROM THE TRUE CENTER CORNER:

- 1) 541.45' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF LOT 1 ON THE SOUTH BOUNDARY OF THE KANSAS INDIAN RESERVE, AKA SOUTHWEST CORNER OF GOVERNMENT LOT 4
- 2) 2,382.45' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 4-18-10, AKA NORTHWEST CORNER OF GOVERNMENT LOT 4

CENTER CORNER 04-18-10