

**WEST 1/4 CORNER SECTION 04, TOWNSHIP 18 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 183 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 22" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-18-10 ON JANUARY 15, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 12.48 CHAINS NORTH TO THE 19" X 10" X 3" LIMESTONE THEY SET ON THE SOUTH BOUNDARY OF THE KANSAS INDIAN RESERVATION
  - 2) 39.32 CHAINS NORTH TO THE 16" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-18-10 ON THE TOWNSHIP LINE
  - 3) 40.00 CHAINS SOUTH TO THE 19" X 17" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-18-10
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 76 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 133 DATED JULY 21, 1875 TO ESTABLISH THE 1/4 CORNER AND THE CORNER ON THE SOUTH BOUNDARY OF THE KAW INDIAN TRUST LANDS ON LINE BETWEEN SECTIONS 4 & 5-18-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 4-18-10 ON **THIS PERMANENT SURVEY.** HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,640' EAST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 4-18-10 THAT WAS SET BY G. M. WALKER ON SEPTEMBER 30, 1868
  - 2) 2,640' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-18-10
  - 3) 576.18' NORTH TO THE 16" X 10" X 4" STONE HE SET ON THE SOUTH BOUNDARY OF THE KAW INDIAN TRUST LANDS
  
- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 19 BY NOTICE FROM JAMES HUMPHREY AND ANNA A. HERBERT REQUESTING A SURVEY TO PERMANENTLY ESTABLISH THE LINES AND CORNERS NECESSARY TO MAKE A COMPLETE SURVEY OF THE LINE BETWEEN SECTIONS 4 & 5-18-10, AND ESTABLISH THE NORTHWEST CORNER, THE CORNER AT THE INTERSECTION OF THE LINE OF THE SOUTH BOUNDARY OF THE KANSAS INDIAN RESERVATION LINE, THE 1/4 CORNER BETWEEN SAID SECTIONS, THE CORNER AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 AND THE SOUTHWEST CORNER OF SECTION 4, SAID THAT **HE SET A 22" X 7" X 6" LIMESTONE MARKED "1/4" ON THE WEST SIDE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 4-18-10 ON **THIS PERMANENT SURVEY.** THE SURVEY WAS COMPLETED ON NOVEMBER 24, 1899 AND FILED ON DECEMBER 23, 1899. HE SAID THAT **THIS STONE IS 7-1/2 LINKS SOUTH AND 4-1/2 LINKS EAST OF ANOTHER STONE HE FOUND WITH NO MARKS.** HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 20.04 CHAINS SOUTH TO THE 16" X 9" X 6" STONE MARKED "1/8" ON THE WEST SIDE HE SET FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 4-18-10
  - 2) 40.08 CHAINS SOUTH TO THE 21" X 13" X 5" STONE PROPERLY NOTCHED HE SET DEEP IN THE GROUND FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 4-18-10
  - 3) 200.86 CHAINS SOUTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-18-10
  - 4) 9.10-1/2 CHAINS NORTH TO THE 17" X 10" X 6" STONE MARKED "RL" ON THE SOUTH SIDE HE SET ON THE INDIAN RESERVE LINE FOR THE PERMANENT NORTHWEST CORNER OF GOVERNMENT LOT 2

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 37.67 CHAINS NORTH TO THE 20" X 10" X 6" STONE PROPERLY NOTCHED HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 4-18-10 ON THE TOWNSHIP LINE
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 105, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 186 DATED SEPTEMBER 11, 1904 FOR NELL STUBBS, PRINCIPAL PETITIONER, FOR A ROAD BETWEEN SECTIONS 4 & 5, TOWNSHIP 18, RANGE 10, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE ESTABLISHED BY COUNTY SURVEYOR MATTHEW BROWN IN 1899** AT THE WEST 1/4 CORNER OF SECTION 4-18-10 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE BETWEEN SECTIONS 4 & 5-18-10 TO THE STONE HE FOUND THE NORTHWEST CORNER OF SECTION 4-18-10 ON THE TOWNSHIP LINE, THAT WAS ESTABLISHED BY COUNTY SURVEYOR MATTHEW BROWN IN 1899, AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE BETWEEN SECTIONS 4 & 5-18-10 TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-18-10, THAT WAS ESTABLISHED BY COUNTY SURVEYOR MATTHEW BROWN IN 1899, TO BEGIN THIS ROAD SURVEY
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 593 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 241 THROUGH 244 PETITIONED BY N. M. STUBBS AND OTHERS TO RE-VIEW THE ROAD BETWEEN SECTIONS 4 & 5-18-10 [PACKET 732 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 11, 1904, WAS GRANTED AS A 40 FOOT WIDE ROAD, AS PER THE ORIGINAL LOCATION, ON DECEMBER 9, 1904 AS NOTED BY JOHN LANGLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON MARCH 23, 1905 BY ALVA J. SMITH, COUNTY SURVEYOR, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE ESTABLISHED BY COUNTY SURVEYOR MATTHEW BROWN IN 1899** AT THE WEST 1/4 CORNER OF SECTION 4-18-10 ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINE BETWEEN SECTIONS 4 & 5-18-10 TO THE STONE HE FOUND THE NORTHWEST CORNER OF SECTION 4-18-10 ON THE TOWNSHIP LINE, THAT WAS ESTABLISHED BY COUNTY SURVEYOR MATTHEW BROWN IN 1899, AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINE BETWEEN SECTIONS 4 & 5-18-10 TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-18-10, THAT WAS ESTABLISHED BY COUNTY SURVEYOR MATTHEW BROWN IN 1899, TO BEGIN THIS ROAD SURVEY
- 6) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 17, 1988, SAID THAT **HE SET A 1/2" REBAR WITH HIS RED "LS 752" PLASTIC CAP** FOR THE WEST 1/4 CORNER OF SECTION 4-18-10.
- 1) 20.3' WEST TO A PK NAIL & WASHER IN A POWER POLE
  - 2) 17.7' EAST TO A PK NAIL & WASHER IN A DEADMAN
  - 3) 14.7' NW TO THE SOUTHEAST CORNER OF A STONE CULVERT
  - 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 3, 1988, SURVEY F04001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 TO ESTABLISH THE NORTHEAST CORNER OF THE WEST HALF OF THE SOUTHWEST 1/4 OF SECTION 4-18-10 AND THE SOUTH LINE OF LOT 2 OF SAID SECTION 4, RECORDED IN VOLUME 441 ON PAGE 5 IN THE REGISTER OF

DEEDS OFFICE ON MAY 23, 1988, SAID THAT HE CONSIDERED THAT THE WEST 1/4 OF SECTION 4-18-10 WAS **LOST**. **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/4 CORNER OF SECTION 4-18-10 BY PROPORTIONATE MEASUREMENT BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF GOVERNMENT LOT 2 AND THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 4-18-10.

- 1) 20.3' WEST TO A PK NAIL & WASHER IN A POWER POLE
- 2) 17.7' EAST TO A PK NAIL & WASHER IN A DEADMAN
- 3) 14.7' NW TO THE SOUTHEAST CORNER OF A STONE CULVERT
- 4) 3.5' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH  
HIS SURVEY REPORT/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) SURVEY COORDINATES: NORTH = 3,640.15 EAST = 2,454.98
  - 2) 599.15' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF GOVERNMENT LOT 2, THAT WAS SET BY WALKER IN THE 1868 DISTRICT COURT ORDERED SURVEY
  - 3) 1,319.09' SOUTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 4-18-10
  - 4) 2,641.69' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 4-18-10
  - 5) 1,317.17' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 4-18-10
  - 6) 2,634.34' EAST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 4-18-10
  - 7) 2,667.34' EAST TO THE MILLIKEN'S WITNESS STONE [3" X 15" X 16" LIMESTONE WITH A POST ROCK ON THE EAST SIDE] HE FOUND AT 33' EAST OF THE CENTER CORNER OF SECTION 4-18-10

8) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 11, 2014 FOR PROJECT NUMBER 13215 FOR THE SURVEY FOR POINTS IN THE WEST 1/2 OF SECTION 4-18-10 FOR JEFF MATILE, SURVEY F04004 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SAID THAT **HE FOUND THE 1/2" IRON PIN WITH HIS "LS 752" CAP** AT THE WEST 1/4 CORNER OF SECTION 4-18-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE FROM MAY 1988.

- 1) 20.45' WEST TO A PK NAIL & WASHER IN A POWER POLE
- 2) 17.3' EAST TO A PK NAIL & WASHER IN A DEADMAN POLE
- 3) 45.6' NNW TO THE TOP CENTER OF THE NORTH END OF A 24" CULVERT PIPE
- 4) 13.5' WEST TO THE TOP CENTER OF THE SOUTH END OF A 24" CULVERT PIPE
- 5) 32' NORTH TO THE CENTERLINE OF A DRIVEWAY TO THE WEST  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) (M) = MEASURED DISTANCE THIS SURVEY
  - 2) (SSB) = BROSEMER DISTANCE 1988
  - 3) 1,319.19' (M) SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 4-18-10 (SSB = 1,319.09')
  - 4) 2,642.04' (M) SOUTH TO THE 5/8" IRON PIN OVER THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 4-18-10 (SSB = 2,641.69')
  - 5) 598.91' NORTH OF THE STONE HE FOUND AT THE NORTHWEST CORNER OF LOT 2 ON THE WEST SIDE OF THE NW1/4 OF SECTION 4-18-10 (SSB = 598.91')
  - 6) 2,449.09' (M) NORTH TO THE SLOAN ALUMINUM CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 4-18-10 ON THE TOWNSHIP LINE

WEST QUARTER CORNER 04-18-10