

NORTH 1/4 CORNER SECTION 14, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) ON PAGE 174 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 14-18-10.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.91 CHAINS WEST TO THE 19" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-18-10
- 2) 39.91 CHAINS EAST TO THE 24" X 14" X 3' LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-18-10

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 33, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 33 DATED MAY 27 & 28, 1884 AT THE REQUEST OF THOMAS CRAIG TO LOCATE THE NORTHEAST AND NORTHWEST CORNERS OF THE EAST 1/2 AND THE NORTHWEST CORNER OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 14-18-10, SAID THAT **HE SET A TEMPORARY STAKE** FOR THE NORTH 1/4 CORNER OF SECTION 14-18-10 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS RECORDED IN VOLUME 41 ON PAGE 18 AT THE REGISTER OF DEEDS OFFICE ON JANUARY 27, 1887 AND SURVEY F14001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 IS A COPY OF THAT FILED SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,333' SOUTH TO THE TEMPORARY STAKE HE SET FOR THE EAST 1/4/4 CORNER OF THE NW1/4 OF SECTION 14-18-10
- 2) 2,666' SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 14-18-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A **PERMANENT SURVEY** ORDERED BY L. JAMES AND J. D. GIBSON TO PERMANENTLY ESTABLISH THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 14-18-10, RECORDED FEBRUARY 17, 1887 IN THE REGISTER OF DEEDS OFFICE IN VOLUME 41 ON PAGE 66 AND SURVEY F14002 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 14-18-10 ON THIS **PERMANENT SURVEY**.

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 143, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 224 DATED FEBRUARY 20-23, 1906 ORDERED BY G. W. FANSKA FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF 49.97 ACRES IN THE SOUTHEAST 1/4 OF 10 AND 34.50 ACRES IN THE SOUTHWEST CORNER OF SECTION 11, ALL IN TOWNSHIP 18, RANGE 10, SAID THAT **HE SET A STAKE** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 11-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 11-18-10 AND THE STONE THAT HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 11-18-10 ON THIS **PERMANENT SURVEY**. SEE HIS FIELD NOTES IN PACKET "M 171" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS SURVEY.

- 1) A NORTH AND SOUTH HEDGE FENCE IS 0.22 CHAINS WEST
- 2) AN EAST & WEST HEDGE FENCE ON THE SOUTH SIDE OF THE ROAD IS 0.80 CHAINS SOUTH
- 3) AN EAST & WEST HEDGE FENCE ON THE NORTH SIDE OF THE ROAD IS 1.32 CHAINS NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 40.53 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 11-18-10, FROM WHICH A HEDGE RUNNING EAST IS 0.27 CHAINS SOUTH, AND A HEDGE RUNNING NORTH & SOUTH IS 0.26 CHAINS EAST
 - 2) 20.27 CHAINS WEST TO THE STAKE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 11-18-10, FROM WHICH THE WEST END OF A HEDGE IS 0.18 CHAINS NORTH AND 0.04 CHAINS EAST, AND A TREE IS 33 LINKS WEST AND 18 LINKS NORTH
 - 3) 33.95 CHAINS WEST TO THE STAKE HE SET ON THIS SURVEY, FROM WHICH A WITNESS STONE IS 0.34 CHAINS WEST AND 0.17 CHAINS NORTH
 - 4) 40.53 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 11-18-10
 - 5) 61.42 CHAINS WEST TO THE STONE MARKED "A" HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 10-18-10
 - 6) 82.31 CHAINS WEST TO THE STONE MARKED "A" HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 11-18-10
 - 7) 122.62 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 11-18-10
- 5) AI CHAMNESS, DULY DEPUTIZED TO PERFORM A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 109, SAID THAT ON JUNE 5, 1935 NOTICE WAS GIVEN BY O. D. HENRY, ENGINEER OF LYON COUNTY, KANSAS, THAT ON THE 15 DAY OF JUNE, 1936, WOULD BEGIN A SURVEY FOR LOCATING AND PERMANENTLY ESTABLISHING THE FOLLOWING CORNERS AS ORDERED BY MISS BESSIE PICKERING THROUGH HER ATTORNEY, OWEN S. SAMUEL OF AMERICUS, KANSAS: THE NORTHEAST CORNER, THE SOUTHWEST CORNER, AND THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 14-18-10; AND ALSO THE EAST 1/4 CORNER, THE NORTH 1/4 CORNER, THE WEST 1/4 CORNER, AND THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 14-18-10; AND ALSO THE CENTER OF SAID QUARTER SECTION, THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4; AND THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 14-18-10. THE REPORT WAS FILED ON AUGUST 20, 1936 AND THE SURVEY WAS RECORDED ON AUGUST 24, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGES 1, 53 IN THE KRETSINGER COLLECTION OF FIELD BOOKS. HE SAID THAT **HE SET A SQUARE IRON PIN AT 14.5' EAST OF A HEDGE RUNNING NORTH AND SOUTH** FOR THE PERMANENT NORTH 1/4 OF SECTION 14-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 14-18-10 AND THE STONE THAT HE FOUND IN PLACE AT THE NORTHEAST CORNERS OF SECTION 14-18-10 ON THIS **PERMANENT SURVEY**.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,337' WEST TO THE IRON PIN HE SET FOR THE PERMANENT NORTH 1/16TH CORNER OF THE NW1/4 OF SECTION 14-18-10, AT 10.66' EAST TO AN IRON POST IN A FENCE AND 12.75' NORTHEAST TO AN OSAGE HEDGE STUMP
 - 2) 2,674' WEST TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 14-18-10
 - 3) 1,337' EAST TO THE THEORETICAL LOCATION FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 14-18-10
 - 4) 2,674' EAST TO THE STONE HE FOUND IN PLACE AT THE NORTHEAST CORNER OF SECTION 14-18-10
 - 5) 1,333.56' SOUTH TO THE AUTO SHAFT HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE NW1/4 OF SECTION 14-18-10
 - 6) 2,667.12' SOUTH TO THE AUTO SHAFT WITH A GEAR WHEEL ON TOP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-18-10
 - 7) 4,015.68' SOUTH TO THE THEORETICAL LOCATION FOR THE EAST 1/16TH CORNER OF THE SW1/4 OF SECTION 16-18-10

HIS INFORMATION IS CONTINUED ON PAGE 3

- 8) 5,349.24' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 14-18-10 NORTHEAST OF A SMALL ELM TREE IN A FENCE, 62' NORTHWEST TO A COTTONWOOD TREE [EAST OF TWO TREES- WEST IS A DOUBLE TREE], AND 14.5' NORTH OF THE FENCE ON THE NORTH SIDE OF THE ROAD
- 6) KRETSINGER REFERENCE TIE BOOK NUMBER 13 ON PAGE 56 SHOWS A **SQUARE IRON PIN** AT THE "NE CORNER NW1/4 SECTION 14-18-10".
- NORTH QUARTER CORNER 14-18-10