

**WEST 1/16TH CORNER SOUTHEAST QUARTER SECTION 14, TOWNSHIP 18 SOUTH,
RANGE 10 EAST**

1) AI CHAMNESS, DULY DEPUTIZED TO PERFORM A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 109, SAID THAT ON JUNE 5, 1935 NOTICE WAS GIVEN BY O. D. HENRY, ENGINEER OF LYON COUNTY, KANSAS, THAT ON THE 15 DAY OF JUNE, 1936, WOULD BEGIN A SURVEY FOR LOCATING AND PERMANENTLY ESTABLISHING THE FOLLOWING CORNERS AS ORDERED BY MISS BESSIE PICKERING THROUGH HER ATTORNEY, OWEN S. SAMUEL OF AMERICUS, KANSAS: THE NORTHEAST CORNER, THE SOUTHWEST CORNER, AND THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 14-18-10; AND ALSO THE EAST 1/4 CORNER, THE NORTH 1/4 CORNER, THE WEST 1/4 CORNER, AND THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 14-18-10; AND ALSO THE CENTER OF SAID QUARTER SECTION, THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4; AND THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 14-18-10. THE REPORT WAS FILED ON AUGUST 20, 1936 AND THE SURVEY WAS RECORDED ON AUGUST 24, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGES 1, 53 IN THE KRETSINGER COLLECTION OF FIELD BOOKS. HE SAID THAT HE DETERMINED A **THEORETICAL LOCATION** FOR THE WEST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 14-18-10 TO BE ON LINE AND HALFWAY BETWEEN THE AUTO SHAFT WITH A GEAR WHEEL ON TOP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-18-10 AND THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 14-18-10 ON THIS **PERMANENT SURVEY**. HE DID **NOT** MONUMENT THIS POSITION. HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,333.56' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 1418-10, NORTHEAST OF A SMALL ELM TREE IN A FENCE, 62' NORTHWEST TO A COTTONWOOD TREE [EAST OF TWO TREES – WEST IS A DOUBLE TREE], AND 14.5' NORTH OF THE FENCE ON THE NORTH SIDE OF THE ROAD
- 2) 1,333.56' NORTH TO THE AUTO SHAFT WITH A GEAR WHEEL ON TOP HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 14-18-10
- 3) 2,667.12' NORTH TO THE AUTO SHAFT HE SET FOR THE PERMANENT EAST 1/16TH CORNER OF THE NE1/4 OF SECTION 14-18-10
- 4) 4,000.68' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 14-18-10, AT 14.5' EAST OF A HEDGE RUNNING NORTH AND SOUTH
- 5) 1,326.5' EAST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF THE SE1/4 OF SECTION 14-18-10
- 6) 2,653' EAST TO THE THEORETICAL LOCATION FOR THE EAST 1/16TH CORNER OF THE SE1/4 OF SECTION 14-18-10
- 7) 1,326.5' WEST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF THE SW1/4 OF SECTION 14-18-10
- 8) 2,653' WEST TO THE THEORETICAL LOCATION FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 14-18-10

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 14-18-10