

**WEST 1/16TH CORNER SOUTHWEST QUARTER SECTION 14, TOWNSHIP 18 SOUTH,  
RANGE 10 EAST**

- 1) AI CHAMNESS, DULY DEPUTIZED TO PERFORM A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 109, SAID THAT ON JUNE 5, 1935 NOTICE WAS GIVEN BY O. D. HENRY, ENGINEER OF LYON COUNTY, KANSAS, THAT ON THE 15 DAY OF JUNE, 1936, WOULD BEGIN A SURVEY FOR LOCATING AND PERMANENTLY ESTABLISHING THE FOLLOWING CORNERS AS ORDERED BY MISS BESSIE PICKERING THROUGH HER ATTORNEY, OWEN S. SAMUEL OF AMERICUS, KANSAS: THE NORTHEAST CORNER, THE SOUTHWEST CORNER, AND THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 14-18-10; AND ALSO THE EAST 1/4 CORNER, THE NORTH 1/4 CORNER, THE WEST 1/4 CORNER, AND THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 14-18-10; AND ALSO THE CENTER OF SAID QUARTER SECTION, THE NORTHWEST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4; AND THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 14-18-10. THE REPORT WAS FILED ON AUGUST 20, 1936 AND THE SURVEY WAS RECORDED ON AUGUST 24, 1936. HIS FIELD NOTES ARE IN BOOK "R" ON PAGES 1, 53 IN THE KRETSINGER COLLECTION OF FIELD BOOKS. HE SAID THAT HE DETERMINED A **THEORETICAL LOCATION** FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 14-18-10 TO BE ON LINE AND HALFWAY BETWEEN THE ROUND MACHINE SHAFT THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 14-18-10 AND THE SQUARE IRON PINE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 14-18-10 ON THIS **PERMANENT SURVEY**.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,329' SOUTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 1418-10, IN THE CENTER OF THE ROAD GOING NORTH BUT 8 FEET SOUTH OF THE NORTH FENCE ON THE ROAD GOING WEST
- 2) 1,329' NORTH TO THE ROUND MACHINE SHAFT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 14-18-10
- 3) 2,658' NORTH TO THE SQUARE IRON PIN HE SET FOR THE PERMANENT WEST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 14-18-10
- 4) 3,987' NORTH TO THE STONE HE FOUND IN PLACE AT THE NORTHWEST CORNER OF SECTION 14-18-10
- 5) 1,326.5' EAST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF THE SW1/4 OF SECTION 14-18-10
- 6) 2,653' EAST TO THE THEORETICAL LOCATION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SW1/4 OF SECTION 14-18-10
- 7) 3,979.5' EAST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF THE SE1/4 OF SECTION 14-18-10
- 8) 5,306' EAST TO THE THEORETICAL LOCATION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 14-18-10

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 14-18-10