

NORTH 1/4 CORNER SECTION 15, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) ON PAGE 178 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 15-18-10 ON JANUARY 11, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.12 CHAINS WEST TO THE 32" X 7" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 9, 10, 15 & 16-18-10
 - 2) 40.13 CHAINS EAST TO THE 19" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 10, 11, 14 & 15-18-10

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 5 RECORDED IN SURVEY BOOK "A" ON PAGES 100 & 101 DATED JANUARY 1868 TO SURVEY THE WEST 1/2 OF THE NE1/4, AND 33 ACRES MORE OR LESS ON THE WEST SIDE OF THE NORTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 10-18-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 10-18-10 ON THIS SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 20.00 CHAINS NORTH TO THE SOUTHWEST CORNER OF THE NW1/4 OF THE SE1/4 OF SECTION 10-18-10 – NOT IDENTIFIED
 - 2) 40.00 CHAINS NORTH TO THE LIMESTONE ROCK HE PLANTED FOR THE CENTER CORNER OF SECTION 10-18-10
 - 3) 80.00 CHAINS NORTH TO THE STONE HE PLANTED FOR THE NORTH 1/4 CORNER OF SECTION 10-18-10

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROD NUMBER 77 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 310 TO 312 PETITIONED BY E. & J. W. SCHWARTZ AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 18-10 [PACKET 227 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 5, 1880, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 5, 1880, AND WAS RECORDED ON NOVEMBER 12, 1880 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 15-18-10 ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF SECTION 16-18-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE FOR 20 CHAINS TO THE TERMINUS OF THIS ROAD SURVEY

- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE PAGE 187 DATED AUGUST 5, 1880, FOR A COUNTY ROAD IN TOWNSHIP 18-10, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF SECTION 15-18-10 ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 16-18-10 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE 20 CHAINS TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 15-18-10 TO THE TERMINUS OF THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 5) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 146 DATED JANUARY 31, 1883 TO ESTABLISH THE CENTER OF SECTION 15-18-10, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 15-18-10 ON THIS **INFORMAL SURVEY**. **HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:**
- 1) 79.67 CHAINS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER LINE OF SECTION 15-18-10
- 6) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 174, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 174 DATED JUNE 27 & 28, 1887 ORDERED BY EMIL ROTHSCHILD'S TO LOCATE THE LINE BETWEEN THE SOUTHEAST AND SOUTHWEST QUARTERS OF THE SOUTHEAST 1/4 OF SECTION 10-18-10, SAID THAT **HE FOUND "UNMISTAKABLE EVIDENCE OF THE 1/4 CORNER"** AT THE SOUTH 1/4 CORNER OF SECTION 10-18-10 ON THIS **PERMANENT SURVEY**. HE NOTED ON THIS SURVEY THAT THERE IS AN ANGLE AT THE 1/4 CORNER BETWEEN THE SOUTHEAST AND SOUTHWEST SECTION CORNERS. **HIS SURVEY NOTES/ DRAWING SHOW THE FOLLOWING INFORMATION:**
- 1) 2,659' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 10-18-10
 - 2) 1,379' EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4/4 CORNER OF THE SE1/4 OF SECTION 10-18-10
 - 3) 2,758' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 10-18-10
- 7) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 143, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 224 DATED FEBRUARY 20-23, 1906 ORDERED BY G. W. FANSKA FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF 49.97 ACRES IN THE SOUTHEAST 1/4 OF 10 AND 34.50 ACRES IN THE SOUTHWEST CORNER OF SECTION 11, ALL IN TOWNSHIP 18, RANGE 10, SAID THAT **HE SET A STONE MARKED WITH AN "A"** FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 10-18-10 ON THIS **PERMANENT SURVEY**. SEE HIS FIELD NOTES IN PACKET "M 171" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE FOR ADDITIONAL INFORMATION ON THIS SURVEY.
- 1) A POST IS N. 12° W. AT 0.23 CHAINS
 - 2) A POST IS S. 65° E. AT 0.18 CHAINS
 - 3) A POST IS S. 33-1/2° W. AT 0.47 CHAINS
 - 4) A POST IS S. 57-1/2° W. AT 0.57 CHAINS
 - 5) A POST IS N. 47-1/2° W. AT 0.48 CHAINS
 - 6) THE CENTER OF AN OLD WELL IS N. 54-1/2° E. AT 2.23 CHAINS
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 40.31 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 10-18-10
 - 2) 20.89 CHAINS EAST TO THE STONE MARKED "A" HE SET FOR THE PERMANENT 1/2/4 CORNER ON THE SOUTH SIDE OF THE SE1/4 OF SECTION 10-18-10
 - 3) 41.78 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 10-18-10
 - 4) 48.36 CHAINS EAST TO THE STAKE HE SET ON THIS PERMANENT SURVEY, FROM WHICH A WITNESS STONE IS 0.34 CHAINS WEST AND 0.17 CHAINS NORTH
 - 5) 62.04 CHAINS EAST TO THE STAKE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 11-18-10, FROM WHICH THE WEST END OF A HEDGE IS 0.18 CHAINS NORTH AND 0.04 CHAINS EAST
 - 6) 82.31 CHAINS EAST TO A STAKE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 11-18-10, FROM WHICH A NORTH & SOUTH HEDGE FENCE IS 0.22 CHAINS WEST, AN EAST & WEST HEDGE FENCE ON THE SOUTH SIDE OF

THE ROAD IS 0.80 CHAINS NORTH, AND AN EAST & WEST HEDGE FENCE ON
THE NORTH SIDE OF THE ROAD IS 1.32 CHAINS NORTH

- 7) 122.84 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST
CORNER OF SECTION 11-18-10

NORTH QUARTER CORNER 15-18-10