

**NORTH 1/16TH CORNER NORTHWEST QUARTER SECTION 17, TOWNSHIP 18 SOUTH,
RANGE 10 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 61 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 209 DATED JULY 12, 1872 TO ESTABLISH THE CENTER CORNER AND THE 1/2/4 AND 1/4/4 CORNERS IN THE NORTHWEST 1/4 OF SECTION 17-18-10, SAID THAT **HE SET A STONE MARKED "1/16"** FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 17-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-18-10 AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-18-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,326' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-18-10
 - 2) 1,326' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 17-18-10
 - 3) 2,640' EAST TO THE STONE MARKED "1/16" HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 17-18-10
 - 4) 3,954' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 17-18-10
 - 5) 1,333-1/2' SOUTH BY HIS NOTES [1,333' ON DRAWING] TO THE STONE MARKED "1/16" HE SET FOR THE PERMANENT CENTER 1/4/4 CORNER OF THE NW1/4 OF SECTION 17-18-10
 - 6) 2,667' SOUTH BY HIS NOTES [2,666' ON DRAWING] TO THE STONE MARKED "1/16" HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 17-18-10

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 145, A ROAD SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 145 FOR A ROAD IN TOWNSHIP 18-10 FOR THOMAS STANLEY, PRINCIPAL PETITIONER, DATED SEPTEMBER 16, 1886, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8-18-10 TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-18-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 333 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 282 TO 284 PETITIONED BY THOMAS STANLEY AND OTHERS FOR A ROAD IN TOWNSHIP 18-10 [PACKET 561 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON SEPTEMBER 16, 1886, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 11, 1886 AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 23, 1886 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8-18-10 TO END THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1-1/4 MILE "PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-18-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY

CONTINUED ON PAGE 2

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 127, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 208 DATED JUNE 6 THROUGH 9, 1905 AT THE ORDER OF ABNER WICKERSHAM FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 9-18-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTH 1/8TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 8-18-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 2 ON PAGES 178, 182 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 72" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 20.12 CHAINS WEST TO THE STONE HE FOUND IN PLACE AT THE SOUTHWEST CORNER OF SECTION 8-18-10
 - 2) 20.12 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/4 CORNER OF SECTION 8-18-10
 - 3) 59.98 CHAINS EAST TO THE PIECE OF BUGGY AXLE TREE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 9-18-10
 - 4) 79.81 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 9-18-10
 - 5) 99.64 CHAINS EAST TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 9-18-10
 - 6) 119.44 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTH 1/8TH CORNER OF THE SE1/4 OF SECTION 9-18-10
 - 7) 139.24 CHAINS EAST TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 9-18-10
- 5) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 102
 A PETITION WITH NO NAME OR DATE WAS SUBMITTED TO **VACATE** A ROAD IN TOWNSHIP 18-10. THE ROAD WAS VIEWED BY THE COUNTY COMMISSION ON DECEMBER 26, 1956, AND THE FINAL ORDER TO **VACATE** THE ROAD WAS SIGNED ON DECEMBER 27, 1956 AS NOTED BY ALBERT L. JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY VESPER M. SHEELEY, JR., COUNTY CLERK,
- 1) BEGINNING AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 8-18-10; THENCE SOUTH FOR A DISTANCE OF 1 MILE MORE OR LESS AND ENDING AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8-18-10.
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 3, 1989, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 17-18-10 FROM INFORMATION IN THE COUNTY SURVEYORS OFFICE. **HE SET REBARS ON THE EAST AND WEST SIDES OF THE STONE.** [**NOTE:** THIS STONE WAS SET BY COUNTY SURVEYOR ROBERT MILLIKEN IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 209 DATED JULY 1872 AND RECOVERED BY COUNTY SURVEYOR ALVA J. SMITH IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 208 IN 1905 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 1) 28.7' NNW TO A PK NAIL & WASHER IN A FENCE POST
 - 2) 28.0' NNE TO A PK NAIL & WASHER IN A FENCE POST
 - 3) 11.7' WEST TO AN OLD LINE OF FENCE TO THE NORTH [EXTENDED]
 - 4) 10.2' EAST TO A NEW LINE OF FENCE TO THE NORTH [EXTENDED]
 - 5) 3.6' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST NORTH SIXTEENTH CORNER NORTHWEST QUARTER 17-18-10