

**NORTH 1/16TH CORNER SOUTHWEST QUARTER SECTION 17, TOWNSHIP 18 SOUTH,
RANGE 10 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 61 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 209 DATED JULY 12, 1872 TO ESTABLISH THE CENTER CORNER AND THE 1/2/4 AND 1/4/4 CORNERS IN THE NORTHWEST 1/4 OF SECTION 17-18-10, SAID THAT **HE SET A STONE MARKED "1/16"** FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 17-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17-18-10 AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 17-18-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:
- 1) 1,336' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17-18-10
 - 2) 1,336' EAST TO THE STONE MARKED "C+" HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 17-18-10
 - 3) 1,333-1/2' NORTH BY NOTES [1,333' ON DRAWING] TO THE STONE MARKED "1/16" HE SET FOR THE PERMANENT 1/4/4 CORNER IN THE CENTER OF THE NW1/4 OF SECTION 17-17-10
 - 4) 2,667' NORTH BY NOTES [2,666' ON DRAWING] TO THE STONE MARKED "1/16" HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 17-18-10

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 17-18-10