

**WEST 1/16TH CORNER NORTHWEST QUARTER SECTION 17, TOWNSHIP 18 SOUTH,
RANGE 10 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 61 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 209 DATED JULY 12, 1872 TO ESTABLISH THE CENTER CORNER AND THE 1/2/4 AND 1/4/4 CORNERS IN THE NORTHWEST 1/4 OF SECTION 17-18-10, SAID THAT **HE SET A STONE MARKED "1/16"** FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NORTHWEST 1/4 OF SECTION 17-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-18-10 AND THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17-18-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 17-18-10
 - 2) 1,323' SOUTH TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 17-18-10
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, BY C. H. RICE, DEPUTY COUNTY SURVEYOR. IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 124 DATED APRIL 6, 1882 AT THE REQUEST OF L. HERR TO ESTABLISH IN TOWNSHIP 18, RANGE 10, THE 1/4 AND 1/8 CORNERS ON THE NORTH LINE OF SECTION 18-18-10 AND THE CENTER AND 1/8 CORNERS ON THE LINE RUNNING THROUGH THE CENTER OF THE SECTION EAST TO WEST, AND ALL OTHER LINES AND CORNERS THAT MAY BE NECESSARY TO COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 18-18-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 20.08-3/4 CHAINS NORTH TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 18-18-10
 - 2) 80.35 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 7-18-10
- 3) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 36 TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS OF THE SOUTHWEST AND THE SOUTHEAST QUARTERS OF SECTION 19-18-10 THAT BEGAN ON JANUARY 13, 1958 AND CARRIED ON AT INTERVALS, WITH SEVERAL POSTPONEMENTS UNTIL COMPLETED, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 18-18-10 ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 4,005' SOUTH TO THE OLD TRUCK AXLE HE DROVE FOR THE PERMANENT NORTHEAST CORNER OF SECTION 19-18-10
- 2) 6,663' SOUTH TO BROKEN TRUCK AXLE HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 19-19-10, THAT FALLS ON THE PRESENT EAST AND WEST FENCE LINE AND 17.5 FEET EAST OF THE STONE CORNER POST
- 3) 9,321' SOUTH TO THE 18" X 8" X 6" LIMESTONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 19-18-10
- 4) 11,964' SOUTH TO THE STONE HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 30-18-10
- 5) 14,609.5' SOUTH TO THE REMAINS OF THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 31-18-10
- 6) 19,944.5' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 31-18-10 ON THE TOWNSHIP LINE

WEST SIXTEENTH CORNER NORTHWEST QUARTER 17-18-10