

CENTER CORNER SECTION 19, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 53 RECORDED IN SURVEY BOOK "A" ON PAGE 152 DATED MAY 21, 1868 FOR A SURVEY OF CALDWELL'S LAND, BEING THE SOUTHWEST 1/4 AND THE SOUTH 1/2 OF THE NORTHWEST 1/4, AND THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 19-18-10, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 19-18-10 ON LINE BETWEEN THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 19-19-10 AND THE STONE THAT HE SET FOR THE WEST 1/4 CORNER OF SECTION 19-19-10 ON THE RANGE LINE, AND AT 160 RODS WEST OF THE EAST 1/4 CORNER OF SECTION 19-18-10 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS EAST TO THE STONE HE SET FOR THE SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 19-18-10
 - 2) 160 RODS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 19-18-10
 - 3) 160 RODS, 8 LINKS SOUTH TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 19-18-10
 - 4) 145 RODS, 11 LINKS WEST TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 19-18-10 ON THE RANGE LINE
 - 5) 80 RODS, 4 LINKS NORTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 19-18-10
 - 6) 160 RODS, 8 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 19-18-10
- 2) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 36 TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS OF THE SOUTHWEST AND THE SOUTHEAST QUARTERS OF SECTION 19-18-10 THAT BEGAN ON JANUARY 13, 1958 AND CARRIED ON AT INTERVALS, WITH SEVERAL POSTPONEMENTS UNTIL COMPLETED, SAID THAT **HE SET THE PERMANENT CENTER CORNER** OF SECTION 19-18-10 AT THE POINT OF INTERSECTION OF THE NORTH & SOUTH AND EAST & WEST 1/2 SECTION LINES ON THIS **PERMANENT SURVEY**. HE DID NOT INDICATE WHAT HE SET FOR THE PERMANENT CENTER CORNER AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

CENTER CORNER 19-18-10