

NORTH 1/4 CORNER SECTION 22, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) ON PAGE 177 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 17" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 22-18-10.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST TO THE 34" X 18" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-18-10
 - 2) 40.00 CHAINS EAST TO THE 31" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-18-10

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 146 DATED JANUARY 31, 1883 TO ESTABLISH THE CENTER OF SECTION 15-18-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-18-10 ON THIS **INFORMAL SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 79.67 CHAINS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER SECTION 15-18-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 108, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 88 DATED JUNE 1, 2 & 3, 1886 FOR A ROAD IN TOWNSHIP 18, RANGE 10 FOR J. D. FOX, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE OR SET A MILE STONE** AT THE SOUTHWEST CORNER OF SECTION 15-18-10 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINE.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-18-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 14-18-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 4) MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 343 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 322 TO 323 PETITION BY J. D. FOX AND OTHERS FOR A THE LOCATION AND VACATION OF A ROAD IN TOWNSHIP 18-10 [PACKET 566 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 1, 1886, WAS ESTABLISHED AS A 40 FOOT WIDE ROAD, BEING 20 FEET ON EACH SIDE OF THE SECTION LINE, AND THE REPORT OF THE ROAD VACATION WAS **REJECTED** ON OCTOBER 20, 1886 AS NOTED BY T. E. McMILLAN, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND WAS RECORDED ON MARCH 11, 1887 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE OR SET A MILE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 15-18-10 ON THIS ROAD SURVEY. BROWN NOTED THAT "MILE STONES SET IN THEIR RESPECTIVE PLACES".
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE "PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-18-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2 MILES "PER GOVERNMENT SURVEY" TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 14-18-10 AT THE TERMINUS OF THIS ROAD SURVEY

NORTH QUARTER CORNER 22-18-10