

**WEST 1/4 CORNER SECTION 22, TOWNSHIP 18 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 176 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 16" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 22-18-10.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 119 RECORDED IN SURVEY BOOK "A" ON PAGES 206 & 207 AND CONTINUED AT THE BOTTOM OF PAGE 208 DATED MAY 22 & 27, 1869 TO SURVEY THE EAST 1/2, AND THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4, AND THE SOUTHWEST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 21-18-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 21-18-10 ON THIS SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 157 RODS WEST TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 21-18-10
  - 2) 236 RODS, 3-1/2 LINKS WEST TO THE STONE HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 21-18-10
  - 3) 315 RODS, 7 LINKS WEST TO THE STONE FOUND AT THE WEST 1/4 CORNER OF SECTION 21-18-10
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A SURVEY NUMBER 70 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 127 DATED APRIL 2, 1875 TO ESTABLISH THE CORNER TO SECTIONS 9-10-15 & 16 AND THE 1/4 CORNER BETWEEN SECTIONS 9 & 10 IN TOWNSHIP 18, RANGE 10, APPARENTLY **FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 22-18-10 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 10-18-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 22-18-10 AND HE STATED THAT "THE LAST 1/2 MILE MEASURES 2,763 FEET" ON THIS **PERMANENT SURVEY**.
- 4) INFORMATION FROM A SHEET FROM "GREAT PLAINS ENGINEERS & SURVEYORS", P.O. BOX 40, EMPORIA, DATED MAY 28, 1982 IN THE SURVEY DRAWER WITH NO CHIEF OF PARTY LISTED AND NO INITIALS ON THE SHEET SHOWS THAT **THEY SET A 1/2" IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 22-18-10. **[NOTE: POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, INFORMED ME THAT THIS WAS PROBABLY GREGORY ALAN MILES, L.S. 667 - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] VERIFY AND CHECK FOR THE STONE OF RECORD AS THERE WAS NO INDICATION OF THE METHODOLOGY HE USED TO SET THIS IRON PIN!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
  - 1) 4.87' ENE TO A NAIL IN THE BASE OF A FENCE POST
  - 2) 21.46' WEST TO A NAIL IN THE TOP OF A CORNER FENCE POST
  - 3) 30.47' NW TO A NAIL IN THE TOP OF A CORNER FENCE POST
  - 4) 1.90' SOUTH OF AN EXISTING FENCE
  - 5) 6.50' EAST OF THE CENTERLINE OF THE OLD TRAVELED-WAY RUNNING NORTH
  - 6) 8.00' EAST OF THE CENTERLINE OF THE OLD TRAVELED-WAY RUNNING SOUTH

WEST QUARTER CORNER 22-18-10