

CENTER CORNER SECTION 29, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2000, FOR PROJECT NUMBER 00146-02, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THE SOUTHEAST 1/4 AND A SUBDIVISION OF THE NORTHEAST 1/4 OF SECTION 29-18-10, SAID THAT **SHE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER CORNER OF SECTION 29-18-10 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS.
 - 1) 8.05' SSW TO A MASONRY NAIL & BOTTLECAP IN THE EAST BRACE POST FOR A FENCE
 - 2) 13.30' SW TO A MASONRY NAIL & BOTTLECAP IN AN INTERSECTION POST OF THE FENCE
 - 3) 12.45' SE TO THE NORTHWEST CORNER [AT THE BASE] OF A STONE POST ROCK
 - 4) 13.85' NORTH TO A MASONRY NAIL & BOTTLECAP IN A 12" DIAMETER HONEY LOCUST TREE
 - 5) 8.0' SOUTH TO A LINE OF FENCE TO THE EAST AND WEST
 - 6) 11.0' WEST TO A LINE OF FENCE TO THE NORTH AND SOUTH
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,640.42' WEST TO THE STONE SHE FOUND AT THE WEST 1/4 CORNER OF SECTION 29-18-10 WITH A 5/8" REBAR WITH A LYON COUNTY CAP SHE SET ON THE NORTH SIDE OF THE STONE
 - 2) 1,324.96' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 29-18-10
 - 3) 2,649.91' NORTH TO THE 5/8" REBAR SHE FOUND AT THE NORTH 1/4 CORNER OF SECTION 29-18-10
 - 4) 1,321.96' FEET EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTH 1/16TH CORNER OF THE NE1/4 OF SECTION 29-18-10
 - 5) 2,643.92' EAST TO THE 1/2" REBAR SHE FOUND AT THE EAST 1/4 CORNER OF SECTION 29-18-10
 - 6) 2,653.01' SOUTH TO THE 1/2" REBAR WITH "LS 752" CAP SHE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-18-10

CENTER CORNER 29-18-10