

NORTH 1/4 CORNER SECTION 29, TOWNSHIP 18 SOUTH, RANGE 10 EAST

- 1) ON PAGE 184 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-18-10.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.09 CHAINS WEST TO THE 32" X 16" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-18-10
- 2) 40.09 CHAINS EAST TO THE 28" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-18-10

- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE PAGE 167 DATED JUNE 27, 1879, FOR A COUNTY ROAD IN TOWNSHIPS 18-10 AND 19-10, APPARENTLY **FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-18-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640' EAST ON THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-18-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO A POINT 7,813' SOUTH OF THE NORTH 1/4 CORNER OF SECTION 8-19-10, WITH DEVIATIONS DUE TO GROWING HEDGES

- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 27 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 106 TO 108 PETITIONED BY C. C. LYNCH AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 18-10 AND 19-10 [PACKET 111 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 24, 1879, WAS ESTABLISHED AT A 40 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 15, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 29-18-10 ON THIS ROAD SURVEY. SEE THE SURVEY NOTES FOR LOCATIONS WHERE THE RIGHT-OF-WAY LINE CHANGED DUE TO HEDGE FENCES.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2,640 FEET TO THE NORTHEAST CORNER OF SECTION 29-18-10 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO A POINT ON THE WEST LINE OF THE EAST 1/2 OF SECTION 17-19-10 ON THE NORTH BANK OF THE COTTONWOOD RIVER TO COMMENCE THIS ROAD SURVEY

- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 30, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 30 DATED MAY 9, 1884 AT THE REQUEST OF N. CAMPBELL, W. BRISLIN, AND CARLYSLE TO ESTABLISH THE NORTH LINE OF SECTION 29 AND THE NORTH, SOUTH AND EAST LINES OF SECTION 30, ALL IN TOWNSHIP 18-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 29-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-18-10 AND THE STONE THAT HE RESET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 29-18-10 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS FILED MAY 17, 1884 AND RECORDED JANUARY 17, 1887 IN VOLUME 41 ON PAGE 16 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY F29002 IN THE SURVEY FILE FOR TOWNSHIP 18-10.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1323' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-18-10
 - 2) 2,646' WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 29-18-10
 - 3) 5,286' WEST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-18-10
 - 4) 7,790' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-18-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
 - 5) 1,323' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4/4 CORNER OF THE NORTHEAST CORNER OF SECTION 29-18-10
 - 6) 2,646' EAST TO THE STONE HE FOUND DOWN AT THE NORTHEAST CORNER OF SECTION 29-18-10 AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 29-18-10, AFTER HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-18-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-18-10
 - 7) 5,288' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 28-18-10
 - 8) 7,883' EAST TO THE STONE HE FOUND DOWN AT THE NORTHEAST CORNER OF SECTION 28-18-10, BUT EVIDENTLY IN THE RIGHT PLACE AS IT CORRESPONDS WITH THE FENCES BUILT YEARS BEFORE
 - 9) 10,509' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 27-18-10
 - 10) 11,921.5' EAST TO THE STONE HE FOUND AT THE NORTH 1/4/4 CORNER OF THE NE1/4 OF SECTION 27-18-10
 - 11) 13,234' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-18-10
- 5) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 59
ON APRIL 12, 1919 A PETITION SIGNED BY W. H. COLLINS AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 18-10 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON MAY 14, 1919, AND THE FINAL ORDER WAS ISSUED TO VACATE THE FOLLOWING ROAD:
- 1) BEGINNING ON THE SOUTH LINE OF THE CENTER OF SECTION 29-18-10; FROM THENCE NORTH ONE MILE, BEING THE ROAD IN THE CENTER OF SAID SECTION 29, AND TERMINATING AT THE NORTH LINE THEREOF, IN AMERICUS TOWNSHIP
- 6) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 704 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 61 PETITIONED BY W. H. COLLINS AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 18-10 [PACKET 854 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON MAY 14, 1919 AND WAS ORDERED ON JUNE 5, 1919 THAT THE ROAD BE VACATED AS PETITIONED FOR: BEGINNING ON THE SOUTH LINE OF THE CENTER OF SECTION 29-18-10; FROM THENCE NORTH ONE MILE, BEING THE ROAD IN THE CENTER OF SAID SECTION 29, AND TERMINATING AT THE NORTH LINE THEREOF, AS NOTED BY C. A. PAINE, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS.
- 7) **REA PIN—MUST VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR** REA BOOK 31 ON PAGE 12 SHOWS THAT **THEY DROVE AN IRON PIN** FOR THE NORTH 1/4 CORNER OF SECTION 29-18-10 AT 2,649.5 FEET EAST OF THE NORTHEAST CORNER OF SECTION 30-18-10.

- 1) 19' SOUTH TO A WITNESS PIN ABOUT 1' NORTH OF A FENCE POST
- 8) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 18-10 SHOWS A **REA PIN** AT THE "SW CORNER SE1/4 SECTION 20-18-10" AND AT THE "NW CORNER NE1/4 SECTION 29-18-10". **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN WAS PROBABLY JUST "HEELED-IN" FOR UTILITY USE ONLY! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR**
 - 1) 19' SOUTH TO AN IRON PIN
- 9) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2000, FOR PROJECT NUMBER 00146-02, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF THE SOUTHEAST 1/4 AND A SUBDIVISION OF THE NORTHEAST 1/4 OF SECTION 29-18-10, SAID THAT **SHE FOUND A 5/8" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 29-18-10. SHE SAID THAT THE ORIGIN WAS UNCERTAIN, BUT THAT IT WAS POSSIBLY FROM THE REA SURVEY, AS THESE ARE THE ONLY REFERENCE TIES ON FILE FOR THIS CORNER. THE PIN IS NOT SQUARE, WHICH COULD CAST DOUBT ON IT BEING AN REA CORNER.
 - 1) THE IRON PIN IS 1.25' DEEP IN THE GRAVEL ROAD SURFACE OF COUNTY ROAD 210
 - 2) IN LINE WITH A FENCE TO THE SOUTH
 - 3) 22.25' NW TO A MASONRY NAIL & BOTTLECAP IN A WOOD FENCE POST
 - 4) 19.15' SOUTH TO A MASONRY NAIL & BOTTLECAP IN A CORNER FENCE POST
 - 5) 20.85' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 6) 1.80' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 210 EAST-WEST
 - 7) 4.50' WEST TO A LINE OF POWER POLES RUNNING SOUTH

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,647.90' WEST TO THE STONE SHE FOUND AT THE NORTHWEST CORNER OF SECTION 29-18-10
 - 2) 1,324.95' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE WEST 1/16TH CORNER OF THE NE1/4 OF SECTION 29-18-10
 - 3) 2,649.91' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE CENTER CORNER OF SECTION 29-18-10
 - 4) 5,302.92' SOUTH TO THE 1/2" REBAR WITH A "LS 752" CAP SHE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 29-18-10
 - 5) 1,323.95' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTH 1/16TH CORNER OF THE NE1/4 OF SECTION 29-18-10
 - 6) 2,647.89' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTHEAST CORNER OF SECTION 29-18-10
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 4, 2011 FOR PROJECT NUMBER 11066-02, A SURVEY FOR MITCH SHIVERS IN THE SOUTHWEST 1/4 OF SECTION 29, SURVEY F29006 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SAID THAT **HE FOUND THE 5/8" REBAR** AT THE NORTH 1/4 CORNER OF SECTION 29-18-10 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, DATED DECEMBER 2000.
 - 1) IN LINE WITH THE FENCE TO THE SOUTH
 - 2) 19.15' SOUTH TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
 - 3) 20.85' SW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 1.80' SOUTH TO THE CENTER OF THE TRAVELED WAY OF COUNTY ROAD 210 EAST-WEST
 - 5) 4.50' WEST TO A LINE OF POWER POLES RUNNING SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 4

- 1) 4,847.23' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST TRACT CORNER
- 2) 5,303.23' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 29-18-10

NORTH QUARTER CORNER 29-18-10