

**NORTH 1/4 CORNER SECTION 30, TOWNSHIP 18 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 185 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 15" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-18-10.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 39.89 CHAINS WEST TO THE 27" X 7" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-18-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
  - 2) 40.00 CHAINS EAST TO THE 32" X 16" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-18-10
  
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 53 RECORDED IN SURVEY BOOK "A" ON PAGE 152 DATED MAY 21, 1868 FOR A SURVEY OF CALDWELL'S LAND, BEING THE SOUTHWEST 1/4 AND THE SOUTH 1/2 OF THE NORTHWEST 1/4, AND THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 19-18-10, SAID THAT **HE SET A STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 19-18-10 AT 160 RODS WEST OF THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-18-10 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 160 RODS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 19-18-10
  - 2) 147 RODS, 4 LINKS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 19-18-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
  - 3) 160 RODS, 8 LINKS NORTH TO THE STONE HE SET FOR THE CENTER CORNER OF SECTION 19-18-10
  - 4) 240 RODS, 12 LINKS NORTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 19-18-10
  - 5) 320 RODS, 16 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 19-18-10
  
- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 30, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 30 DATED MAY 9, 1884 AT THE REQUEST OF N. CAMPBELL, W. BRISLIN, AND CARLYSLE TO ESTABLISH THE NORTH LINE OF SECTION 29 AND THE NORTH, SOUTH AND EAST LINES OF SECTION 30, ALL IN TOWNSHIP 18-10, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-18-10 AT 2,640' WEST OF THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-18-10 ON THIS **PERMANENT SURVEY**. THIS SURVEY WAS FILED MAY 17, 1884 AND RECORDED JANUARY 17, 1887 IN VOLUME 41 ON PAGE 16 IN THE REGISTER OF DEEDS OFFICE, AND SURVEY F29002 IN THE SURVEY FILE FOR TOWNSHIP 18-10.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,504' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-18-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
  - 2) 2,640' EAST TO THE STONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 30-18-10
  - 3) 3,963' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 29-18-10
  - 4) 5,286' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 29-18-10
  - 5) 6,609' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4/4 CORNER OF THE NE1/4 OF SECTION 29-18-10
  - 6) 7,932' EAST TO THE STONE HE FOUND DOWN AT THE NORTHEAST CORNER OF SECTION 29-18-10 AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER

- OF SECTION 29-18-10, AFTER HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 20-18-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-18-10
- 7) 10,574' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 28-18-10
  - 8) 13,169' EAST TO THE STONE HE FOUND DOWN AT THE NORTHEAST CORNER OF SECTION 27-18-10, BUT APPARENTLY IN THE RIGHT PLACE AS IT CORRESPONDS WITH THE FENCES BUILT YEARS BEFORE
  - 9) 15,795' EAST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 27-18-10
  - 10) 17,207.5' EAST TO THE STONE HE FOUND AT THE NORTH 1/4/4 CORNER OF THE NE1/4 OF SECTION 27-18-10
  - 11) 18,520' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 27-18-10
- 4) LESLIE M. GOULD, L.S 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 36 TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS OF THE SOUTHWEST AND THE SOUTHEAST QUARTERS OF SECTION 19-18-10 THAT BEGAN ON JANUARY 13, 1958 AND CARRIED ON AT INTERVALS, WITH SEVERAL POSTPONEMENTS UNTIL COMPLETED, SAID THAT **HE SET AN OLD TRUCK AXLE** FOR THE PERMANENT SOUTH 1/4 OF SECTION 19-18-10 ON THIS **PERMANENT SURVEY** BY SINGLE PROPORTIONATE MEASUREMENT "SET ACCORDING TO SPECIFIC INSTRUCTIONS WHICH MAY BE FOUND IN PARAGRAPH 376 PAGE 298 OF THE MANUAL OF SURVEYING INSTRUCTIONS 1947 ISSUED BY THE DEPT. OF INTERIOR, BUREAU OF LAND MANAGEMENT". HE NOTED THAT THIS OLD TRUCK AXLE FELL 62 FEET EAST OF THE PRESENT FENCE CORNER. SEE HIS NOTES FOR WHY HE DID NOT SET THIS STONE AT 2,640' WEST OF THE NORTHEAST CORNER OF SECTION 30-18-10 AS McAULEY AND EDMISTON.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,575' WEST TO THE IRON PIN HE DROVE FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 19-18-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
  - 2) 2,582' EAST TO THE 18" X 8" X 6" LIMESTONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 19-18-10

NORTH QUARTER CORNER 30-18-10