

**NORTH 1/16TH CORNER NORTHEAST QUARTER SECTION 34, TOWNSHIP 18 SOUTH,
RANGE 10 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 65 RECORDED IN SURVEY BOOK "F" ON PAGE 145 DATED JANUARY 27, 1903, A **PERMANENT SURVEY** AT THE REQUEST OF S. R. LEWIS FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 34-18-10 AND RUN SUCH LINES AS MAY BE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE SET A 15" X 12" X 6" STONE** FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 34-18-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 34-18-10 AND THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-18-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN BOOK NUMBER 3 ON PAGE 112 IN THE "KRETSINGER COLLECTION". THERE IS ADDITIONAL INFORMATION IN PACKET "M 163" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.85 CHAINS EAST TO THE 20" X 10" X 8" STONE MARKED "X" ON THE WEST SIDE HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 34-18-10
 - 2) 19.85 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-18-10
 - 3) 39.80 CHAINS WEST TO THE STONE HE FOUND AT THE NORTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 34-18-10
 - 4) 59.72 CHAINS WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-18-10
 - 5) 16.89 CHAINS SOUTH TO THE PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
 - 6) 30.39 CHAINS SOUTH TO THE PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
 - 7) 40.52 CHAINS SOUTH TO THE STONE HE SET FOR TH PERMANENT SOUTH 1/2/4 STONE OF THE NE1/4 OF SECTION 34-18-10
 - 8) 50.66-1/2 CHAINS SOUTH TO THE PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
 - 9) 60.81 CHAINS SOUTH TO THE PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
 - 10) 70.95-1/2 CHAINS SOUTH TO THE PERMANENT PROPERTY STONE HE SET ON THIS SURVEY
 - 11) 81.10 CHAINS SOUTH TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 OF THE SE1/4 OF SECTION 34-18-10 ON THE TOWNSHIP LINE
- 2) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 17, 1983, SAID THAT **HE FOUND A 6" X 12" LIMESTONE AT 16" DEEP** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 34-18-10 THAT WAS SET BY ALVA J. SMITH IN 1903 IN SURVEY BOOK "F" ON PAGE 145. **HE DROVE 5/8" CAPPED REBARS ON THE NORTH AND SOUTH SIDES OF THE STONE, AND HE SET A 5/8" X 12" CAPPED REBAR OVER A DRILL HOLE THAT HE MADE IN THE STONE.**
- 1) 24.3' SOUTH TO A LINE OF POWER POLES EAST-WEST
 - 2) 30.6' NORTH TO A LINE OF FENCES EAST & WEST
 - 3) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST & WEST
- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 7, 2005, FOR PROJECT NUMBER 05387-02, SURVEY F34003 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A 10.0 ACRE TRACT IN THE NORTH 1/2 OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 AND THE

SOUTH 1/2 OF THE SOUTH 1/2 OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 34-18-10 FOR RON SWINT, SAID THAT **HE FOUND THE 6" X 12" LIMESTONE THAT WAS SET BY ALVA J. SMITH IN A 1903 PERMANENT SURVEY WITH A 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE STONE** AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 34-18-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE IN 1983.

- 1) 34.2' WSW TO THE TOP CENTER OF AN OEM SIGN POST
- 2) 44.5' WNW TO THE TOP CENTER OF AN OEM SIGN POST
- 3) 43.0' WEST TO THE CENTERLINE OF A CORRUGATED METAL PIPE CULVERT UNDER THE ROAD
- 4) 43.3' SE TO A 40 D NAIL & WASHER IN A POWER POLE
- 5) 30.6' NORTH TO A LINE OF FENCES EAST AND WEST
- 6) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 200 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,308.05' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 34-18-10
- 2) 2,506.01' SOUTH TO THE THEORETICAL POSITION OF THE NORTHWEST CORNER OF THE S1/2 OF THE S1/2 OF THE S1/2 OF THE SE1/4 OF THE NE1/4 OF SECTION 34-18-10
- 3) 2,673.08' SOUTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 34-18-10 THAT WAS SET BY ALVA J. SMITH IN A 1903 PERMANENT SURVEY
- 4) 5,351.29' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 34-18-10 ON THE TOWN-SHIP LINE

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 8, 2008 FOR PROJECT NUMBER 08203-02, SURVEY F34004 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A SURVEY OF A 2.57 ACRE TRACT IN THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 34-18-10 FOR RODGER HARGETT, SAID THAT **HE FOUND THE 6" X 12" LIMESTONE THAT WAS SET BY ALVA J. SMITH IN A 1903 PERMANENT SURVEY WITH A 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE STONE** AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 34-18-10 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE BY HIM IN 2005.

- 1) 34.2' WSW TO THE TOP CENTER OF AN OEM SIGN POST
- 2) 44.5' WNW TO THE TOP CENTER OF AN OEM SIGN POST
- 3) 43.0' WEST TO THE CENTERLINE OF A CORRUGATED METAL PIPE CULVERT UNDER THE ROAD
- 4) 43.3' SE TO A 40 D NAIL & WASHER IN A POWER POLE
- 5) 30.6' NORTH TO A LINE OF FENCES EAST-WEST
- 6) 1' NORTH TO THE CENTERLINE TRAVELED-WAY OF GRAVEL COUNTY ROAD 200 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,308.05' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 34-18-10
- 2) 2004.81' [C] TO THE THEORETICAL POSITION OF THE NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF THE NE1/4 OF SECTION 34-18-10
- 3) 2,673.08' SOUTH TO THE STONE FOUND FROM A PRIOR SURVEY AT THE SOUTHWEST CORNER OF THE E1/2 OF THE NE1/4 OF SECTION 34-18-10

CONTINUED ON PAGE 3

5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 3, 2011 FOR PROJECT NUMBER 11126-02, A SURVEY FOR LYON COUNTY RURAL WATER DISTRICT NUMBER 2 IN THE NORTHEAST 1/4 OF SECTION 34, SURVEY F34005 IN THE SURVEY FILE FOR TOWNSHIP 18-10, SAID THAT **HE FOUND THE 6" X 12" LIMESTONE WITH THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE TOP CENTER OF THE STONE AT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 34-18-10 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYOR'S OFFICE. HE NOTED THAT HE HAD FOUND THE STONE IN 1983 AND HE HAD SET THE 5/8" CAPPED REBAR OVER THE STONE. [NOTE: THE STONE WAS SET BY ALVA J. SMITH, COUNTY SURVEYOR, IN A PERMANENT SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 145 IN 1903. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

- 1) 34.5' WSW TO THE TOP CENTER OF AN OEM SIGN POST
- 2) 44.5' WNW TO THE TOP CENTER OF AN OEM SIGN POST
- 3) 43.0' WEST TO THE CENTERLINE OF A CMP UNDER THE ROAD
- 4) 43.0' SE TO A 40 D NAIL & WASHER IN A POWER POLE
- 5) 30.6' NORTH TO A LINE OF FENCES EAST-WEST
- 6) 1' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 200 EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,308.11' EAST TO THE 5/8" CAPPED REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 34-18-10
- 2) 1,310.10' WEST TO THE 5/8" CAPPED REBAR HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 34-18-10

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 34-18-10