

**NORTH 1/16TH CORNER SOUTHEAST QUARTER SECTION 35, TOWNSHIP 18 SOUTH,
RANGE 10 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 30, 2010 FOR PROJECT NUMBER 10163-02, SURVEY F35005 IN THE SURVEY FILE FOR TOWNSHIP 18-10 FOR A TRACT IN THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 35-18-10 FOR JOHN NEWLAND, SAID THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 35-18-10 TO BE ON LINE AND HALFWAY BETWEEN THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 35-18-10 AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF THE NORTHEAST 1/4 OF SECTION 35-18-10 THAT WAS SET BY ALVA J. SMITH. THIS POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.48' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 35-18-10 THAT WAS SET BY ALVA J. SMITH IN 1903
- 2) 1,323.48' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 35-18-10
- 3) 3,951.24' WEST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE **NE1/4** OF SECTION 35-18-10 [**NOTE:** THIS SHOULD BE THE SOUTHWEST CORNER OF THE **NW1/4** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 4) 1,027.74' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR A CORNER OF A 10 ACRE TRACT
- 5) 1,327.74' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF THE NE1/4 OF SECTION 35-18-10
- 6) 2,655.48' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF THE NE1/4 OF SECTION 35-18-10 THAT WAS SET BY ALVA J. SMITH

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 35-18-10