

**WEST 1/16TH CORNER NORTHWEST QUARTER SECTION 35, TOWNSHIP 18 SOUTH,  
RANGE 10 EAST**

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 145 AND DATED JANUARY 1903, SAID THAT **HE SET A STONE** FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 35-18-10 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK NUMBER 3 ON PAGE 112 IN THE "KRETSINGER COLLECTION". THERE IS ADDITIONAL INFORMATION IN PACKET "M 163" IN MISCELLANEOUS DRAWER 8 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.
  
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 7, 2005, FOR PROJECT NUMBER 05387-02, SAID THAT **HE FOUND A LIMESTONE WITH A DRILL HOLE IN THE TOP OF THE STONE** AT THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 34-18-10 FROM A 1903 PERMANENT SURVEY BY ALVA J. SMITH FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE BY HIM IN 1983.
  - 1) 53.9' NNW TO A SPIKE & WASHER IN A POWER POLE
  - 2) 60.7' SSW TO A SPIKE & WASHER IN A POWER POLE
  - 3) 50.3' SSE TO A 1/2" REBAR HE FOUND AT THE RIGHT-OF-WAY LINE OF COUNTY ROAD "E"
  - 4) 22.8' EAST TO A LINE OF HEDGE NORTH-SOUTH
  - 5) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "E" NORTH-SOUTH

WEST SIXTEENTH CORNER NORTHWEST QUARTER 35-18-10